

LED

LED Wall Pack

Applications – Security, pathway and perimeter lighting; ideal for entry ways, walkways and parking facilities.

Typical Mounting Height: 8 to 15 feet **Typical Spacing:** 1 to 2 times the mounting height

NEW!



7-1/4"H x 8-1/2"W x 7-1/4"D
Weight: 3 lbs.



NEUTRAL WHITE (4000K)

**27-watt LED,
1375 Delivered Lumens
(Comparable to 100W Incandescent)**

CAT.# E-WP1X031Z7

Accessories



CAT.# E-ACP1
(120 volts)

*Photocell is field installed.
Drilling of the housing in the field is required.*

Features:

- 25,000 hours of maintenance-free operation
- 120-volt operation
- Non-dimmable
- Sturdy die-cast aluminum housing and lens frame, with dark-bronze polyester powder-coat finish
- Minimum starting temperature: -40° F
- UV stabilized prismatic polycarbonate refractor
- One-piece anodized aluminum reflector
- 3/8-inch NPT tapped back and two sides for conduit entrances
- Optional photocell available
- RoHS compliant
- Cree LEDs inside
- UL Listed for wet locations
- 3-year warranty

LED Wall Mount

Applications – Security, entry ways, stairways, storage and perimeter areas, as well as residential exteriors.

Typical Mounting Height: 8 to 18 feet **Typical Spacing:** 1.5 to 2 times the mounting height

NEW!



9"H x 5-3/4"W x 4"D
Weight: 2 lbs.



WARM WHITE (3000K)

**14-watt LED,
675 Delivered Lumens
(Comparable to 65W Incandescent)**

Bronze CAT.# E-WW1X011Z3
White CAT.# E-WW1X011W3

WARM WHITE (3500K)

**21-watt LED,
1200 Delivered Lumens
(Comparable to 100W Incandescent)**

Bronze CAT.# E-WW1X021Z3
White CAT.# E-WW1X021W3

Features:

- 25,000 hours of maintenance-free operation
- 120-volt operation
- Non-dimmable
- Built-in photocell
- Polycarbonate housing in bronze or white with heavy-duty aluminum mounting plate
- 1/2-inch NPT tapped back and bottom for conduit entrances
- Minimum starting temperature: -40° F
- UV-stabilized polycarbonate prismatic refractor
- RoHS compliant
- Cree LEDs inside
- UL Listed for wet locations
- 3-year warranty