

PROPOSED LEGEND

Table with 2 columns: Symbol and Description. Includes entries for PROPERTY LINE, BUILDING SETBACK LINE, LANDSCAPE BUFFER LINE, TRENCH CURB, TRENCH CURB BY OTHERS, TYPE "F" CURB, BUILDING, CONCRETE PAVEMENT, CONCRETE SIDEWALK, ASPHALT PAVEMENT, 3' WIDE MILL AND OVERLAY, TRAFFIC ARROW, PARKING COUNT SYMBOL, SITE LIGHTING POLE, FLOW LINE, SLOPE AND FLOW ARROW, SPOT ELEVATION, DRAINAGE STRUCTURE CALLOUT, STORM WATER PIPE, STORM CATCH BASIN, STORM CLEANOUT, LIMITS OF SUB-BASIN, RIDGE LINE, YARD DRAIN, EXISTING CONTOUR, PROPOSED CONTOUR, UNDERGROUND ELECTRIC, UNDERGROUND TELEPHONE, NATURAL GAS LINE, SANITARY SEWER, WATER MAIN, UNDERGROUND LIGHTING SCHEMATIC, IRRIGATION SLEEVE, REUSE WATER MAIN, SANITARY SEWER CLEANOUT, SANITARY SEWER STRUCTURE SYMBOL, GROUND TO BE CLEARED AND GRUBBED, CONCRETE CURB TO BE REMOVED, UTILITY CONDUIT/PIPE TO BE REMOVED, LIMITS OF SAWCUT AND PAVEMENT REMOVAL, LIMITS OF DISTURBANCE, DIRECTION OF OVERLAND FLOW, TEMPORARY SILT FENCE, SILT DIKE ON PAVEMENT, SWPPP INFORMATION SIGN, CONSTRUCTION EXIT, TEMPORARY INLET PROTECTION.

EXISTING LEGEND

Table with 2 columns: Symbol and Description. Includes entries for SITE BENCHMARK, FOUND MONUMENT (AS NOTED), SANITARY MANHOLE, CLEANOUT, STORM INLET (RECTANGLE), IRRIGATION CONTROL VALVE, LIGHT POLE, ELECTRIC METER, ELECTRIC TRANSFORMER, UTILITY POLE, A/C UNIT, MONITOR WELL, HANDICAP PARKING, REGULAR PARKING SPACES, PILLAR, DECIDUOUS TREE, PALM TREE, LANDSCAPED AREA, BOLLARD, SIGN, STORM LINE (UNDERGROUND), SANITARY LINE (UNDERGROUND), WATER LINE (UNDERGROUND), GAS LINE (UNDERGROUND), ELECTRIC LINE (UNDERGROUND), ELECTRIC LINE (OVERHEAD), FIBEROPTIC LINE (UNDERGROUND), TELEPHONE LINE (UNDERGROUND), PLASTIC FENCE, CONCRETE AREA, MEASURED, RECORD, POLYVINYL CHLORIDE PIPE, CORRUGATED METAL PIPE.

STANDARD ABBREVIATIONS

Table with 2 columns: Abbreviation and Full Name. Includes entries like AC ACRES, ADA AMERICANS WITH DISABILITY ACT, BC BOTTOM OF CURB, BL BASELINE, BLDG BUILDING, BOL BOLLARD, BM BENCH MARK, BRL BUILDING RESTRICTION LINE, CF CUBIC FEET, CL CENTERLINE, CMP CORRUGATED METAL PIPE, CONC CONCRETE, CPP CORRUGATED PLASTIC PIPE, CY CUBIC YARDS, DIP DUCTILE IRON PIPE, DMH DRAINAGE MANHOLE, ELEC ELECTRIC, ELEV ELEVATION, EP EDGE OF PAVEMENT, ES EDGE OF SHOULDER, EX EXISTING, FES FLARED END SECTION, FFE FINISH FLOOR ELEVATION, FH FIRE HYDRANT, FG FINISHED GRADE, GC GRADE CHANGE, GV GATE VALVE, HDPE HIGH DENSITY POLYETHYLENE PIPE, HH HANDHOLE, HP HIGH POINT, HOR HORIZONTAL, HW HEADWALL, INT INTERSECTION, INV INVERT, LF LINEAR FOOT, LOD LIMITS OF DISTURBANCE, LOW LOW POINT, ME MATCH EXISTING, MAX MAXIMUM, MIN MINIMUM, MJ MECHANICAL JOINT, OC ON CENTER, R RADIUS, RCP REINFORCED CONCRETE PIPE, ROW RIGHT OF WAY, S SLOPE, SG SPOT GRADE, SMH SANITARY MANHOLE, SAN SANITARY SEWER, SF SQUARE FEET, STA STATION, STM STORM, TC TOP OF CURB, TEL TELEPHONE, TG TOP OF GRATE, TP TOP OF PAVEMENT OR CONCRETE, TW TOP OF WALK, TYP TYPICAL, UG UNDERGROUND, UP UTILITY POLE, WL WATER LINE, WM WATER METER, ± PLUS OR MINUS, ° DEGREE, Ø DIAMETER.

GENERAL DEMOLITION NOTES:

- 1. THE CONTRACTOR IS RESPONSIBLE FOR THE DEMOLITION, REMOVAL AND DISPOSAL IN A LOCATION APPROVED BY ALL GOVERNING AUTHORITIES... 2. THE CONTRACTOR IS RESPONSIBLE FOR REMOVING ALL DEBRIS FROM THE SITE AND DISPOSING... 3. THE CONTRACTOR SHALL COORDINATE WITH RESPECTIVE UTILITY COMPANIES PRIOR TO THE REMOVAL AND/OR RELOCATION OF UTILITIES... 4. THE LOCATIONS OF ALL EXISTING UTILITIES SHOWN ON THIS PLAN HAVE BEEN DETERMINED FROM THE BEST INFORMATION AVAILABLE... 5. ALL EXISTING SEWERS, PIPING AND UTILITIES SHOWN ARE NOT TO BE INTERPRETED AS THE EXACT LOCATION... 6. ELECTRICAL, TELEPHONE, CABLE, WATER, FIBER OPTIC CABLE AND/OR GAS LINES NEEDING TO BE REMOVED OR RELOCATED SHALL BE COORDINATED WITH THE AFFECTED UTILITY COMPANY... 7. CONTRACTOR MUST PROTECT THE PUBLIC AT ALL TIMES WITH FENCING, BARRICADES, ENCLOSURES, ETC... 8. CONTINUOUS ACCESS SHALL BE MAINTAINED FOR THE SURROUNDING PROPERTIES AT ALL TIMES... 9. PRIOR TO DEMOLITION OCCURRING, ALL EROSION CONTROL DEVICES ARE TO BE INSTALLED... 10. SHOULD REMOVAL AND/OR RELOCATION ACTIVITIES DAMAGE FENCING, LIGHTING AND/OR ANY OTHER APPURTENANCES... 11. CONTRACTOR SHALL LIMIT SAW-CUT PAVEMENT REMOVAL TO ONLY THOSE AREAS WHERE IT IS REQUIRED AS SHOWN ON THESE CONSTRUCTION PLANS... 12. THE CONTRACTOR SHALL COORDINATE WATER MAIN WORK WITH THE FIRE DEPT. AND THE CITY/COUNTY UTILITY DEPARTMENT... 13. DAMAGE TO ALL EXISTING CONDITIONS SHOW TO REMAIN IN THESE PLANS WILL BE REPLACED AT CONTRACTORS EXPENSE.

GENERAL SITE NOTES:

- 1. ALL CONSTRUCTION MATERIALS AND TECHNIQUES OF INSTALLATION SHALL MEET PERFORMANCE VALUES OF THE MATERIALS SPECIFIED AND COMPLY WITH ALL CITY/COUNTY REGULATIONS AND O.S.H. STANDARDS... 2. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT THIS PROJECT IS CONSTRUCTED IN ACCORDANCE WITH THESE DOCUMENTS AND IN COMPLIANCE WITH CODES INDICATED HEREIN... 3. ALL MATERIALS ARE TO BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S REQUIREMENTS... 4. ALL CONDITIONS SHOWN TO BE EXISTING SHALL BE KEPT BY THE GENERAL CONTRACTOR PRIOR TO START OF CONSTRUCTION... 5. CONTRACTOR TO REVIEW AND FOLLOW CONSTRUCTION TECHNIQUES/SPECIFICATIONS OUTLINED IN THE GEOLOGICAL REPORT... 6. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR HAVING A THOROUGH KNOWLEDGE OF EXISTING FIELD CONDITIONS... 7. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THE SAFETY OF ALL PERSONS ON THE JOB SITE AT ALL TIMES INCLUDING (BUT NOT LIMITED TO) SUBCONTRACTORS, FACILITY EMPLOYEES, VENDORS, DESIGN STAFF PROFESSIONALS AND INSPECTION PERSONNEL... 8. THE GENERAL CONTRACTOR SHALL PROVIDE DUMPSTERS, PORTABLE TOILETS AND TEMPORARY POWER FOR UNRESTRICTED PROJECT RELATED USE BY OTHERS... 9. THE GENERAL CONTRACTOR SHALL COORDINATE PROJECT PHASING AND STORAGE OF MATERIALS WITH THE OWNER... 10. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR RECEIVING, UNLOADING, STORING AND PROTECTING OF MATERIALS AND EQUIPMENT SUPPLIED BY THE OWNER... 11. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING THE AREA CLEAN AND FREE OF DEBRIS AT ALL TIMES DURING CONSTRUCTION... 12. EXISTING PAVING THAT WILL REMAIN AFTER CONSTRUCTION SHALL BE PROTECTED FROM DAMAGE... 13. THE GENERAL CONTRACTOR SHALL FIELD VERIFY THE EXACT LOCATION OF ALL PUBLIC AND PRIVATE UTILITIES... 14. IF REQUESTED BY THE OWNER, PROVIDE TEMPORARY CONSTRUCTION FENCING... 15. ALL DIMENSIONS ARE TO GROUND LEVEL IMPROVEMENTS... 16. CONTRACTOR IS RESPONSIBLE FOR PROTECTION OF ALL PROPERTY CORNERS... 17. CONTRACTOR SHALL MATCH PROPOSED CURB AND GUTTER, CONCRETE, AND PAVEMENT TO EXISTING IN GRADE AND ALIGNMENT... 18. CONSTRUCTION SHALL COMPLY WITH ALL GOVERNING CODES AND BE CONSTRUCTED TO SAME... 19. CONTRACTOR IS RESPONSIBLE FOR REPAIRING THE DAMAGE DONE TO ANY EXISTING ITEM TO REMAIN DURING CONSTRUCTION... 20. CONTRACTOR SHALL REFER TO THE ARCHITECTURAL PLANS FOR EXACT LOCATIONS AND DIMENSIONS OF BUILDING APPURTENANCES... 21. ALL DISTURBED AREAS ARE TO RECEIVE FOUR INCHES OF TOPSOIL, SEED OR SO2, MULCH AND WATER UNTIL A HEALTHY STAND OF GRASS IS ESTABLISHED... 22. EXISTING STRUCTURES WITHIN CONSTRUCTION LIMITS ARE TO BE ABANDONED, REMOVED OR RELOCATED AS NECESSARY... 23. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL RELOCATIONS... 24. ANY DISCREPANCIES ON THE DRAWINGS SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE OWNER... 25. IN THE EVENT THE CONSTRUCTION IS ABANDONED PRIOR TO THE COMPLETION OF THE PROJECT... 26. THESE PLANS ARE INTENDED TO AND SHALL COMPLY WITH AMERICANS WITH DISABILITIES ACT... 27. ALL VEGETATION FROM CLEARING AND GRUBBING SHALL BE DISPOSED OF OFF-SITE... 28. CONTRACTOR IS RESPONSIBLE FOR PERMITTING, INSTALLATION AND MAINTENANCE OF ALL MAINTENANCE OF TRAFFIC OPERATIONS DURING CONSTRUCTION... 29. ALL DESIGN AND CONSTRUCTION MUST CONFORM TO THE MINIMUM STANDARDS SET DOWN IN THE CITY DEVELOPMENT CODE, ZONING, AND/OR RELATED ORDINANCES...

GENERAL PAVING AND GRADING NOTES:

- 1. ALL PAVING AND GRADING CONSTRUCTION MATERIALS AND METHODS SHALL MEET THE STANDARD SPECIFICATIONS AND REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION... 2. ALL CUT ON FULL SLOPES SHALL BE 3:1 OR FLATTER UNLESS OTHERWISE NOTED... 3. PRECAST STRUCTURES MAY BE USED AT CONTRACTORS OPTION... 4. IF ANY EXISTING STRUCTURES TO REMAIN ARE DAMAGED DURING CONSTRUCTION IT SHALL BE THE CONTRACTORS RESPONSIBILITY TO REPAIR AND/OR REPLACE... 5. THE CONTRACTOR SHALL ADHERE TO ALL TERMS & CONDITIONS AS OUTLINED IN THE EPA OR APPLICABLE STATE GENERAL WQDES PERMIT FOR STORM WATER DISCHARGE ASSOCIATED CONSTRUCTION ACTIVITIES... 6. CONTRACTOR SHALL ADJUST AND/OR CUT EXISTING PAVEMENT AS NECESSARY TO ASSURE A SMOOTH FIT AND CONTINUOUS GRADE... 7. CONTRACTOR SHALL ASSURE POSITIVE DRAINAGE AWAY FROM BUILDINGS FOR ALL NATURAL AND PAVED AREAS... 8. TOPOGRAPHIC INFORMATION IS TAKEN FROM A TOPOGRAPHIC SURVEY... 9. ALL UNSURFACED AREAS DISTURBED BY GRADING OPERATION SHALL RECEIVE 4 INCHES OF TOPSOIL... 10. CONTRACTOR SHALL MAINTAIN A MINIMUM OF 30% COVER OVER ALL WATER LINES.

- AUTHORITY HAVING JURISDICTION SPECIFICATIONS AND STANDARDS (LATEST EDITION) RESPECTIVELY... 12. ALL REINFORCED CONCRETE PIPE SHALL BE CLASS B UNLESS OTHERWISE NOTED... 13. ALL CONCRETE USED ON THE SITE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 4000 PSI... 14. ALL AREAS INDICATED AS PAVEMENT SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE TYPICAL PAVEMENT SECTIONS AS INDICATED ON THE DRAWINGS... 15. THE CONTRACTOR SHALL ENSURE THAT ALL PLANTING AREAS (INTERIOR ISLANDS, FOUNDATION PLANTING AREAS, ETC.) ARE NOT COMPACTED AND DO NOT CONTAIN LIMEROCK OR OTHER MATERIAL... 16. CONTRACTOR IS SPECIFICALLY CAUTIONED, DEPENDING ON THE TIME OF YEAR AND PROJECT LOCATION... 17. IF DEWATERING IS REQUIRED... 18. STRIP TOPSOIL AND ORGANIC MATTER AND PAVING MATERIAL FROM ALL AREAS TO BE IMPERVIOUS... 19. FIELD DENSITY TESTS SHALL BE TAKEN AT FREQUENCY AS REQUIRED... 20. CONTRACTOR SHALL ENSURE POSITIVE FLOW TO ALL INLETS WITH DRAINAGE BASINS... 21. THE CONTRACTOR SHALL TAKE ALL MEASURES NECESSARY TO CONTROL SEDIMENT... 22. CONTRACTOR SHALL COORDINATE ANY DISRUPTIONS TO EXISTING UTILITY SERVICES... 23. PRIOR TO THE CONSTRUCTION OF OR CONNECTION TO ANY STORM DRAIN, SANITARY SEWER, WATER MAIN OR ANY OF THE DRY UTILITIES... 24. PRIOR TO CONSTRUCTION, THE GENERAL CONTRACTOR SHALL VERIFY THAT "SUB OUTS" FOR POWER, TELEPHONE, FIBER OPTIC, WATER, CABLE HAVE BEEN PROVIDED BY OTHERS...

GENERAL UTILITY NOTES:

- 1. CONTRACTOR SHALL COORDINATE ANY DISRUPTIONS TO EXISTING UTILITY SERVICES... 2. CONSTRUCTION SHALL NOT START ON ANY PUBLIC UTILITY SYSTEM UNTIL WRITTEN APPROVAL... 3. PRIOR TO THE CONSTRUCTION OF OR CONNECTION TO ANY STORM DRAIN, SANITARY SEWER, WATER MAIN OR ANY OF THE DRY UTILITIES... 4. PRIOR TO CONSTRUCTION, THE GENERAL CONTRACTOR SHALL VERIFY THAT "SUB OUTS" FOR POWER, TELEPHONE, FIBER OPTIC, WATER, CABLE HAVE BEEN PROVIDED BY OTHERS... 5. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE SCHEDULE FOR INSTALLATION... 6. ALL SANITARY SEWER MANHOLES IN PAVED AREAS SHALL BE FLUSH WITH PAVEMENT... 7. ALL FIELD MATERIALS ARE TO BE INSTALLED IN ACCORDANCE WITH THE SHOWN AND CONTRACTED... 8. CONTRACTOR SHALL NOTIFY THE UTILITY AUTHORITIES INSPECTORS 72 HOURS BEFORE CONNECTING TO ANY EXISTING LINE... 9. UNDERGROUND UTILITY LINES SHALL BE INSTALLED, INSPECTED AND APPROVED BEFORE BACKFILLING... 10. ALL CONCRETE FOR ENCASUREMENTS SHALL HAVE A MINIMUM 28 DAY COMPRESSION STRENGTH AT 4000 P.S.I... 11. REFER TO ARCHITECTURAL PLUMBING DRAWINGS FOR THE IN OF ALL UTILITIES... 12. DRAININGS DO NOT PURPORT TO SHOW ALL EXISTING UTILITIES... 13. THE CONTRACTOR SHALL CONSTRUCT GRAVITY SEWER, LATERALS, MANHOLES, GRAVITY SEWER LINES AND DOMESTIC WATER AND FIRE PROTECTION SYSTEM AS SHOWN ON THESE PLANS... 14. THE CONTRACTOR SHALL RESTORE ALL DISTURBED VEGETATION IN KIND, UNLESS SHOWN OTHERWISE... 15. DEFLECTION OF PIPE JOINTS AND CURVATURE OF PIPE SHALL NOT EXCEED THE MANUFACTURER'S SPECIFICATIONS... 16. ALL UTILITY AND STORM DRAIN TRENCHES LOCATED UNDER AREAS TO RECEIVE PAVING SHALL BE COMPLETELY BACKFILLED AND COMPACTED IN ACCORDANCE WITH SPECIFICATIONS... 17. SHOP DRAWINGS FOR ALL MATERIALS AND APPURTENANCE SHALL BE SUBMITTED TO AND APPROVED BY THE GOVERNING UTILITY DEPARTMENT... 18. AT LEAST THREE WEEKS PRIOR TO CONSTRUCTION... 19. THE CONTRACTOR SHALL PERFORM AN INFILTRATION/INFILTRATION TEST ON ALL GRAVITY SEWERS... 20. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING EXISTING WATER MAINS, FORCE MAINS, SANITARY SEWER AND STORM MAINS... 21. SANITARY SEWER, FORCE MAINS, SEWER LATERALS, AND STORM SEWERS SHOULD CROSS UNDER WATER MAINS... 22. A MINIMUM HORIZONTAL DISTANCE OF TEN FEET SHOULD BE MAINTAINED BETWEEN WATER LINES AND SEWER LINES... 23. A MINIMUM HORIZONTAL DISTANCE OF THREE FEET SHALL BE MAINTAINED BETWEEN WATER LINES AND OTHER UNDERGROUND UTILITIES... 24. ALL DIP SHALL BE CLASS 50 OR HIGHER... 25. TREES SHALL BE PLACED SO AS TO AVOID BURIED UTILITIES... 26. ALL UTILITY MAIN LENGTHS SHOWN ARE APPROXIMATE... 27. PRESSURE PIPE TESTING SPECIFICATIONS SHALL REFERENCE THE CITY AND/OR FIRE DEPARTMENT... 28. CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES FOR INSTALLATION REQUIREMENTS... 29. REFER TO BUILDING PLANS FOR SITE ELECTRICAL PLAN... 30. WHERE SANITARY SEWER, FORCE MAINS, SEWER LATERALS, AND STORM SEWERS MUST CROSS A WATER MAIN WITH LESS THAN 18 INCHES VERTICAL DISTANCE... 31. ALL CROSSINGS SHOULD BE ARRANGED SO THAT THE SEWER MAIN PIPE JOINTS AND THE WATER MAIN PIPE JOINTS ARE EQUIVALENT FROM THE POINT OF CROSSING... 32. ALL DIP SHALL BE CLASS 50 OR HIGHER... 33. ALL FIRE HYDRANTS SHALL BE INSTALLED WITH HOSE CONNECTIONS FACING THE BUILDING... 34. NO LANDSCAPE PLANTS, OTHER THAN SOD, SHALL BE PLACED WITHIN 7 1/2 FEET OF EACH SIDE AND THE FRONT... 35. SANITARY SEWER PIPE SHALL BE AS FOLLOWS UNLESS OTHERWISE NOTED... 36. POTABLE WATER LINES SHALL BE AS FOLLOWS UNLESS OTHERWISE NOTED... 37. CONTRACTOR SHALL MAINTAIN A MINIMUM OF 30% COVER OVER ALL WATER LINES.

CKE GROUP logo with 'GROUP' in a box. Below it, 'CKE GROUP INCORPORATED' with 'engineering • architecture • planning'. Address: 15500 NEW BARN ROAD, SUITE 106, MIAMI LAKES, FLORIDA 33014. Phone: (305) 558-4124, Fax: (305) 826-0619, EB#0004432. A circular seal with text: 'SEAL EDUARDO L. CARCACHÉ CIVIL ENGINEER-PE 31914 ANA A. GONZALEZ VALDEZ ARCHITECT-AR 97769'.

Table with 3 columns: NO., DATE, DESCRIPTION. Row 1: 03-02-18. Below the table are several empty rows with triangles in the NO. column.

CONTRACT DATE: ----- BUILDING TYPE: CUSTOM PLAN VERSION: 1 SITE NUMBER: 309797 STORE NUMBER: 420630 TACO BELL 5070 W. Atlantic, Blvd. Delray Bch., FL

TACO BELL logo. Text: 'T-40 OPEN KITCHEN DELRAY BEACH SOL LEGEND & GEN. NOTES CV-2'. Plot Date: 07-26-2018