



**FLOOR PLAN**  
SCALE: 1/8" = 1'-0"

**KEYNOTES**

1. 6" REINFORCED CONCRETE SLAB OVER 6" ABC.
2. MASONRY PLANTER WALL - SEE WALL SECTIONS.
3. 4" FIBERMESH CONCRETE SLAB OVER 6" ABC.
4. MASONRY SCREEN WALL - SEE DETAIL 14/A5.3.
5. LANDSCAPE AREA - SEE LANDSCAPE PLAN.
6. BRICK BANDING - SEE SHEET A1.0 FOR CONTINUATION.
7. ENTRANCE MATT.
8. EXPANSION JOINT - SEE DETAIL 2A/A1.0.
9. CONTROL JOINT - SEE DETAIL 2B/A1.0.
10. PRE-CAST CONCRETE COLUMN.
11. ALUMINUM WINDOW WALL WITH 1/4" GLASS.
12. WOOD/GLASS PARTITION WALL - SEE DETAIL 13/A5.2.
13. MOP SINK - SEE PLUMBING DRAWINGS.
14. MASONRY WALL - SEE STRUCTURAL DRAWINGS.
15. METAL LOUVERED GATE - SEE DETAIL 15/A5.3.
16. METAL LOUVER - SEE DETAIL 16/A5.3.
17. 4" CONCRETE SLAB RAISED OVER 6" SLAB FOR SERVICE ENTRANCE SECTION.
18. SAFE DEPOSIT BOXES - BY OWNER.
19. 18" FORM STORAGE - COORDINATED BY MERABANK AND MILLWORK SUBCONTRACTOR.
20. 24" STORAGE SHELVING - COORDINATED BY MERABANK AND MILLWORK SUBCONTRACTOR.
21. 30" DEEP COUNTERTOP WITH SHELVES BELOW, 40" AFF - COORDINATED BY MERABANK AND MILLWORK SUBCONTRACTOR.
22. 2'-6" COUNTERTOP - 2'-0" DEEP WITH CARPET INSET, NO SPLASH - COORDINATED BY MERABANK AND MILLWORK SUBCONTRACTORS.
23. PANELIZED VAULT WALL ATTACHED TO MASONRY WALL.
24. FIRE EXTINGUISHER - BRACKET MOUNTED.
25. DRIVE ALERT SENSOR SET IN 4" X 4" X 24" HINGED WIREWAY AND SCREW COVER BY "GRAYBAR", RECESSED IN CONCRETE.
26. FUTURE INSTALLED KIOSKS FOR DRIVE-UP PNEUMATIC SYSTEM.
27. FACE OF ROOF OVERHANG - TYPICAL.
28. SLOPE CONCRETE 1/4" / FT. TO 2" WEEP HOLES AT SLAB LEVEL; SPACE EVERY 4'-0" O.C.

**GENERAL NOTES**

1. SLUMP BLOCK MASONRY AT EXTERIOR AND EXPOSED INTERIOR CONDITIONS TO BE STAINED AND THE GROUT JOINTS TO BE "BAGGED" WITH MORTAR. CONTRACTOR TO PREPARE MOCK-UP FOR ARCHITECT/OWNER REVIEW.
2. EXPOSED T-111 WOOD SIDING AT EXTERIOR SOFFITS AND EXTERIOR WOOD FACIAS TO BE STAINED IN DUNN EDWARDS SEMI-TRANSPARENT OIL STAIN #17-84, SPICE.
3. ALL EXTERIOR EXPOSED METAL AND CONCRETE-FILLED BOLLARDS TO BE PAINTED TO MATCH STAIN ON SLUMP BLOCK MASONRY.
4. ALUMINUM WINDOW WALLS TO INCORPORATE STOCK MATERIAL PROVIDED BY THE OWNER. USE CLEAR INSULATED GLASS AT NORTH AND EAST WINDOWS, AND 1/4" CLEAR GLASS AT ENTRY WINDOW WALL ON THE EAST SIDE. VERIFY THESE LOCATIONS OF INSULATED GLASS WITH OWNER.

**LEGEND**

- WINDOW TYPES - SHEET A5.2
- INTERIOR ELEVATION - SH. A5.0/A5.1
- WALL TYPES - SHEET A5.3

Architecture/Planning/Interior Design  
**LENDRUM DESIGN GROUP**  
 3033 North Forty-fourth Street  
 Phoenix, Arizona 85018  
 602/955-2100



**MeraBank**  
 KINGMAN, ARIZONA  
 BRANCH BANK

JOB NUMBER  
 10434.00  
 DATE  
 11-11-88  
 DRAWN  
 S.C.F.  
 CHECKED  
 P.G.  
 SHEET TITLE  
**FLOOR PLAN**

SCALE  
 1/8" = 1'-0"  
 REVISIONS  
 DRAWING NUMBER  
**A 2.0**