

GATE COLUMN FOOTING N.T.S. **F**

WALL SECTION N.T.S. **D**

GATE HARDWARE: ALL HARDWARE AND ACCESSORIES SHALL BE HEAVY GALVANIZED.


GATE STOP: MUSHROOM TYPE OR FLUSH PLATE WITH ANCHORS SET IN CONCRETE TO ENGAGE THE CENTER DROP ROD OR PLUNGER BAR.

GATE NOTES: (4) EQUAL WIDE x 6-0" HIGH MTL. GATES, TYPE 'B' 1 1/2" DECKING, 22GA. W/ T.S. 1 X .1875 BAR CROSS BRACING WELD AND GRIND SMOOTH ALL CONNECTIONS, TYP. PRIME AND PAINT ALL STEEL COMPONENTS.


SYMBOL	AREA	MANUFACTURER	COLOR
1	GATE FRAME	SHERWIN WILLIAMS	SW 7045 "INTELLECTUAL GRAY"
2	PIPE BOLLARDS	SHERWIN WILLIAMS	CAUTION YELLOW
3	NOT USED		
4	CMU	SHERWIN WILLIAMS	SW 7045 "INTELLECTUAL GRAY"
5	METAL GATES	SHERWIN WILLIAMS	SW 7045 "INTELLECTUAL GRAY"

ENCLOSURE NOTES N.T.S. **I**


SCHEDULE N.T.S. **G**




FRONT ELEVATION N.T.S. **E**



SIDE ELEVATION N.T.S. **J**




BOLLARD DETAIL 1/4" = 1'-0" **B**



CONCRETE NOTES:
 1. INSTALL 1/2" EXP. JT. MATERIAL AND SEALANT BETWEEN CONCRETE SLABS
 2. INSTALL CONTROL JT'S AT MAX. 10' O.C. IN SLABS

DUMPSTER PLAN N.T.S. **A**



OWN/STATE COMMENTS 08.10.20

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544


TACO BELL
 EXPLORER LITE
 MEDIUM40

TRASH ENCLOSURE DETAILS

G2.0

- NOTES**
- IF EXISTING SPEAKER POST LOCATION IS TO BE REUSED, CENTERLINE OF SPEAKER POST FOOTING CAN BE BETWEEN 1'-10" AND 2'-10" FROM THE FACE OF CURB.
 - CENTERLINE OF CANOPY FOOTING MUST BE WITHIN 18" OF FACE OF CURB.
 - ALL AREAS OF THE MB MUST BE VISIBLE TO DRIVER LOCATED AT SPEAKER POST. ASSUME DRIVERS LOCATION IS 24" FROM FACE OF CURB, CENTERED ON SPEAKER POST.
 - CENTER OF MB TO BE 5'-6" TO 9'-0" FROM DRIVERS POINT OF VIEW.
 - PROVIDE (2) 1" CONDUITS FROM BUILDING TO SPEAKER POST FOR LOW VOLTAGE WIRING


CORNER DIMENSIONS				
RADIUS	A	B	C	MENU BRD DEG TILT
15'-0"	6'-3"	3'-3"	1'-3"	48°
18'-0"	5'-10"	3'-6"	1'-7"	52°
20'-0"	5'-11"	3'-7"	1'-9"	54°



NOT USED N.T.S. 17

NOT USED N.T.S. 18

ENLARGED MENU BOARD DETAIL @ STRAIGHT CURB 3/8" = 1'-0" 1




- NOTES**
- IF EXISTING SPEAKER POST LOCATION IS TO BE REUSED, CENTERLINE OF SPEAKER POST FOOTING CAN BE BETWEEN 1'-10" AND 2'-10" FROM THE FACE OF CURB.
 - CENTERLINE OF CANOPY FOOTING MUST BE WITHIN 18" OF FACE OF CURB.
 - ALL AREAS OF THE MB MUST BE VISIBLE TO DRIVER LOCATED AT SPEAKER POST. ASSUME DRIVERS LOCATION IS 24" FROM FACE OF CURB, CENTERED ON SPEAKER POST.
 - CENTER OF MB TO BE 5'-6" TO 9'-0" FROM DRIVERS POINT OF VIEW.
 - PROVIDE (2) 1" CONDUITS FROM BUILDING TO SPEAKER POST FOR LOW VOLTAGE WIRING

ENLARGED MENU BOARD DETAIL @ STRAIGHT CURB 3/8" = 1'-0" 1

NOT USED N.T.S. 11

NOT USED N.T.S. 3




BOLLARD DETAIL 3/4" = 1'-0" 8

NOT USED N.T.S. 16

NOT USED N.T.S. 12

NOT USED N.T.S. 4

ARCVISION
 INCORPORATED
 ARCHITECTURE • ENGINEERING • STORE PLANNING
 SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
 1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
 PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com



OWN/STATE COMMENTS 08.10.20

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544



SITE DETAILS
CT1.0

6/29/20


FINAL SITE DEVELOPMENT PLANS

FOR

TACO BELL

3615 BREMEN HIGHWAY


SECTION 28, TOWNSHIP 37 NORTH, RANGE 3 EAST, PENN TOWNSHIP, CITY OF MISHAWAKA, ST. JOSEPH COUNTY INDIANA



VICINITY MAP

SCALE: 1"=2,000'

SOURCE: GOOGLE MAPS



LOCATION MAP

SCALE: 1"=400'

SOURCE: ST. JOSEPH COUNTY GIS

UTILITY CONTACTS	
Gas	NIPSCO 1039 East Pennsylvania Avenue, South Bend, IN 46601 Contact: Jonathan Erdahl (574) 800-6132
Electric	Mishawaka Utilities, Electric Department 1646 East 12th Street, Mishawaka, IN 46544 Contact: Kevin Wasmer (574) 258-1717
Telephone	AT&T 307 South Main Street, South Bend, IN 46601 Contact: Thomas Pendergrass (574) 237-8822
Fiber Optics	St. Joe Valley Metronet Commerce Center, Suite 305 401 East Colfax Avenue, South Bend, IN 46617 Contact: Ben Hudson (574) 986-5353
Cable	Comcast 1920 E. McKinley Avenue, Mishawaka, IN 46545 Contact: Jay Costello (574) 789-1039
Water	Mishawaka Utilities, Water Department 401 East Jefferson Boulevard, Mishawaka, IN 46545 Contact: Dave Majewski (574) 258-1652
Sewer, Streets	City of Mishawaka Engineering Department 600 East 3rd Street, Mishawaka, IN 46544 Contact: Christine Jamrose, PE (574) 258-1619



Call 811 OR 1-800-382-5544
24 Hours a Day, 7 Days a Week

OWNER
Delight TB Indiana, LLC
PO Box 780023
Wichita, KS 67278
(617) 233-7114
rkrumholz@delightrg.com

SURVEYOR/CIVIL ENGINEER
Abonmarche Consultants, Inc.
750 Lincoln Way East
South Bend, IN 46601
(574) 232-8700
mhuber@abonmarche.com

DEVELOPER
Delight TB Indiana, LLC
PO Box 780023
Wichita, KS 67278
(617) 233-7114
rkrumholz@delightrg.com

ARCHITECT
ArcVision, Inc.
1950 Craig Road, Ste. 300
St. Louis, MO 63146
(314) 415-2400
bbaquet@arcv.com

SHEET INDEX		
Sheet Number	Description	Latest Revision
C0.0	Cover Sheet & Index	
C1.0	Construction Notes & Specifications	
C2.0	Existing Conditions Map & Removals Plan	
C3.0	Site Plan	
C4.0	Utilities Plan	
C5.0	Grading Plan	
C6.0-C6.1	Drainage Plan	
C7.0	Landscape Plan	
C7.1	Lighting Plan	
C8.0	General Details	
C8.1	Utility Details	
C8.2	Sewer Details	
C9.0-C9.1	Erosion Control Plan & Details	

2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------

**SHEET C3.0 - SITE PLAN
CONSTRUCTION NOTES**

- Contractor shall obtain all required local, state and federal permits except for the IDEM Rule 5 Construction/Land Disturbance permit that will be obtained by the Owner.
- Contractor shall follow the current Indiana Rule 5 storm water quality guidelines for controlling soil erosion and controlling and treating nonpoint source sediment laden runoff. See Erosion Control Plan, Sheets C9.0-C9.1.
- Contractor shall request existing utility location from Indiana 811 prior to commencing construction.
- Damage to public and private property shall be repaired to equal or better condition at no additional cost to the Owner.
- No streets shall be closed without prior approval from the local municipality.
- Contractor shall protect the work and the safety of the public and shall provide, erect and maintain barricades, signals, signs and other traffic control devices in accordance with the Indiana Manual on Uniform Traffic Control Devices.
- Contractor shall follow "2020 Indiana Department of Transportation Standard Specifications" for pavement materials and installation procedures.
- See "Miscellaneous Construction Details", Sheet C8.1 for additional construction notes and details of curb, sidewalk, pavement, sidewalk ramps, signs and pavement markings, including ADA accessible spaces.
- Contractor shall construct sidewalks, ramps, parking spaces and ADA accessible areas in accordance with the current ADA standards.
- Sign designations from the U.S. Dept. of Transportation Federal Highway Administration "Manual on Uniform Traffic Control Devices" (MUTCD).
- Radial are noted along the drive centerline. Offset from centerline to determine curb alignment along back of parking bays, unless noted otherwise.
- Parking spaces along curve are radial with a minimum width of 9'. ADA access aisles are minimum 5' wide.
- Curb radii noted on the site layout plan are dimensioned along the back of curb.
- Thicken concrete pavement adjacent to HMA pavement, See Detail, Sheet C8.0.
- Contractor shall bring Drawing discrepancies and conflicts to the attention of the Engineer as soon as they are noticed, for clarifications and revisions as necessary.
- Contractor shall prepare Record Drawings with field locations and elevations upon completion of the work for submittal to the Engineer.

**SHEET C4.0 - UTILITIES PLAN
CONSTRUCTION NOTES**

- For additional construction notes including material and testing specifications and for construction details see "Utility Details," Sheet C8.1; and "Sewer Details," Sheet C8.2. For underground storage system, See "Chamber Details," Sheet C6.1.
- Contractor is responsible for having existing underground utilities located and field confirming locations and depths prior to commencing construction.
- Contractor shall coordinate utility service locations and depths in the R/W with utility companies prior to installation.
- Contractor shall verify utility service locations and depths at the building with the Architect prior to installation.
- Contractor shall coordinate with utility companies as necessary if service interruption is required.
- Materials, construction and testing shall be in accordance with the current construction standards for City of Mishawaka.
- Contractor shall verify the water table depth and include dewatering costs in the Bid. The water table shall be lowered to at least 12 inches below the lowest pipe invert prior to pipe installation.
- Maintain minimum 10 feet clear of horizontal separation between sewer and water pipes. Maintain minimum 18 inches clear of vertical separation at sewer and water pipe crossings. If clearances cannot be met, sewer shall be water grade pipe in accordance with AWWA standards. At crossings, water grade sewer pipe shall extend a minimum of 10 feet past each side of the crossing, and one full length of water pipe shall be centered at the crossing.
- Maintain minimum 5 feet of cover at water mains & services.
- Unsuitable material that may affect the structural integrity of the pipe shall be replaced or treated to support the anticipated loads.
- Storm and sanitary sewer castings shall be imprinted with the notices as specified on the construction details.
- Remove sediment buildup from storm structures prior to Owner's acceptance of the Work.
- Roof downspouts shall connect to the storm sewer. It is the Contractor's responsibility to review the Arch. plans and confirm downspout locations.
- Utilities other than sewer and water shall be installed underground and placed in PVC conduit where located under pavement sidewalk and curb.

**SHEETS C5.0, C6.0 - C6.1 -
GRADING & DRAINAGE PLAN
CONSTRUCTION NOTES**

- Contractor shall remove topsoil and stockpile the material onsite at a location approved by the Owner. Place a minimum of 4 inches of topsoil on all disturbed areas outside the building and parking areas.
- All fill material shall be placed and compacted in accordance with the geotechnical report.
- Prior to commencing paving operations, Contractor shall proof roll exposed subgrade with a geotechnical engineer or qualified representative to witness the work. Excavate unsuitable soil and backfill and compact with suitable material capable of supporting the anticipated loads.
- Place site grading backfill in maximum six inch lifts and compact to 100% Standard Proctor to the top of subgrade.
- Finished grades at building doorways shall match the building finished floor elevation, unless otherwise noted.
- Contractor is responsible for meeting ADA guidelines at sidewalks and parking areas.
- The proposed contours and spot elevations on this Drawing show grading intent only. Contractor is responsible for confirming that the provided grading plan maintains positive drainage to prevent ponded water or encroachment onto adjacent properties; and shall contact the Engineer if additional grades are needed, if the design does not provide positive drainage, or if any discrepancies/conflicts are found.

**SHEET C7.0 - LANDSCAPE PLAN
CONSTRUCTION NOTES**

- All landscaping shall comply with the City of Mishawaka Zoning Ordinance.
- Work shall be performed by a single firm specializing in landscape work with a minimum of five (5) years experience.
- All plant materials shall be nursery grown and meet the latest edition of the "American Standard for Nursery Stock". Tree caliper size indicates the diameter of the trunk taken at 6" above ground level.
- Contractor shall restore existing lawn and planting areas disturbed during construction to existing or better condition.
- Contractor is responsible for coordinating landscape work with other work.
- Contractor shall notify Developer, prior to planting, of any foreign substance that may damage vegetation.
- Contractor shall maintain moist soil for vegetation until planted. Check balled and burlapped plants to ensure they are receiving water through burlap material. If vegetation cannot be planted immediately, heel in root balls and cover with mulch.
- Landscape Contractor to prepare planting area soil. Test topsoil to verify fertility. Amend soil if pH is less than 5.5 or greater than 7.0. Adjust soil as indicated by analysis.
- Contractor shall verify that landscaped areas meet surveyed benchmarks and intended elevations for site drainage prior to finishing landscaping and placing topsoil; that building and trench backfilling is complete and inspected; and subgrade is contoured and compacted.
- Topsoil shall be 6" minimum depth in lawn areas. Planting soil shall be 18" minimum depth in planting areas and consist of 1/3 topsoil, 1/3 subsoil, and 1/3 peat moss and fertilizer. Topsoil shall be fertile, agricultural soil, typical for locality, capable of sustaining vigorous plant growth; well drained, free of subsoil, clay or impurities, free from stones, roots, branches, or debris over 1/2" in size and free from herbicide or other toxins. Remove soils contaminated with petroleum products.
- Top of planted root ball shall be even with finished grade. Plants shall be plumb with a level subbase. Contractor shall provide a two (2) year straightening guarantee in lieu of staking trees.
- Landscape beds shall be defined by commercial grade 1/8" x 4" steel edging, manufactured by an established company. Stake per manufacturer's recommendation.
- Place 3" of shredded hardwood mulch at landscape beds. Place a 36" diameter 3" deep spaded natural "v" edged hardwood mulch ring at trees located outside of landscape beds.
- Hydroseed lawns. Restore areas disturbed during construction. Provide alternate price for sodding in lieu of hydroseeding.
- Irrigate planting and lawn areas per Owner's direction. Provide a permanent automatic irrigation system on a design build-basis to irrigate 100% of the landscape areas.
- All tree wrap/twine, stakes, and guys etc. to be removed in one (1) year as part of maintenance. Contractor shall provide a one (1) year guarantee for plant material from the date of installation. Warranty shall include replacement of dead or unhealthy vegetation to be planted in the next growing season, with a new one (1) year warranty commencing on date of replacement for each plant replaced.

SHEETS C8.0 - GENERAL DETAILS


- GENERAL**
 - Curb and walk to be constructed of INDOT Class A concrete.
 - Cure concrete in accordance with current INDOT and municipal specifications.
 - Align curb, gutter and sidewalk joints.
- SIDEWALK**
 - Expansion joints shall be 1/2" wide with elastomeric filler, extending the full depth of the concrete located at a maximum spacing of 40'-0" and where sidewalk abuts concrete driveways, curb or other adjacent structures.
 - Contraction joints shall be scored 1/2" deep and spaced at 5 feet.
 - Formed joints shall be finished with a tool having a 1/4" radius.
 - Finish: Steel trowelled with a light broom texture perpendicular to the direction of travel.
- CURB**
 - Expansion joints shall be 1/2" wide with elastomeric filler, extending the full depth of the concrete, located at a maximum spacing of 40'-0".
 - Contraction joints shall be scored 1/2" deep and spaced at 10'.

SHEETS C8.2 - SEWER CONSTRUCTION NOTES

- All sewer main materials and construction shall be in accordance with City of Mishawaka Construction Standards and these Construction Drawings.
- Sanitary sewer fittings shall conform to the requirements of ASTM D3034 with a minimum wall thickness of SDR 35, as defined in 7.4.1, and molded in one piece with elastomeric joints and minimum socket depths as specified in Sections 6.2 and 7.3.2. PVC material shall have a cell classification of 12454-B and C as defined in ASTM D1784.
- Contractor shall supply as-built record drawings to the Owner and Engineer upon completion of work.
- The following tests shall be performed by the Contractor in accordance with the City of Mishawaka Standards and witnessed by a licensed Professional Engineer. The Engineer and Owner shall be provided 48 hours notice of all testing.
 - Low pressure air leakage test per ASTM F1417, standard test method for installation acceptance of plastic gravity sewer lines using low-pressure air. The infiltration rate shall not exceed 100 gallons per inch diameter of pipe per mile per day. If the test fails, the Contractor shall determine the cause, repair/replace the sewer line to the satisfaction of the Owner, and then re-test.
 - Tests for deflection of sanitary sewer pipes shall be performed no earlier than 30 days after installation. The pipe shall be tested with an approved 9-point mandrel. No pipe shall exceed a deflection of five (5%) percent. In the event the sanitary sewer pipe fails the deflection test, the section of pipe which failed shall be completely removed, replaced, and tested starting with low pressure air leakage testing and then deflection testing. The mandrel shall be pulled without the aid of a mechanical pulling device.
 - Sanitary sewer manholes, if specified, shall be tested by negative air pressure in accordance with ASTM C1244-93. If the test fails, the Contractor shall determine the cause, and then repair/replace the manhole to the satisfaction of the Owner. The test shall be repeated until it is successful.

SHEETS C8.1 - WATER CONSTRUCTION NOTES

- Water main, domestic and fire services, materials and construction shall be in accordance with City of Mishawaka Construction Standards, AWWA Standards, and these Construction Drawings.
- Water main (4-inch diameter and larger) shall be Class 50 ductile iron and pipe fittings shall be Class 250 ductile iron mechanical joint meeting the requirements of the City of Mishawaka and AWWA C-110 or AWWA C-111. Water main joints shall be bell and spigot with elastomeric rubber gaskets. Joints shall be push-on or mechanical, unless otherwise noted in the plans. Mechanical joint fittings shall be restrained by a mega-lug flange or grip ring meeting Mishawaka's latest specifications.
- Water services (less than 4-inch diameter) shall be Type 'K' Copper.
- All gate valves shall be resilient sealed and meet or exceed AWWA C509 (standard for resilient wedge seated valves) and the City of Mishawaka Standards. Valves shall be rated for 200 psi working water pressure with mechanical joints and open left (counterclockwise). Valves shall be anchored with restrained joints and thrust blocking. Valves shall be installed with standard cast iron valve boxes, plumb over the wrench nut of the valve and to finished grade, and have a round plug-type cover embossed with "WATER".
- Retainer glands shall be provided on all valves and fittings in accordance with City of Mishawaka Standards.
- Water main and services shall have a minimum cover of 5 feet.
- Water main shall be backfilled in accordance with the requirements as set forth in the plans for rigid pipe beneath pavement.
- Maintain a minimum horizontal clear separation 10 feet between water and sewer pipes. Where water and sewer pipes cross, maintain a minimum vertical clear separation of 18 inches. If separation cannot be met, the sewer pipe shall be constructed of water grade pipe meeting AWWA Standards for a distance of 10 feet each side of the water pipe. At crossings, one full length of water pipe shall be installed so that the joints will be as far from the sewer pipe as possible.
- All tees, plugs, valves, dead ends, reducers, and bends shall be installed with a restrained joint in accordance with City of Mishawaka Standards.
- Flushing, Disinfection, and Testing for domestic service shall be in accordance with City of Mishawaka and AWWA Standards. Water main shall be subjected to hydrostatic pressure 50% above normal operating pressure or 150 psi for at least 2 hours. Water Department to determine test pressure prior to performing testing. Leakage shall not exceed 36 gallons per 24 hours per mile of pipe per inch nominal diameter for pipes in 12' lengths, 27 gallons for 16' lengths, and 24 gallons for 18' lengths. All pipes or joints that do not surpass the requirements of the leakage testing shall be removed and replaced at the Contractor's expense.
- Flushing, Disinfection, and Testing for fire service shall be in accordance with City of Mishawaka Fire Department and AWWA Standards. Fire Department to determine test pressure and allowable leakage prior to performing testing.



**TACO BELL
3615 BREMEN HIGHWAY
MISHAWAKA, INDIANA**

PROJECT:

**CONSTRUCTION NOTES
AND SPECIFICATIONS**

SHEET TITLE:

DRAWN BY: **DEF**
 DESIGNED BY: **DEF**
 PM REVIEW: **MJH**
 QA/QC REVIEW: **RTN**
 DATE: **3-25-2020**
 SEAL:




SIGNATURE: *[Signature]*
 DATE: **7-1-2020**

SCALE:
 HORZ:
 VERT:

ACI JOB # **20-0205**
 SHEET NO.

C1.0

2	UPDATE ADDRESS	DEF	8/10/20
RNUM	RDESC	RBY	RDATE



EXISTING STRUCTURE DATA

- STR. NO. 108**
Exist. CB
Rim= 868.12
12" W= 865.98
- STR. NO. 123**
Exist. CB
Rim= 766.11
12" S= 862.26
12" E= 862.25
- STR. NO. 127**
Exist. CB
Rim= 865.53
12" S= 861.90
12" W= 861.94
12" NE DI= 861.89
- STR. NO. 131**
Exist. CB
Rim= 865.32
12" SW DI= 861.49
12" N DI= 861.49
- STR. NO. 135**
Exist. CB
Rim= 864.45
12" S DI= 861.00
12" NW DI= 861.00

EXISTING FEATURES LEGEND

- CB Inlet/Catch Basin
- W Water Valve
- Fire Hydrant
- Light Pole
- Telephone Marker
- SMH Sanitary Manhole
- Storm Inlet
- Drywell
- G Gas Line
- OH Overhead Electric Line
- E Electric Line
- T Telephone Line
- Sanitary Sewer
- Storm Sewer
- W Water Main
- 740 Contour

REMOVALS LEGEND

- Remove Existing Concrete Pavement
- 1 Existing electric and telephone to be relocated to 5' Indiana Michigan Power Company Easement (North edge of site) (By Others)
- 2 Relocate Power Pole 2' Behind Curb (By Others)
- 3 Relocate Light Pole 2' Behind Curb (By Others)
- 4 Relocate Sign Behind Curb
- 5 Remove Existing Curb
- 6 Remove Existing Concrete Center Curb

NOTES

1. Contractor shall request existing utility location from Indiana 811 prior to commencing construction.
2. Contractor shall notify the City of Mishawaka Department of Engineering prior to commencing construction within R/W.
3. Contractor shall remove topsoil and stockpile the material onsite at a location approved by the Owner.
4. Removed items shall be disposed off-site in accordance with all applicable local, state and federal codes.

SURVEY NOTES

1. Topographic survey data collection was performed in February, 2020.
2. The horizontal and vertical control datum for this survey is based on state plane coordinate system.

REFERENCES

1. ALTA Survey, Project No. 19-1474, Sheet 1 of 1, dated 11-5-19 by Michael Rozycki, PLS of Abonmarche Consultants, Inc.
2. Building footprint by Arcvision, Inc. St. Louis, MO.


CONTROL POINT DATA HORIZONTAL DATUM

CONTROL POINT #10	SET REBAR WITH RED CAP "ABONMARCHE CONTROL POINT" LOCATED AT NE COR. OF BREMEN HWY & MEIJER DR., APPROX. 9' EAST OF TRAF. MH	2324016.7148	188691.1978	866.08
-------------------	--	--------------	-------------	--------


BENCHMARK DATA VERTICAL DATUM

TBM A	CHISELED "X" IN NE BOLT OF FIRE HYDRANT APPROX. 23' N OF NE COR. OF SITE	865.48
TBM B	CHISELED "X" IN NE BOLT OF FIRE HYDRANT LOCATED AT THE SE COR. OF BREMEN HWY & MEIJER DRIVE	866.53

FIRM Source
St. Joseph County, Indiana
and Incorporated Areas
Map Number 18141C0218D
Effective Date January 2, 2011



FEMA FLOOD INSURANCE RATE MAP (FIRM)
Scale: 1" = 500'




2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------

ABONMARCHÉ
750 Lincoln Way E
South Haven, IN 46601
P 574.251.4440
abonmarche.com

TACO BELL
3615 BREMEN HIGHWAY
MISHAWAKA, INDIANA


EXISTING CONDITIONS & REMOVAL PLAN

SHEET TITLE:
DRAWN BY: DEF
DESIGNED BY: DEF
PM REVIEW: MJH
QA/QC REVIEW: RTN
DATE: 3-25-2020
SEAL:
REGISTERED PROFESSIONAL ENGINEER
No. 60016991
STATE OF INDIANA
SIGNATURE:
DATE: 7-1-2020
SCALE:
HORIZ: 1" = 20'
VERT:
ACI JOB #
20-0205
SHEET NO.
C2.0



PROPOSED FEATURES LEGEND

- Standard HMA Pavement:
 - 1-1/2" HMA Surface (165 #/SY)
 - 2-1/2" HMA Intermediate (275 #/SY)
 - 8" Compacted #53 Aggregate Base
- PCCP, 10" on Subbase for PCCP
- 8" Concrete Pavement on 4" compacted #53 aggregate base
- 6" 4,000 PSI Concrete with WWF on 6" compacted #53 aggregate base
- 4" Concrete Sidewalk
- Landscape Area; See Sheet C7.0
- Sidewalk Ramp, Type 1
- Concrete Curb
- Integral Concrete Curb, 8"
- Combination Concrete Curb & Gutter, Depressed Curb
- Concrete Center Curb, Type "C"
- 24" White Paint Stop Line
- 4" Solid White Paint Line
- Relocate Sign
- Relocate Light Pole
- Quantity of 9'x20' Auto Parking Spaces/Bay
- Int'l. Symbol of Access
- R1-1 MUTCD R-1 "STOP" Sign & Post
- R7-8 (ADA Access) Sign & Post
- Drainage Structure
- Clean out
- Light Pole



LEGAL DESCRIPTION:

A PARCEL LOCATED IN THE SOUTHEAST QUARTER OF SECTION 28, TOWNSHIP 37 NORTH, RANGE 3 EAST, CITY OF MISHAWAKA, PENN TOWNSHIP, ST. JOSEPH COUNTY, INDIANA, BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT THE NORTHEAST CORNER OF SAID QUARTER SECTION; THENCE SOUTH 00°19'19" EAST, 656.34 FEET TO A POINT ON THE CENTERLINE OF ELMWOOD AVENUE; THENCE SOUTH 89°49'23" WEST ALONG SAID CENTERLINE AND THE NORTH LINE OF A TRACT OF LAND CONVEYED TO CITY OF MISHAWAKA FOR RIGHT OF WAY DEDICATION AS DESCRIBED IN INSTRUMENT NUMBER 2019-18674, DEDICATION #1, ST. JOSEPH COUNTY RECORDER, A DISTANCE OF 57.31 FEET TO THE NORTHWEST CORNER OF SAID DEDICATION #1 AND BEING THE POINT OF BEGINNING; THENCE CONTINUING SOUTH 89°49'23" WEST ALONG SAID CENTERLINE 269.01 FEET TO THE NORTHEAST CORNER OF A TRACT OF LAND CONVEYED TO CITY OF MISHAWAKA FOR RIGHT OF WAY DEDICATION AS DESCRIBED IN INSTRUMENT NUMBER 2019-18674, DEDICATION #2, ST. JOSEPH COUNTY RECORDER; THENCE SOUTH 00°10'41" WEST, ALONG THE EAST LINE OF SAID DEDICATION #2 A DISTANCE OF 99.91 FEET; THENCE SOUTH 32°00'32" EAST ALONG AN EASTERLY LINE OF SAID DEDICATION #2 A DISTANCE OF 21.37 FEET; THENCE SOUTH 89°49'19" EAST ALONG THE NORTH LINE OF SAID DEDICATION #2 AND THE NORTH LINE OF A TRACT OF LAND CONVEYED TO CITY OF MISHAWAKA FOR RIGHT OF WAY DEDICATION AS DESCRIBED IN INSTRUMENT NUMBER 2019-18673, ST JOSEPH COUNTY RECORDER, A DISTANCE OF 237.53 FEET; THENCE NORTH 43°27'29" EAST ALONG THE WESTERLY LINE OF SAID CITY OF MISHAWAKA LAND AND THE WESTERLY LINE OF SAID DEDICATION #1 A DISTANCE OF 29.26 FEET; THENCE NORTH 00°11'59" EAST ALONG THE WEST LINE OF SAID DEDICATION #1 A DISTANCE OF 96.70 FEET TO THE POINT OF BEGINNING; CONTAINING 31,424 SQUARE FEET, MORE OR LESS, AND SUBJECT TO EASEMENTS, COVENANTS, AND RIGHTS OF WAY OF RECORD.

TABULATED DATA

PROPOSED BUILDING	
Restaurant with Drive Thru	2,053 SF
TOTAL	2,053 SF

PROPOSED LOT COVERAGE		
Area (SF)	% Coverage	
Building Footprint	2,053	6.5%
Pavement & Sidewalk	18,242	58.1%
Open/Landscape Area	11,121	35.4%
TOTAL	31,416	100.0%

(0.72 Ac)

PARKING SUMMARY

AUTOMOBILE PARKING SPACES REQUIRED

- Restaurant with Drive Thru: 15 Space/1,000 GSF
- = (15 Space) x (2,053 SF)/1,000 = 30 Spaces


Total 30 Automobile Spaces Required

TOTAL PARKING SPACES PROVIDED

- Automobile: 24 Spaces (Incl. 1 ADA Accessible)
- See Note 5

GENERAL NOTES

- Current Zoning: City of Mishawaka S2 PUD.
- Existing Land Use: Vacant / Proposed Land Use: Restaurant with Drive Thru.
- Building and parking setbacks in accordance with the S-2 PUD conditions and development regulations (Ord. 5057) and/or the C-7 Auto-Oriented Restaurant Commercial District, when applicable.
- The building will be serviced by City of Mishawaka municipal water and sewer.
- Variance to reduce required parking to 24 spaces was approved by the City of Mishawaka BZA Appeal 20-02 on February 11, 2020.
- Landscape, lighting & signage will be in accordance with the zoning ordinance unless the proper variances are obtained.
- Storm water will be collected on-site by the Owner.
- See Sheet C1.0 for Site Plan Construction Notes. See Sheet C8.0-C8.2 for Construction Details.
- See Architectural Drawings for building layout, foundations, wiring, etc.
- The approach and deceleration lane have been designed in accordance with the Mishawaka Engineering Standards for a commercial drive approach Type 1A with a posted speed limit of 40 mph on Bremen Highway.
- The 6" concrete curb shall transition to the 8" Integral Concrete Curb through the approach.
- Proposed Building will be one-story in height.




NO.	REVISION	DATE	BY
1	REVISE PAVEMENT MATERIAL IN DRIVE THRU	7/24/20	DEF
		8/10/20	DEF

ABONMARCHÉ
 17 N. Washington Street
 Valparaiso, IN 46383
 Phone: 219.850.4625
 Fax: 219.850.4625
 abonmarche.com
 abonmarche.com

TACO BELL
3615 BREMEN HIGHWAY
MISHAWAKA, INDIANA


SITE PLAN

SHEET TITLE:
 DRAWN BY: DEF
 DESIGNED BY: DEF
 PM REVIEW: MJH
 QA/QC REVIEW: RTN
 DATE: 3-25-2020
 SEAL:



SIGNATURE:
 DATE: 7-1-2020
 SCALE:
 HORZ: 1" = 20'
 VERT:

PROJECT NO: **20-0205**
 SHEET NO: **C3.0**



EXISTING FEATURES LEGEND

- CB Inlet/Catch Basin
- W Water Valve
- FH Fire Hydrant
- LP Light Pole
- TM Telephone Marker
- SMH Sanitary Manhole
- SI Storm Inlet
- DR Drywell
- G Gas Line
- OH Overhead Electric Line
- E Electric Line
- T Telephone Line
- SS Sanitary Sewer
- StS Storm Sewer
- WM Water Main

PROPOSED FEATURES LEGEND

- DS Drainage/Sewer Structure
- CO Clean-out
- W Water Valve
- SS Storm Sewer
- 6" SDR 35 PVC Sanitary Sewer Service
- WS Water Service
- G Gas Service
- E Electric Service
- T Telephone Service
- C Cable TV Service
- FOC Fiber Optics Service
- LP Light Pole

GENERAL NOTES

1. See Drainage Plan, Sheet C6.0, for structure notes with pipe lengths and invert elevations.
2. See Sheet C1.0 for Utilities Plan Construction Notes.
3. See Erosion Control, Sheets C9.0- C9.1.
4. A qualified soil testing firm approved by the Owner shall perform compaction testing.
5. XFMR doors for the electric cabinet to open to the north.

Grease Trap Sizing

Grease Trap Sizing conforms to the requirements set forth by the City of Mishawaka.

Assumptions:

- Building will be a Fast Casual Restaurant (Peak Factor = 1.33)
- Building will have a commercial kitchen with dishwashing machines (Waste Flow Rate Factor = 6)
- Building will have commercial kitchen waste (Retention Time = 2.4)
- Building will have a 24-hour operation (Storage Factor = 3)

Approximate Restaurant Seating = 35 seats

Required = (35 seats x 1.33) x 6 x 2.4 x 3 = 2,011 gallons


Provided = 3,000 gallons

ABONMARCHÉ
 750 Lincoln Way E
 South Haven, IN 46601
 Phone: 574.231.4400
 Fax: 574.231.4440
 abonmarche.com

**TACO BELL
 3615 BREMEN HIGHWAY
 MISHAWAKA, INDIANA**


UTILITIES PLAN

PROJECT: TACO BELL 3615 BREMEN HIGHWAY MISHAWAKA, INDIANA
 SHEET TITLE: UTILITIES PLAN
 DRAWN BY: DEF
 DESIGNED BY: DEF
 PM REVIEW: MJH
 QA/QC REVIEW: RTN
 DATE: 3-25-2020




SIGNATURE: [Signature]
 DATE: 7-1-2020

SCALE:
 HORZ: 1" = 20'
 VERT:
 ACT JOB #
20-0205



2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------

SHEET NO. **C4.0**



EXISTING FEATURES LEGEND

- ☐ Inlet/Catch Basin
- ⊙ Water Valve
- ⊕ Fire Hydrant
- ⊙ Light Pole
- ⊙ Telephone Marker
- ⊙ SMH Sanitary Manhole
- 740--- Contour

PROPOSED FEATURES LEGEND

- ⊙ Drainage Structure
- TC: 745.00 Top of Curb Elevation
- P: 744.50 Finished Pavement Elevation
- XXX.XX Finished Pavement Elevation
- XXX.XX* Existing Elevation (Match)
- 748--- Contour
- ⊙ 9' Wide Flush Curb for Mower Access to Lawn; Taper Curb @ Each End

ABONMARCHÉ
 17 N. Washington Street
 Marion Harbor
 Vespene, IN 46383
 # 219.850.4225
 abonmarche.com
 Engineering - Architecture - Land Surveying


TACO BELL
3615 BREMEN HIGHWAY
MISHAWAKA, INDIANA

PROJECT:

GRADING PLAN

SHEET TITLE:


DRAWN BY: DEF
 DESIGNED BY: DEF
 PM REVIEW: MJH
 QA/QC REVIEW: RTN
 DATE: 3-25-2020




SIGNATURE: [Signature]
 DATE: 7-1-2020

SCALE:
 HORIZ: 1" = 20'
 VERT: 1" = 20'

ACT JOB # 20-0205
 SHEET NO. C5.0



2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------



Taco Bell

Design Return Period 100 years
 Watershed Area 0.72 acres
 Developed Runoff Coefficient 0.72

Release Rate:

Total Release Rate 0.45 cfs

Storm Duration (hrs)	100-Year Intensity (in/hr)	Inflow Rate (cfs)	Release Rate (cfs)	Storage Rate (cfs)	Required Storage (acre-feet)	Storage w/ Silt. Factor (1.06)	Required Storage (cft)
0.08	9.84	5.10	0.45	4.65	0.03	0.03	1,432
0.17	7.38	3.83	0.45	3.38	0.05	0.05	2,208
0.25	6.12	3.17	0.45	2.72	0.06	0.06	2,619
0.33	5.58	2.89	0.45	2.44	0.07	0.07	3,102
0.5	4.42	2.29	0.45	1.84	0.08	0.08	3,543
0.67	3.92	2.03	0.45	1.58	0.09	0.09	4,079
0.83	3.46	1.79	0.45	1.34	0.09	0.10	4,291
1	2.96	1.53	0.45	1.08	0.09	0.10	4,173
1.5	2.42	1.25	0.45	0.80	0.10	0.11	4,643
2	1.87	0.97	0.45	0.52	0.09	0.09	3,997
3	1.35	0.70	0.45	0.25	0.06	0.07	2,884
6	0.81	0.42	0.45				
9	0.72	0.37	0.45				
12	0.63	0.33	0.45				
24	0.26	0.13	0.45				

Available Storage

Required Storage 0.11 4,643 cft

Proposed Underground Chamber
 Total Volume 4,648 cft

Time for Required Storage to Infiltrate Soil
 2.87 hrs

Total Available Storage 4,648 cft 0.11 acre-ft

Drainage Calculations
 Drainage Design conforms to the requirements set forth by the St. Joseph County Storm Drainage System is designed to retain all post development storm water on the developed site for a 100 year, 24 hour storm event plus 6% for siltation.

Site Coverage
 Impervious Surfaces (C=0.90) = 0.47 acres
 Open Area (C=0.20) = 0.25 acres
 Total = 0.72 acres

Modified Runoff Coefficient - Developed Area
 $(0.47 \text{ acres} \times 0.90) + (0.25 \text{ acres} \times 0.20) = 0.72 \text{ acres}$



Detention Sizing
 100 Year, 24 Hour Storm Intensity
 Intensity Reference: National Oceanic and Atmospheric Administration (NOAA)
 Developed Catchment Area, Total (C=0.73) = 0.72 acres

From Detention Analysis (Above),
 Storage Required = 4,643 cft < 4,648 cft = Storage Provided

Allowable Release Rate
 Pre-development area = 0.72 acres
 $i = 10 \text{ year } 27 \text{ min.} = 3.13/\text{hour}$
 $Q = CIA$
 $Q = (0.2)(3.13)(0.72)$
 $Q = 0.45 \text{ cfs}$

Groundwater Elevation
 Soil borings completed by GME Testing May 29, 2020.
 Existing groundwater elevation measured at 845±.


Note
 1. The St. Joseph County Drainage Board approved discharge into the Laing Ditch at its July 6, 2020 meeting.
 2. Storm sewer pipe is ADS N-12 or approved equal.
 3. Flat casting is Neenah R-1642 or approved equal.



- PROPOSED FEATURES LEGEND**
- ③ Longitudinal Joint
 - ⑭ Integral Concrete Curb, 8"
 - ⑧1 Mulched Seeding

Bremen Highway Decel Lane
 Scale: 1/2" = 1'-0"
 Per Elmwood Avenue Realignment Plans by Abonmarche Consultants, Inc. March 14, 2019.

SHEET TITLE:
 DRAWN BY: DEF
 DESIGNED BY: DEF
 PM REVIEW: MJH
 QA/QC REVIEW: RTN
 DATE: 3-25-2020



SIGNATURE:
 DATE: 7-1-2020

SCALE:
 HORZ: 1" = 20'
 VERT:
 ACT JOB # 20-0205

NO.	DESCRIPTION	DATE
2	UPDATE ADDRESS	8/10/20
1	MODIFICATION TO UG CHAMBER & STORM SEWER	7/16/20



Bremen Highway Taco Bell

Mishawaka, IN

STORMTECH CHAMBER SPECIFICATIONS

- CHAMBERS SHALL BE STORMTECH SC-740, SC-310, OR APPROVED EQUIV.
- CHAMBERS SHALL BE MANUFACTURED FROM VIRGIN POLYPROPYLENE OR POLYETHYLENE RESINS.
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORT PANELS THAT WOULD IMPIDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE ASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE ASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL MEET ASTM F2922 (POLYETHYLENE) OR ASTM F2418 (POLYPROPYLENE), "STANDARD SPECIFICATION FOR THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- CHAMBERS SHALL BE DESIGNED AND ALLOWABLE LOADS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. THE CHAMBER MANUFACTURER SHALL SUBMIT THE FOLLOWING UPON REQUEST TO THE SITE DESIGN ENGINEER FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE:
 - A STRUCTURAL EVALUATION SEALED BY A REGISTERED PROFESSIONAL ENGINEER THAT DEMONSTRATES THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.85 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY ASHTO FOR THERMOPLASTIC PIPE.
 - A STRUCTURAL EVALUATION SEALED BY A REGISTERED PROFESSIONAL ENGINEER THAT DEMONSTRATES THAT THE LOAD FACTORS SPECIFIED IN THE ASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET, THE 50 YEAR CRISP MODULUS DATA SPECIFIED IN ASTM F2418 OR ASTM F2922 MUST BE USED AS PART OF THE ASHTO STRUCTURAL EVALUATION TO VERIFY LONG-TERM PERFORMANCE.
 - STRUCTURAL CROSS SECTION DETAIL ON WHICH THE STRUCTURAL EVALUATION IS BASED.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-310/SC-740 SYSTEM

- STORMTECH SC-310 & SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
- STORMTECH SC-310 & SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS.

STORMTECH RECOMMENDS 3 BACKFILL METHODS:

 - STONESHOOTER LOCATED OFF THE CHAMBER BED.
 - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
 - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
- THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
- MAINTAIN MINIMUM 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4" (20-50 mm).
- THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
- ADS RECOMMENDS THE USE OF "LEASTFORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.

NOTES FOR CONSTRUCTION EQUIPMENT

- STORMTECH SC-310 & SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
 - THE USE OF CONSTRUCTION EQUIPMENT OVER SC-310 & SC-740 CHAMBERS IS LIMITED:
 - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
 - NO RUBBER Tired LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
 - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
 - FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.
- CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.




ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT	
D	FINAL FILL: FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	ANY SOIL/ROCK MATERIALS, NATIVE SOILS, OR PER ENGINEER'S PLANS. CHECK PLANS FOR PAVEMENT SUBGRADE REQUIREMENTS.	N/A	
C	INITIAL FILL: FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 12" (300 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	GRANULAR WELL-GRADED SOIL/AGGREGATE MIXTURES, <35% FINES OR PROCESSED AGGREGATE. MOST PAVEMENT SUBBASE MATERIALS CAN BE USED IN LIEU OF THIS LAYER.	AASHTO M145* A-1, A-2.4, A-3 OR AASHTO M43* 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10	BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL-GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN). DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN).
B	EMBEDMENT STONE: FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	CLEAN, CRUSHED, ANGULAR STONE, NOMINAL SIZE DISTRIBUTION BETWEEN 3/4-2 INCH (20-50 mm)	AASHTO M43* 3, 357, 4, 467, 5, 56, 57	NO COMPACTION REQUIRED.
A	FOUNDATION STONE: FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	CLEAN, CRUSHED, ANGULAR STONE, NOMINAL SIZE DISTRIBUTION BETWEEN 3/4-2 INCH (20-50 mm)	AASHTO M43* 3, 357, 4, 467, 5, 56, 57	PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. **

PLEASE NOTE:

- THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
- STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
- WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.




NOTES:

- SC-740 CHAMBERS SHALL CONFORM TO THE REQUIREMENTS OF ASTM F2418 "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS", OR ASTM F2922 "STANDARD SPECIFICATION FOR POLYETHYLENE (PE) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- SC-740 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- "ACCEPTABLE FILL MATERIALS" TABLE ABOVE PROVIDES MATERIAL LOCATIONS, DESCRIPTIONS, GRADATIONS, AND COMPACTION REQUIREMENTS FOR FOUNDATION, EMBEDMENT, AND FILL MATERIALS.
- THE "SITE DESIGN ENGINEER" REFERS TO THE ENGINEER RESPONSIBLE FOR THE DESIGN AND LAYOUT OF THE STORMTECH CHAMBERS FOR THIS PROJECT.
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- ONCE LAYER 'C' IS PLACED, ANY SOLMATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.

CONCEPTUAL LAYOUT

(5) STORMTECH SC-740 CHAMBERS
(8) STORMTECH SC-740 END CAPS
INSTALLED WITH 6" COVER STONE, 8" BASE STONE, 40% STONE VOID
INSTALLED SYSTEM VOLUME: 4648 CF
AREA OF SYSTEM: 2237 FT²
PERIMETER OF SYSTEM: 256 FT

COMPUTER GENERATED CONCEPTUAL LAYOUT - NOT FOR CONSTRUCTION



Bremen Highway Taco Bell
Mishawaka, IN


DATE: 03/04/2020 DRAWN: DF CHECKED: ---
PROJECT #: 201

StormTech
1800 WILSON BLVD
HILLIARD, OH 43026
1-800-733-7473

ADS
4640 TREHMAN BLVD
HILLIARD, OH 43026
1-800-733-7473

NOT TO SCALE

SHEET 2 OF 5




SC-740 ISOLATOR ROW DETAIL
NTS

INSPECTION & MAINTENANCE

- STEP 1) INSPECT ISOLATOR ROW FOR SEDIMENT
- REMOVE OPEN LID ON NYLOPLAST INLINE DRAIN
 - REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
 - USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
 - LOWER A CAMERA INTO ISOLATOR ROW FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
 - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- B. ALL ISOLATOR ROWS
- REMOVE COVERS FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW
 - USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW THROUGH OUTLET PIPE
 - MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
 - FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE.
 - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW USING THE JETVAC PROCESS
- A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPRAY OF 45' (1.1 m) OR MORE IS PREFERRED
 - APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
 - VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

NOTES

- INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION, ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.



SC-740 6" INSPECTION PORT DETAIL
NTS

Bremen Highway Taco Bell
Mishawaka, IN

DATE: 03/04/2020 DRAWN: DF CHECKED: ---
PROJECT #: 201

StormTech
1800 WILSON BLVD
HILLIARD, OH 43026
1-800-733-7473

ADS
4640 TREHMAN BLVD
HILLIARD, OH 43026
1-800-733-7473

SHEET 4 OF 5

ABONMARCHÉ

17 N. Washington Street
Vincennes, IN 46383
219.850.4625
abonmarche.com

Engineering - Architecture - Land Surveying

TACO BELL 3615 BREMEN HIGHWAY MISHAWAKA, INDIANA

PROJECT:


CHAMBER DETAILS

SHEET TITLE:

DRAWN BY: DEF
DESIGNED BY: DEF
PM REVIEW: MJH
QA/QC REVIEW: RTN

DATE: 3-25-2020

SEAL:




SIGNATURE: *[Signature]*
DATE: 7-1-2020

SCALE: HORIZ: AS SHOWN
VERT:

ACI JOB # 20-0205
SHEET NO. C6.1

2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------



Contractor to coordinate with MMU Electric Department the relocation of the light pole. The contractor will be responsible for new 2" conduit, new foundation with anchor bolts and removal of the old foundation.

- LEGEND**
- (L1) SITE AREA LIGHTS (SPILL CONTROL)

LUMINAIRE SCHEDULE

QTY	SYMBOL	MODEL NUMBER AND DESCRIPTION
5	L1	DSX1 LED P1 30K T2S MVOLT HS DSX1 LED P1 30K T2S MVOLT WITH HOUSE SHIELD TYPE II SPILL CONTROL MOUNTING HEIGHT = 25'

- NOTES**
- LUMINAIRES ARE MANUFACTURED BY LITHONIA LIGHTING. ALL ELECTRICAL WORK SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE NATIONAL ELECTRICAL CODE.
 - ALL WIRE SHALL BE 4-1/C NO. 10 THW COPPER WIRE IN 1 1/2" PVC SCHEDULE 80 CONDUIT FROM THE ELECTRICAL SERVICE PANEL TO THE LIGHTING FOUNDATION AND IN THE POLES TO THE LUMINAIRES. THERE WILL BE NO UNDERGROUND SPLICES ALLOWED AND ALL WIRE SPLICES SHALL BE IN THE POLE BASES.
 - COVERS FOR LIGHTING PULL BOXES SHALL BE WATERPROOF AND BEAR THE WORD "LIGHTING" ON THE COVER.
 - LUMINAIRE POLES SHALL BE FIELD VERIFIED AND APPROVED BY ENGINEER PRIOR TO ORDERING MATERIALS OR PLACING FOUNDATIONS.
 - LUMINAIRE POLES SHALL BE LOCATED 2' BEHIND BACK OF CURB, UNLESS OTHERWISE NOTED.
 - FOUNDATIONS SHALL LEVEL WITH ADJACENT FINISHED GRADE AND HEIGHT ABOVE FINISHED GRADE SHALL MATCH EXISTING LUMINAIRE FOUNDATIONS.
 - FIXTURE ORIENTATION SHALL BE PERPENDICULAR TO THE ADJACENT PAVEMENT UNLESS OTHERWISE NOTED ON PLANS. ORIENTATION OF POLES SHALL BE FIELD VERIFIED AND APPROVED BY ENGINEER PRIOR TO INSTALLATION.
 - ALL SITE LIGHTING SHALL BE LIMITED TO 25' IN HEIGHT. 90° CUT-OFF FIXTURES SHALL BE REQUIRED FOR BOTH POLE AND WALL MOUNTED FIXTURES. SHIELDING OF LIGHTING SHALL BE REQUIRED IN THE AREAS ADJACENT TO (IN SIGHT OF) RESIDENTIAL AREAS. LIGHTING WITHIN 50' OF RESIDENTIALLY ZONED PROPERTY SHALL BE LIMITED TO 15' IN HEIGHT.

ABONMARCHÉ
 750 Lincoln Way E
 South Haven, IN 46601
 Phone: 574.251.4400
 Fax: 574.251.4440
 abonmarche.com


TACO BELL
3615 BREMEN HIGHWAY
MISHAWAKA, INDIANA

PROJECT:

LIGHTING PLAN

SHEET TITLE:

DRAWN BY: DEF
 DESIGNED BY: DEF
 PM REVIEW: MJH
 QA/QC REVIEW: RTN
 DATE: 3-25-2020
 SEAL:



SIGNATURE: [Signature]
 DATE: 7-1-2020

SCALE:
 HORZ: 1" = 20'
 VERT: [Blank]
 ACT JOB #:
20-0205
 SHEET NO.:

C7.1

D-Series Size 1 LED Area Luminaire

Specifications
 EPA: 1.01 ft (0.31m)
 Length: 33" (0.84m)
 Width: 13" (0.33m)
 Height H1: 7-1/2" (0.19m)
 Height H2: 3-1/2" (0.09m)
 Weight (max): 27 lbs (12.3kg)

Ordering Information
 EXAMPLE: DSX1 LED P7 40K T3M MVOLT SPLA NLTAR2 PIRHN DBBKD

Series	Optic	Color Temperature	Mounting	Voltage	Mounting
DSX1 LED	Forward optics				
	P1	PK	T75	120V	SPMA
	P2	PS	T85	120V	SPMA
	P3	PS	T95	120V	SPMA
	P4	PK	T105	120V	SPMA
	P5	PK	T115	120V	SPMA
	P6	PK	T125	120V	SPMA
	P7	PK	T135	120V	SPMA
	P8	PK	T145	120V	SPMA
Recessed optics					
P10	P12	T15	120V	SPMA	
P11	P13	T15	120V	SPMA	

Ordering Information
 DSX1 LED P1 PK T75 40K T3M MVOLT SPLA NLTAR2 PIRHN DBBKD

Shipping Information
 DSX1 LED P1 PK T75 40K T3M MVOLT SPLA NLTAR2 PIRHN DBBKD

Ordering Information

Accessories



Options

Drilling


Tenon Mounting Slipfitter**

Series	Optic	Color Temperature	Mounting	Voltage	Mounting
2-1/8"	SPMA	AST5-190	AST5-290	AST5-390	AST5-490
2-1/8"	SPMA	AST5-190	AST5-290	AST5-390	AST5-490
2-1/8"	SPMA	AST5-190	AST5-290	AST5-390	AST5-490
4"	SPMA	AST5-190	AST5-290	AST5-390	AST5-490


Typical Light Pole Foundation Detail




2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------




PIPE BOLLARD
(NOT TO SCALE)



**PAVEMENT MARKINGS:
CROSSWALK & NO ACCESS AREA**
(NOT TO SCALE)





STANDARD SPACE




ADA ACCESSIBLE SPACE

**PAVEMENT MARKINGS:
TYPICAL PARKING SPACE**
(NOT TO SCALE)




DUMPSTER ENCLOSURE ELEVATIONS
(NOT TO SCALE)




- Notes:
1. See Construction Notes, this sheet for joint specifications.
2. Install an expansion joint along the back of walk, if adjacent to a structure.

CONCRETE SIDEWALK WITH INTEGRAL CURB
(NOT TO SCALE)




RAMP ISOMETRIC


SIDEWALK CURB RAMP
(NOT TO SCALE)




COMBINATION CURB & GUTTER
(NOT TO SCALE)



CONCRETE CURB
(NOT TO SCALE)




INTEGRAL CONCRETE CURB, 8\"/>




Note: Thicken edge of concrete as shown at transitions from concrete to asphalt pavement.


CONCRETE PAVEMENT THICKENED EDGE
(NOT TO SCALE)




CONCRETE CURB
(NOT TO SCALE)



INTEGRAL CONCRETE CURB, 8\"/>



TYPICAL SIGN & POST
(NOT TO SCALE)



NOTES:

1. Minimum restrained joint length required for the given pipe size, depth, material, soil condition, etc. Use 1.5:1 safety factor and 150 psi test pressure (Typical Each Side)
2. Provide adequate support if the obstacle is in place before the water main is constructed.

WATER PIPE / UTILITY CONFLICT CROSSINGS
(NOT TO SCALE)


STORM SEWER CASTINGS

All castings shall be stamped with a Fish Image and the lettering "Dump No Waste" "Drains to Waterways"


STRUCTURES IN CURB LINE
NEENAH R-3010 or approved equal

STRUCTURES IN PAVEMENT
NEENAH R-2502 or approved equal


STRUCTURES IN LAWN
NEENAH R-2560-C or approved equal




COVER CAP FOR 48" MANHOLE
(NOT TO SCALE)




STANDARD 48" STORM MANHOLE
(NOT TO SCALE)



WATER SERVICE DETAIL
(DOMESTIC AND FIRE)
(NOT TO SCALE)





DOWNSPOUT CONNECTOR
(NOT TO SCALE)








STANDARD STORM INLET
(NOT TO SCALE)



2	UPDATE ADDRESS	DEF	8/10/20
RNUM	RDESC	RBY	RDATE



AS-BUILT DETAIL
(NOT TO SCALE)




2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------



- INSTALLATION**
1. Remove all vegetation and other objectionable material from the foundation area.
 2. Grade foundation and crown for positive drainage. If the slope of the construction entrance is toward a public road and exceeds two percent, construct an 8-inch high diversion ridge with a ratio of 3-to-1 side slopes across the foundation area about 15 feet from the entrance to divert runoff away from the road.
 3. Install a culvert pipe under the pad if needed to maintain proper public road drainage.
 4. If wet conditions are anticipated, place geotextile fabric on the graded foundation to improve stability.
 5. Place specified aggregate to the dimensions shown leaving the surface smooth and sloped for drainage.
 6. Top-dress the first 50 feet adjacent to the public roadway with 2-3 inches of washed #53 aggregate [optional, used primarily where the purpose of the pad is keep soil from adhering to vehicle tires]
 7. Where possible, divert all storm water runoff and drainage from the pad to a sediment trap or basin.
- MAINTENANCE**
1. Inspect daily.
 2. Reshape pad as needed for drainage and runoff control.
 3. Top dress with clean aggregate as needed.
 4. Immediately remove mud and sediment tracked or washed onto public roads.
 5. Flushing should only be used if the water can be conveyed into a sediment trap or basin

Temporary Construction Entrance
(Not to Scale)




- INSTALLATION**
1. Prior to installation, Contractor shall submit brand and model information to Owner for approval prior to installation. Install per manufacturer recommendations.
 2. Remove grate and clean ledge of the casting frame or drainage structure.
 3. Drop frame and sediment bag insert onto load bearing lip of casting or concrete structure
 4. Re-install grate and confirm it is elevated no more than thickness of insert hangers.
- MAINTENANCE**
1. Inspection should occur at least once a week and following each 1/2" or more rain event.
 2. Empty the sediment bag if more than half filled with sediment and debris.
 3. Remove the grate, engage the lifting bars or handles and lift from the drainage structure, and dispose of any sediment or debris in accordance with EPA Guidelines.
 4. Remove any caked on silt from the sediment bag and reverse flush the bag with medium spray for optimal filtration.
 5. Replace the bag if torn or punctured to 1/2" diameter or greater on the lower half of the bag.
 6. When the contributing drainage area within 50 feet upstream of the inlet has been stabilized, remove insert (basket) and properly dispose of sediment deposits.

Temporary Inlet Protection
(Not to Scale)

- Notes**
1. Any storm sewer inlets in or adjacent to the construction limits shall be protected as specified on the plan or an approved equal. The intent of this measure is to prevent sediment from entering any drainage systems.
 2. Until the project is accepted by the Owner, the Contractor shall maintain all erosion control measures to prevent sediment from entering any public or private storm sewers and from leaving the project site. Contractor shall implement and maintain any additional measures at the request of the Local and/or State Storm Water and Erosion Control Inspectors at no additional cost.
 3. Silt Fencing - Tentative location shown on plan. Actual field conditions shall indicate the location and amount of silt fencing required to prevent sediment from entering public and private storm sewers and from leaving the project site. Silt fencing or other appropriate sediment barrier shall be installed a minimum of 10' away from the toe of slope stockpile, borrow, and/or disposal areas.
NO OFFSITE SEDIMENT FLOWS OR SEDIMENT LADEN STORMWATER FLOWS ARE TO OCCUR AT ANY TIME. INSTALL SILT FENCING ON AN AS NEEDED BASIS.
 4. Locations for concrete washout and temporary construction staging shall be determined by the Contractor and Owner prior to construction.
 5. All areas disturbed by construction shall be stabilized with seeding or an alternative surface stabilization measure. Temporary Seeding shall take place as soon as possible on any bare or thinly vegetated areas which have less than 70 percent cover and will remain inactive for a period of 15 days or more.

EROSION CONTROL LEGEND

- Erosion Control Blankets
- Silt Fence
- Inlet Protection




2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------

ABONMARCHÉ
 750 Lincoln Way E
 South Haven, IN 46601
 Phone: 574.231.4400
 Fax: 574.231.4440
 abonmarche.com

TACO BELL
3615 BREMEN HIGHWAY
MISHAWAKA, INDIANA

EROSION CONTROL PLAN

DRAWN BY: DEF
DESIGNED BY: DEF
PM REVIEW: MJH
QA/QC REVIEW: RTN
DATE: 3-25-2020





SIGNATURE: [Signature]
DATE: 7-1-2020

SCALE:
HORIZ: 1" = 20'
VERT:
ACI JOB #
20-0205

SHEET NO.
C9.0

Engineering - Architecture - Land Surveying




Installation

1. Dependent upon the type of system, either excavate the pit or install the containment system. For prefabricated containers, locate, and install according to the manufacturer's recommendations.
2. A base shall be constructed and prepared that is free of rocks and other debris that may cause tears/punctures in the polyethylene lining.
3. Install the polyethylene lining. For excavated systems, the lining should extend over the entire excavation. The lining for bermed systems should be installed over the pooling area with enough material to extend the lining over the berm or containment system. The lining should be secured with pins, staples, or other fasteners.
4. Place flags, safety fencing, or equivalent to provide a barrier to construction equipment and other traffic.
5. Place a non-collapsing, non-water holding cover over the washout facility prior to a predicted rainfall event to prevent accumulation of water and possible overflow of the system (optional).
6. Install signage that identifies concrete washout areas and post signs directing contractors and suppliers to designated locations.
7. Where necessary, provide stable ingress and egress or alternative approach pad for concrete washout systems.


Maintenance

1. Inspect daily and after each storm event – inspect the integrity of the overall structure and containment system where applicable.
2. Inspect the system for leaks, spills, and tracking of soil by equipment, and the polyethylene lining for failure, including tears and punctures.
3. Once concrete wastes harden, remove and dispose of the material.
4. Excess concrete should be removed when the washout system reaches 50 percent of the design capacity. Use of the system should be discontinued until appropriate measures can be initiated to clean the structure. Prefabricated systems should also utilize this this criterion, unless the manufacturer has alternate specifications.
5. Upon removal of the solids, inspect the structure. Repair the structure as needed or construct a new system.
6. Dispose of all the concrete in a legal manner. Reuse the material on site, recycle, or haul the material to an approved construction/demolition landfill site. Recycling of material is encouraged. The waste material can be used for multiple applications including but not limited to roadbeds and building. The availability for recycling should be checked locally.
7. The plastic liner should be replaced after every cleaning; the removal of material will usually damage the lining.
8. The concrete washout system should be repaired or enlarged as necessary to maintain capacity for concrete waste.
9. Concrete washout systems are designed to promote evaporation. However, if the liquids do not evaporate and the system is near capacity it may be necessary to vacuum or remove the liquids and dispose of them in an acceptable method. Disposal may be allowed at the local sanitary sewer authority provided their national pollutant discharge elimination system permits allow for acceptance of this material. Another option would be to utilize a secondary containment system or basin for further dewatering.
10. Prefabricated units are often pumped and the company supplying the unit provides this service.
11. Inspect construction activities on a regular basis to ensure suppliers, contractors, and others are utilizing designated washout areas. If concrete waste is being disposed of improperly, identify violators and take appropriate action.
12. When concrete washout systems are no longer required, the concrete washout system shall be closed. Dispose of all hardened concrete and other materials used to construct the system.
13. Holes, depressions and other land disturbances associated with the system should be backfilled, graded, and stabilized.

Concrete Washout Structure
(Not to Scale)



Erosion Control Blanket Slope Stabilization
(Not to Scale)



Installation


1. Lay out the location of the fence so that it is parallel to the contour of the slope and at least 10 feet beyond the toe of the slope to provide a sediment storage area. Turn the ends of the fence up slope such that the point of contact between the ground and the bottom of the fence and terminates at a higher elevation than the top of the fence at its lowest point.
2. Excavate an 8-inch deep by 4-inch wide trench along the entire length of the fence. (installation by plowing is acceptable)
3. Install silt fence with the filter fabric located on the up-slope side of the excavated trench and the support posts on the down-slope side of the trench.
4. Drive the support posts at least 18 inches into the ground, tightly stretching the fabric between the posts as each is driven into the soil. A minimum of 12 inches of the filter fabric should extend into the trench.
5. Lay the lower 4 inches of fabric on the bottom of the trench and extend it toward the up-slope side of the trench.
6. Backfill the trench with soil material and compact it in place.
7. If the silt fence is being constructed onsite, attach the filter fabric to the support posts and attach wooden lathe to secure the fabric to the posts. Allow for at least 12 inches of fabric below ground level. Complete the silt fence installation, following steps 1 through 6 above.

Maintenance

1. Inspect within 24 hours of a half-inch or greater rain event and at least once every week.
2. If fence fabric tears or starts to decompose, or in any way becomes ineffective, replace the section immediately in accordance with installation specifications above.
3. Remove deposited sediment when it causes filter fabric to bulge or when it reaches 1/2 the height of the fence at its lowest point.
4. When the contributing drainage area has been stabilized, remove the fence and sediment deposits, grade the site to blend with the surrounding area and stabilize.


Temporary Silt Fence
(Not to Scale)

2	UPDATE ADDRESS	DEF	8/10/20
---	----------------	-----	---------



FOUNDATION PLAN
SCALE: 1/4" = 1'-0"

PROJECT NUMBER	20-0616
PROJECT MANAGER	RAD
PROJECT ENGINEER	SA
PROJECT DRAFTER	MJN



△	OWN/STATE COMMENTS 08.10.20
△	
△	
△	
△	
△	
△	
△	
△	
△	

CONTRACT DATE:	8/26/19
BUILDING TYPE:	EXP. LITE MED40
PLAN VERSION:	MARCH 2018
BRAND DESIGNER:	DAN DICKSON
SITE NUMBER:	314007
STORE NUMBER:	TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544



FOUNDATION PLAN


S1.0

DESIGN CRITERIA	D
<p>DESIGN CRITERIA:</p> <p>2012 IBC</p> <p>ROOF SNOW LOADS:</p> <p>GROUND SNOW LOAD (Pg): 30 PSF</p> <p>EXPOSURE FACTOR (Ce): 1.0</p> <p>IMPORTANCE FACTOR (I): 1.0</p> <p>THERMAL FACTOR (Ct): 1.0</p> <p>ROOF LOADS:</p> <p>LIVE LOAD: 20 PSF</p> <p>DEAD LOAD: 20 PSF</p> <p>WIND LOADS:</p> <p>3 SECOND GUST: 115 MPH</p> <p>RISK CATEGORY: II</p> <p>EXPOSURE CATEGORY (MWFRS): C</p> <p>INTERNAL PRESSURE COEFF.: ±.18</p> <p>PROVIDE SHOP DRAWINGS AND CALCULATIONS BY REGISTERED ENGINEER FOR SIGNS AND ROOF TRUSSES.</p>	<p>SEISMIC LOADS:</p> <p>RISK CATEGORY: II</p> <p>SEISMIC IMPORTANCE FACTOR: 1.0</p> <p>SITE CLASS: D</p> <p>MAPPED SPECTRAL RESPONSE ACCEL:</p> <p>Ss: 0.097g</p> <p>S1: 0.057g</p> <p>SPECTRAL RESPONSE COEFF.:</p> <p>SHORT PERIODS (SDS): 0.103g</p> <p>1 SEC. PERIODS (SD1): 0.092g</p> <p>SEISMIC DESIGN CATEGORY: B</p> <p>ANALYSIS BY EQUIVALENT LATERAL LOAD PROCEDURE</p>

FOUNDATION	C															
<p>1. FOUNDATION DESIGN IS BASED UPON THE GEOTECHNICAL ENGINEERING REPORT BY GME TESTING, PROJECT NUMBER G20-050162 DATED 5/29/2020.</p> <p>2. CONTRACTOR TO PROVIDE FOUNDATION & FOOTING AS REQUIRED FOR PYLON OR MONUMENTAL SIGN. SEE ELECTRICAL DRAWINGS FOR DETAIL.</p> <p>3. COORDINATE STRUCTURAL PLANS AND DETAILS WITH REQUIREMENTS OF GEOTECHNICAL REPORT. FOUNDATION DESIGN IS BASED ON 1,000 PSF ALLOWABLE BEARING CAPACITY.</p> <p>4. CONTRACTOR SHALL TREAT SOIL BELOW SLAB FOR TERMITES.</p> <p>5. REFER TO THE GEOTECHNICAL REPORT FOR GENERAL REQUIREMENTS OF EARTHWORK, OVEREXCAVATION, SUBGRADE PREPARATION, FILL AND COMPACTION, WATERPROOFING AND OTHER PERTINENT REQUIREMENTS AND INFORMATION.</p> <p>6. PROTECT PIPES AND CONDUITS RUNNING THROUGH WALLS AND SLABS WITH 1/2 INCH EXPANSION MATERIAL. LOWER CONTINUOUS FOOTINGS AND GRADE BEAMS PERPENDICULAR TO PIPE RUNS TO ALLOW PIPES TO PASS ABOVE THE FOOTINGS OR THROUGH THE GRADE BEAMS. ALTERNATIVELY, PROVIDE A CONCRETE JACKET IF PIPES ARE LOW ENOUGH TO BE PLACED BELOW THE FOOTINGS AND GRADE BEAMS. LOWER FOOTINGS AND GRADE BEAMS PARALLEL TO PIPE RUNS TO AVOID SURCHARGE ONTO ADJACENT TRENCH EXCAVATIONS.</p> <p>7. MAINTAIN SUBGRADE AND FILL MOISTURE CONTENT UNTIL FOUNDATIONS ARE PLACED.</p> <p>8. ARRANGE FOR OWNER'S INDEPENDENT TESTING AGENCY TO MONITOR CUT AND FILL OPERATIONS AND PERFORM FIELD DENSITY AND MOISTURE CONTENT TESTS TO VERIFY COMPACTION AND APPROVE FOOTING SUBGRADES PRIOR TO PLACING CONCRETE.</p> <p>9. DO NOT PLACE FOOTINGS OR SLABS AGAINST SUBGRADE CONTAINING FREE WATER, FROST, OR ICE.</p> <p>10. MAINTAIN PROPER SITE DRAINAGE DURING CONSTRUCTION TO ENSURE SURFACE RUNOFF AWAY FROM STRUCTURES AND TO PREVENT PONDING OF SURFACE RUNOFF NEAR THE STRUCTURES.</p>	<p>CONCRETE:</p> <p>A. CONCRETE SHALL BE HARD ROCK CONC. (5 SACK CEMENT PER CU YD. MIN.) AND MEET THE FOLLOWING MIN. ULTIMATE COMPRESSIVE STRENGTHS AT 28 DAYS:</p> <table border="1"> <thead> <tr> <th>LOCATION</th> <th>MIN. STRENGTH (28 DAYS DESIGN)</th> <th>AGGREGATE SIZE - INCHES</th> <th>SLUMP INCHES</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>SLAB ON GRADE</td> <td>4000</td> <td>1" x #4</td> <td>3-1/2"</td> <td>±1/2"</td> </tr> <tr> <td>FOUNDATIONS</td> <td>3000</td> <td>1" x #4</td> <td>3-1/2"</td> <td>±1/2"</td> </tr> </tbody> </table> <p>B. CONCRETE MIX DESIGN AND TESTING SHALL MEET WITH THESE SPECS. CEMENT SHALL BE IN ACCORDANCE WITH ASTM C 150 TYPE II. VERIFY MIN. CONC. STRENGTH AND CEMENT TYPE.</p> <p>C. REINFORCING STEEL SHALL CONFORM TO ASTM A-615, GRADE 60. STEEL SHALL BE KEPT CLEAN AND FREE OF RUST.</p> <p>D. CONCRETE CURING SHALL BE IN ACCORDANCE WITH REQUIREMENTS OF ACI-318-95 SECTION 5.11 AND STANDARD PRACTICE FOR CURING CONCRETE REPORTED BY COMMITTEE 308.</p> <p>E. ANCHOR BOLTS - A36 OR A307, USE 5/8" DIAMETER x 12" ANCHOR BOLTS (A.B.) AT 48" O.C. U.O.N. ANCHOR BOLTS SHALL BE TIED IN PLACE PRIOR TO PLACEMENT OF CONC.</p> <p>F. TO RESIST FREEZE - THAW DETERIORATION W/C. RATIO SHALL NOT EXCEED .50 FOR CONCRETE IN CONTACT WITH SOILS.</p> <p>G. TOTAL AIR CONTENT TO BE 6% ± 1.5%.</p> <p>SLAB:</p> <p>A. DESIGN IS BASED UPON 4" THICK CONCRETE SLAB REINFORCED W/ WWF 6x6-W1.4x1.4 OR #4 BARS @ 18" O.C. EA. WAY, OVER 10 MIL VISQUEEN MEMBRANE, OVER 6" OF GRANULAR FILL. SLAB SUBGRADE SHALL BE COMPACTED TO ACHIEVE 95 PERCENT OR MORE PER ASTM D-1557. SEE GEOTECHNICAL REPORT FOR ADDITIONAL INFORMATION.</p>	LOCATION	MIN. STRENGTH (28 DAYS DESIGN)	AGGREGATE SIZE - INCHES	SLUMP INCHES	TOLERANCE	SLAB ON GRADE	4000	1" x #4	3-1/2"	±1/2"	FOUNDATIONS	3000	1" x #4	3-1/2"	±1/2"
LOCATION	MIN. STRENGTH (28 DAYS DESIGN)	AGGREGATE SIZE - INCHES	SLUMP INCHES	TOLERANCE												
SLAB ON GRADE	4000	1" x #4	3-1/2"	±1/2"												
FOUNDATIONS	3000	1" x #4	3-1/2"	±1/2"												

FOUNDATION PLAN NOTES	C
<p>MISCELLANEOUS:</p> <p>A. DIMENSIONS NOTED ARE TO FACE OF CONCRETE. REFER TO DWG. A1.0 FOR DIMENSIONS TO FACE OF STUD AND OTHER DIMENSIONS NOT OTHERWISE NOTED.</p> <p>B. DRAWINGS SHALL NOT BE SCALED. ALL DIMENSIONS AND FIT SHALL BE DETERMINED AND VERIFIED BY THE CONTRACTOR PRIOR TO COMMENCEMENT OF WORK.</p> <p>C. DETAILS NOT FULLY OR SPECIFICALLY SHOWN SHALL BE OF SAME NATURE AS OTHER SIMILAR CONDITIONS.</p> <p>D. SEE PLUMB DWGS. FOR PLUMB. LAYOUT DIMENSIONS, U.O.N.</p> <p>E. SEE ELECT DWGS. FOR ELECT. LAYOUT DIMENSIONS, U.O.N.</p> <p>F. COORD. FOUNDATION AND SLAB LAYOUT WITH OTHER TRADES PRIOR TO POURING SLAB.</p>	<p>1 FLOOR DRAINS LOCATED 1/2" BELOW T.O. SLAB. SLOPE SLAB AS INDICATED ON PLAN TO PROVIDE POSITIVE DRAINAGE.</p> <p>2 PROVIDE HUB DRAIN (HD) UNLESS REQUIRED BY LOCAL CODE TO HAVE FLOOR SINK (FS).</p> <p>3 INDICATES INSIDE SURFACE OF FOOTING. SEE SHEET S4.0, BOTTOM OF FOOTING (B.O.F.)</p> <p>4 DEPRESSED FOUNDATION WALL AT THRESHOLD. SEE 3/S4.0.</p> <p>5 ANCHOR BOLTS LOCATED THROUGHOUT PERIMETER OF BUILDING SHALL BE PROVIDED AS REQUIRED PER THE "PLATE/ANCHOR BOLT" COLUMN OF THE "WALL SHEATHING AND SHEARWALL SCHEDULE." SEE D/S2.0.</p> <p>6 AT OWNER/ CONTRACTOR OPTION: VESTIBULE.</p> <p>7 NOT USED.</p> <p>8 (2) HDU14-SDS2.5 HOLDDOWN ANCHOR AT EACH END OF SHEARWALL. SEE 6/S4.0 FOR HOLDDOWN EMBEDMENT DETAIL.</p> <p>9 4" CONCRETE SLAB REINFORCED W/ WWF6x6-W1.4x1.4 OR #4 BARS @ 18" O.C. EA. WAY OVER MIN. 10 MIL. POLYETHYLENE VAPOR BARRIER, OVER 4" AGGREGATE BASE OVER SUBGRADE.</p> <p>10 HDU8-SDS2.5 HOLDDOWN ANCHOR AT EACH END OF SHEARWALL. SEE 6/S4.0 FOR HOLDDOWN EMBEDMENT DETAIL.</p> <p>11 NOT USED</p>

KEY NOTES	B
<p>1 FLOOR DRAINS LOCATED 1/2" BELOW T.O. SLAB. SLOPE SLAB AS INDICATED ON PLAN TO PROVIDE POSITIVE DRAINAGE.</p> <p>2 PROVIDE HUB DRAIN (HD) UNLESS REQUIRED BY LOCAL CODE TO HAVE FLOOR SINK (FS).</p> <p>3 INDICATES INSIDE SURFACE OF FOOTING. SEE SHEET S4.0, BOTTOM OF FOOTING (B.O.F.)</p> <p>4 DEPRESSED FOUNDATION WALL AT THRESHOLD. SEE 3/S4.0.</p> <p>5 ANCHOR BOLTS LOCATED THROUGHOUT PERIMETER OF BUILDING SHALL BE PROVIDED AS REQUIRED PER THE "PLATE/ANCHOR BOLT" COLUMN OF THE "WALL SHEATHING AND SHEARWALL SCHEDULE." SEE D/S2.0.</p> <p>6 AT OWNER/ CONTRACTOR OPTION: VESTIBULE.</p> <p>7 NOT USED.</p> <p>8 (2) HDU14-SDS2.5 HOLDDOWN ANCHOR AT EACH END OF SHEARWALL. SEE 6/S4.0 FOR HOLDDOWN EMBEDMENT DETAIL.</p> <p>9 4" CONCRETE SLAB REINFORCED W/ WWF6x6-W1.4x1.4 OR #4 BARS @ 18" O.C. EA. WAY OVER MIN. 10 MIL. POLYETHYLENE VAPOR BARRIER, OVER 4" AGGREGATE BASE OVER SUBGRADE.</p> <p>10 HDU8-SDS2.5 HOLDDOWN ANCHOR AT EACH END OF SHEARWALL. SEE 6/S4.0 FOR HOLDDOWN EMBEDMENT DETAIL.</p> <p>11 NOT USED</p>	<p>FOUNDATION PLAN</p> <p>S1.0</p> <p>6/29/20</p>



WALL FRAMING PLAN

SCALE:

MARK	BUILT-UP SECTION	MANUF. MEMBER
1	(3) 2x12	-
2	(3) 2x8	-
3	(3) 2x6	-

NOTES:
1. BUILT-UP HEADER SECTION SHALL HAVE 1/2" PLYWOOD SANDWICHED PIECES. REF 14/S4.1

SW	SHEATHING	EDGE	FIELD	PLATE / ANCHOR BOLT	REMARKS
1	1/2" CDX PLYWD (32/16), PS1 RATING	6d @ 6" O.C.	10d @ 12" O.C.	5/8" DIA. F1554 (8x3) @ 32" O.C. W/ WASHER	PLYWOOD ON EXTERIOR FACE OF STUDS
2	1/2" CDX PLYWD (32/16), PS1 RATING	8d @ 4" O.C.	10d @ 12" O.C.	5/8" DIA. F1554 (8x3) @ 32" O.C. W/ WASHER	PLYWOOD ON EXTERIOR FACE OF STUD
3	1/2" CDX PLYWD (32/16), PS1 RATING	10d @ 2" O.C.	10d @ 12" O.C.	5/8" DIA. F1554, (8x3) @ 12" O.C. W/ WASHER	PLYWOOD ON BOTH SIDES OF WALL
***	1/2" CDX PLYWD (32/16), PS1 RATING	10d @ 6" O.C.	10d @ 12" O.C.	5/8" DIA. F1554, (8x3) @ 48" O.C. W/ WASHER	NAILING @ HEADERS PER 12/S4.1

*** REQUIREMENTS FOR EXTERIOR NON-SHEARWALL WALLS

- OSB OF COMPARABLE THICKNESS MAY BE USED IN LIEU OF PLYWOOD WHEN APPROVED IN WRITING BY THE PROJECT ENGINEER AND THE LOCAL JURISDICTION OF COMPARABLE THICKNESS MAY BE USED IN LIEU OF PLYWOOD WHEN APPROVED IN WRITING BY THE PROJECT ENGINEER AND THE LOCAL JURISDICTION.
- BLOCK ALL UNSUPPORTED EDGES WITH 2x MATERIAL U.O.N. BLOCK EDGES WITH 3x MATERIAL WHERE 10d NAILING IS 3" O.C. OR LESS AND 8d NAILING IS 2" O.C. OR LESS. ALL UNSUPPORTED EDGES WITH 2x MATERIAL U.O.N. BLOCK EDGES WITH 3x MATERIAL WHERE 10d NAILING IS 3" O.C. OR LESS AND 8d NAILING IS 2" O.C. OR LESS.
- ALL PLYWOOD NAILS SHALL BE COMMON WIRE. SEE SPECIFICATIONS FOR OTHER NAIL REQUIREMENTS.
- EXTERIOR WALLS NOT DESIGNATED AS SHEARWALLS IN THE WALL FRAMING PLAN SHALL MEET REQUIREMENTS INDICATED FOR NON-SHEARWALL WALLS IN THE SCHEDULE ABOVE. EXTERIOR WALLS NOT DESIGNATED AS SHEARWALLS IN THE WALL FRAMING PLAN SHALL MEET REQUIREMENTS INDICATED FOR NON-SHEARWALL WALLS IN THE SCHEDULE ABOVE.
- SHEARWALL LENGTHS WHERE NOTED ARE MINIMUM. DO NOT LOCATE HOLDDOWNS FROM THESE DIMENSIONS. SEE ARCH DWGS FOR ACTUAL WALL LENGTHS. SHEARWALL LENGTHS WHERE NOTED ARE MINIMUM. DO NOT LOCATE HOLDDOWNS FROM THESE DIMENSIONS. SEE ARCH DWGS FOR ACTUAL WALL LENGTHS.
- HD REFERS TO SIMPSON STRONGTIE CO. HOLDDOWNS. INSTALL PER 6/S4.0. POST WIDTH SHALL MATCH STUD WALL WIDTH. SEE FOUNDATION PLAN FOR OTHER REQ'S.
- EDGE NAIL WALL PLY TO STUDS OR POSTS WITH HOLD-DOWNS.
- WHERE PANELS ARE APPLIED TO BOTH FACES OF A WALL AND NAIL SPACING IS LESS THAN 6" O.C. ON EITHER SIDE, PANEL JOINTS SHALL BE OFFSET TO WALL ON DIFFERENT FRAMING MEMBERS OR FRAMING SHALL BE 3x OR THICKER AND NAILS ON EACH SIDE SHALL BE STAGGERED.

WALL SHEATHING AND SHEARWALL SCHEDULE

WALL FRAMING:

- EXTERIOR WALL NON-BEARING & BEARING STUDS SHALL BE NO. 2 DOUG-FIR. 6x6 POSTS TO BE DOUG-FIR #2. INTERIOR WALL STUDS MAY BE STUD GRADE.
- ALL BEAMS AND JOISTS SHALL BE SEAT CUT FOR FULL UNIFORM BEARING AT SUPPORTS, BEAM SEATS AND COLUMN CAPS. SEE SHEET A1.0 FOR DIMENSIONS.
- EXTERIOR STUD WALLS ARE 2x6 AT 16" O.C. U.O.N.
- ALL WOOD IN CONTACT WITH CONC., STEEL OR GRADE SHALL BE PRESSURE TREATED.
- ALL BOLTED OR NAILED STRAP CONNECTIONS SHALL HAVE AN EQUAL NUMBER OF BOLTS OR NAILS EACH SIDE OF THE SPLICE JOINT. THE FIRST BOLT OR NAIL FROM EACH SIDE OF THE SPLICED OR TREATED MEMBER SHALL BE EQUAL DISTANCE FROM THE SPLICE. STRAPS USING 16d NAILS ON 2x MATERIAL SHALL BE INSTALLED ON THE 1-1/2" EDGE OF THE MEMBER.
- THE CONTRACTOR SHALL VERIFY THAT THE MOISTURE CONTENT OF ALL FRAMING LUMBER AND PLYWOOD MEET THE REQUIREMENTS OF THE SPECS. AT THE TIME OF INSTALLATION AND AT CLOSE-IN.
- USE AT PRESSURE TREATED LUMBER AT WINDOW JAMBS, SILL AND STUDS UNDER SILL AS WELL AS ALL TOILET PLUMBING WALLS.

STUD LAYOUT:

- LAYOUT STUDS ON SIDEWALLS (LONG WALLS) STARTING AT REAR OF BUILDING TOWARDS FRONT.
- LAYOUT STUDS ON ENDWALLS (SHORT WALLS) STARTING AT EACH END AND WORKING TOWARDS CENTER.

FRAMING PLAN NOTES

- COORDINATE WITH ELECTRICAL POWER PLAN SHEET E3.0.
- INTERIOR NON-BEARING STUD WALL FRAMING: REFER TO SHEET A1.0 FOR DIMENSIONS AND STUD SIZES. SEE DETAIL 10 & 11/S4.1 AND WALL FRAMING NOTES.
- (2) 2x6 TOP PLATES - SPLICE PER 12/S4.1. U.O.N. REF. 1/S4.3 FOR CAP DETAIL.
- TOP OF TRUSS BEARING PLATE. SEE DETAIL 2/S4.1.
- TOP OF PARAPET. SEE DETAIL 1/S4.3.
- FREEZER/COOLER BY MANUFACTURER.
- COORDINATE WITH PLUMBING ROUGH IN SHEET P4.0.
- AT OWNER/ CONTRACTOR OPTION: VESTIBULE.
- USE (2) 2x6 BUILT UP STUDS AT 16" O.C. FOR EXTERIOR TOWER STUD WALL.
- POST TO HEADER CONNECTION PER DETAIL 6/S4.3

KEY NOTES

PROJECT NUMBER 20-0616
PROJECT MANAGER RAD
PROJECT ENGINEER SA
PROJECT DRAFTER MJN

CARUSO TURLEY SCOTT INC.
consulting structural engineers
1215 W. Rio Salado Pkwy
Suite 200
Tempe, Arizona 85281
(480) 774-1700
(480) 774-1701 FAX



OWN/STATE COMMENTS	DATE
	08.10.20


CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544



WALL FRAMING PLAN

S2.0



ROOF FRAMING PLAN
SCALE: 1/4" = 1'-0"

ROOF FRAMING PLAN 1/4" = 1'-0" **A**

TYPE	NAILING / SHEATHING	REMARKS
BN	10d @ 6" O.C.	
EN	10d @ 6" O.C.	
FN	10d @ 12" O.C.	
ROOF SHEATHING	5/8" CDX PLYWOOD (4020), PS1 RATING	

NOTE:
SEE 8/S4.2 FOR DEFINITIONS.

ROOF FRAMING NOTES:

- A. ALL UNSUPPORTED EDGES OF PLYWOOD SHEATHING SHALL BE SUPPORTED WITH SIMPSON PSCL CLIPS, PROVIDE (2) CLIPS EQUALLY SPACED BETWEEN EACH TRUSS/SUPPORT. SEE DETAIL 9/S4.2. OSB OF COMPARABLE THICKNESS MAY BE USED IN LIEU OF PLYWOOD WHEN APPROVED IN WRITING BY THE PROJECT ENGINEER AND THE LOCAL JURISDICTION.
- B. ALL MECHANICAL SUPPLY AND RETURN OPENINGS SHALL BE BETWEEN FRAMING U.O.N.

MANUFACTURED ROOF TRUSS NOTES:

- A. MFR'D ROOF TRUSSES ARE AT 2'-8" O.C. U.O.N.
- B. "T" # DENOTES ROOF TRUSS TYPE. REFER TO SCHEDULE 7/S4.2.
- C. TRUSS DWGS ARE PROVIDED FOR CONCEPTUAL DESIGN ONLY. MFR SHALL SUBMIT SHOP DWGS AND CALCS, BOTH SIGNED BY A LICENSED STRUCTURAL ENGINEER (STATE OF INDIANA). SUBMIT SHOP DWGS AND CALCS TO THE ARCHITECT AND ENGINEER FOR REVIEW AND SUBMITTAL AND, IF REQUIRED, TO BLDG OFFICIAL FOR APPROVAL PRIOR TO FABRICATION. SHOP DWGS SHALL INCLUDE LAYOUT PLAN AND CONNECTORS. CALCS SHALL BE BASED ON THE SPECIFIED LOADING CONDITIONS SHOWN HEREIN. MFR SHALL PROVIDE HANGERS AND CONNECTIONS BETWEEN TRUSSES. REVIEW AND APPROVE DIMENSIONS, SHAPES AND DETAILS SHOWN ON SHOP DWGS PRIOR TO SUBMITTAL TO THE ARCHITECT / ENGINEER FOR REVIEW AND COMMENT.
- D. TRUSS MFR SHALL PROVIDE HANGERS AND CONNECTORS ADEQUATE FOR LOADS. ROOF CONNECTORS ARE BASED UPON SIMPSON "STRONG TIE" OR APPROVED EQUAL.
- E. TRUSS CHORDS AND PARAPET VERTICALS SHALL BE 2x6 MIN AND CONSISTENTLY SIZED THROUGHOUT PROJECT.

- F. REFER TO TRUSS ELEVATIONS FOR SHAPE, OVERHANG, SLOPES, SPAN, ETC. LOCATION OF BEARING POINTS ARE AS INDICATED ON THE DRAWINGS. SEE 2/S4.2.
- G. MFR'D ROOF TRUSS DESIGN LOADS: SEE TRUSS DESIGN CRITERIA 3/S4.2.
- H. THE POSITIONS, WEIGHTS, AND METHODS OF ATTACHMENT OF ALL MECHANICAL UNITS, ELECT FIXTURES, PLUMBING, ETC. SHALL BE INCLUDED IN THE DESIGN OF THE TRUSSES BY THE TRUSS MFR.
- I. DESIGN ROOF TRUSSES TO SUPPORT ALL IMPOSED LOADS, INCLUDING WIND & LATERAL LOADS. COORDINATE SIZE, LOCATION AND WEIGHT OF EQUIPMENT WITH MECHANICAL WORK. PROVIDE MULTIPLE TRUSSES WHERE ONE TRUSS CANNOT SUPPORT THE LOAD. PROVIDE BRIDGING BETWEEN TRUSSES AS SPECIFIED AS MINIMUM STANDARD.
- J. INSTALLATION OF ALL TRUSSES SHALL BE DONE USING A SPREADER BAR WITH A THREE POINT VERTICAL PICK. CARE SHALL BE USED IN LIFTING TO PREVENT HORIZONTAL BENDING.
- K. IMPROPER HANDLING OF THE TRUSSES AS NOTED ABOVE AND IN THE SPECS SHALL MEAN REMOVAL OF THE TRUSSES FROM THE JOBSITE AND REPLACEMENT AT CONTRACTOR'S EXPENSE.
- L. SEE DIV. 6 OF THE SPECS FOR DETAILS ON TRUSS MANUFACTURING AND NAILING.
- M. TRUSS MANUFACTURER SHALL KEEP CHORD SPLICES AWAY FROM PANEL POINTS TO MINIMIZE PRESS PLATE PROFILE DIMENSIONS.

- (1) STARTING POINT OF TRUSS LAYOUT - CENTERLINE OF TRUSS.
- (2) VERIFY NECESSITY OF DOUBLE TRUSSES WITH TRUSS MFR. DUE TO POINT LOADING AND ADDITIONAL UNIFORM LOADING, TYPICAL.
- (3) COORDINATE BLOCKING WITH EXHAUST AND SUPPLY DUCT.
- (4) CONT 2x4 WD BRIDGING ON TOP OF BOTTOM CHORD. ADJUST AS REQUIRED FOR DUCT PLENUMS. MAX SPACING AT 5'-0" O.C. OR TIGHTER SPACING AS REQUIRED BY TRUSS DESIGN. SEE 13/S4.1 FOR BRIDGING LAP DETAIL.
- (5) SIMPSON MSTA 24 AT CORNER DBL TOP PLATE. CENTER STRAP ON CORNER.
- (6) (2) 2x6 BLOCKING W/ U26-2 HANGERS. TYP. EDGES OF ALL ROOF TOP EQUIPMENT AND ALL ROOF OPENINGS - SEE DET. 6 & 10/S4.2.
- (7) LOC. OF HOOD. SEE HOOD DRAWINGS FOR HOOD ATTACHMENT DETAIL 6/S4.1.
- (8) ROOF HATCH.
- (9) BLOCKING UNIT ON ROOF TOP EQUIPMENT. COORDINATE WITH MECHANICAL.
- (10) HVAC ROOF OPENING FOR DUCT. VERIFY SIZE WITH HVAC MFR. & MECHANICAL DWGS.
- (11) (2) 2x6 BUILT-UP COLUMN AT TRUSS BEARING, TYP. @ GIRDER. TRUSS ONLY. REF. DETAIL 12/S4.2.
- (12) KICKERS PER DETAIL 3/S4.4.

- (12) 19/32" PLYWOOD ROOF DECK. SEE NAILING SCHEDULE, THIS SHEET.
- (13) NOT USED.
- (14) 2x6 @ 2'-0" O.C. WITH SIMPSON U-26 EA. END.
- (15) CANOPY BY MANUF.
- (16) AT OWNER/ CONTRACTOR OPTION: VESTIBULE.
- (17) 2x6 AT 16" O.C.

NAILING SCHEDULE - ROOF **D**

ROOF FRAMING NOTES **C**

KEY NOTES **B**

PROJECT NUMBER	20-0616
PROJECT MANAGER	RAD
PROJECT ENGINEER	SA
PROJECT DRAFTER	MJN



OWN/STATE COMMENTS	08.10.20


CONTRACT DATE:	8/26/19
BUILDING TYPE:	EXP. LITE MED40
PLAN VERSION:	MARCH 2018
BRAND DESIGNER:	DAN DICKSON
SITE NUMBER:	314007
STORE NUMBER:	TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544




ROOF FRAMING PLAN


S3.0




EQUIPMENT PEDESTAL SECTION 3/4" = 1'-0" **9**




FOOTING AT DRIVE THRU 3/4" = 1'-0" **10**




FOUNDATION 25'-0" MAX LIGHT POLE 3/4" = 1'-0" **11**




CONTROL JOINTS 3/4" = 1'-0" **5**



HOLDDOWN DETAIL 3/4" = 1'-0" **6**



FOOTING AT FRONT WALL 3/4" = 1'-0" **7**




FOOTING AT SHEARWALL 3 3/4" = 1'-0" **8**


NOTES:

1. CONCRETE SLAB ON GRADE, FOR HEIGHT OF REINFORCING, SEE TYPICAL DETAIL.
2. SAWCUT - 1/8" WIDE X 1/4" SLAB THICKNESS IN DEPTH - CUT SHALL BE MADE SOON ENOUGH TO PREVENT SHRINKAGE CRACKING, BUT NOT SO SOON AS TO CAUSE SPALLING. WORK MUST BE ACCOMPLISHED WITHIN 4 TO 12 HOURS OF CONCRETE FINISH.
3. CONTINUOUS KEY - SEE TYPICAL KEY IN CONCRETE SLAB ON GRADE MESH REINFORCING. SEE TYPICAL DETAIL FOR HEIGHT IN SLAB.
4. DO NOT CONTINUE REINFORCEMENT THRU KEYPED JOINTS.


NOTE: KEYPED JOINTS NEED ONLY OCCUR AT EXPOSED EDGES DURING PLACEMENT UNLESS SPECIFICALLY NOTED ON THE PLANS.




FOOTING AT SIDE AND REAR WALLS 3/4" = 1'-0" **1**



FOOTING AT SHEARWALL 2 3/4" = 1'-0" **2**




FOOTING AT FULL HEIGHT OPENING 3/4" = 1'-0" **3**



FOOTING AT DRIVE THRU 3/4" = 1'-0" **4**

PROJECT NUMBER	20-0816
PROJECT MANAGER	RAD
PROJECT ENGINEER	SA
PROJECT DRAFTER	MJN



OWN/STATE COMMENTS	08.10.20


CONTRACT DATE:	8/26/19
BUILDING TYPE:	EXP. LITE MED40
PLAN VERSION:	MARCH 2018
BRAND DESIGNER:	DAN DICKSON
SITE NUMBER:	314007
STORE NUMBER:	TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544




STRUCTURAL DETAILS


S4.0




TYP. MULTIPLE HEADER 1-1/2" = 1'-0" **14**




SUPPORT - PARALLEL TO TRUSS N.T.S. **10**




HANGING BULKHD. OR HOOD DETL. N.T.S. **6**




LEDGER DETAIL N.T.S. **3**




DETAIL NOT USED N.T.S. **1**



SUPPORT PERP. TO TRUSS N.T.S. **11**



FRAMING ELEVATION @ OPENING N.T.S. **7**



BRIDGING DETAIL N.T.S. **4**







PLATE LAP DETAIL 1" = 1'-0" **12**




DETAIL NOT USED 1/4" = 1'-0" **8**




BRIDGING LAP DETAIL N.T.S. **13**



BRIDGING LAP DETAIL @ OPEN CLG. N.T.S. **9**



TYPICAL WALL BELOW TRUSS 3/4" = 1'-0" **5**



SIDE WALL @ TRUSS N.T.S. **2**

PROJECT NUMBER 20-0816
 PROJECT MANAGER RAD
 PROJECT ENGINEER SA
 PROJECT DRAFTER MJN

CARUSO TURLEY SCOTT INC.
 consulting structural engineers
 1215 W. Rio Salado Pkwy
 Suite 200
 Tempe, Arizona 85281
 (480) 774-1700
 (480) 774-1701 FAX

SANDRA J. HERD
 REGISTERED
 No. 12000373
 STATE OF INDIANA
 PROFESSIONAL ENGINEER
 08-07-20

OWN/STATE COMMENTS 08.10.20

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
 MEDIUM40


STRUCTURAL DETAILS

S4.1

CONNECTION TYPE:

1. JOIST TO SILL OR GIRDER, TOENAIL (3-8d)
2. BRIDGING TO JOIST, TOENAIL EACH END (2-8d)
3. 1"x6" (25MMx152MM) SUBFLOOR OR LESS TO JOIST, FACE NAIL (2-8d)
4. WIDER THAN 1" X 6" (25MMx152MM) SUBFLOOR TO JOIST, FACE NAIL (3-8d)
5. 2" (52MM) SUBFLOOR TO GIRDER, BLIND AND FACE NAIL (2-16d)
6. SOLE PLATE TO JOIST OR BLOCKING, TYPICAL FACE NAIL (16d @ 16" O.C.)
7. SOLE PLATE TO JOIST OR BLOCKING, AT BRACED W. PANELS (3-16d PER 16")
8. TOP PLATE TO STUD, END NAIL (2-16d)
9. STUD TO SOLE PLATE (2-16d END NAIL)
10. DOUBLE STUDS, FACE NAIL (16d @ 24" O.C.)
11. DOUBLE TOP PLATES, TYPICAL FACE NAIL (16d @ 16" O.C.)
12. DOUBLE TOP PLATES, LAP SPLICE (8-16d)
13. BLOCKING BETWEEN JOISTS OR RAFTERS TO TOP PLATE, TOENAIL (3-8d)
14. RIM JOIST TO TOP PLATE, TOENAIL (8d @ 6" O.C.)
15. TOP PLATES, LAPS AND INTERSECTIONS, FACE NAIL (2-16d)
16. CONTINUOUS HEADER, TWO PIECES (16d @ 16" O.C. ALONG EDGE)
17. CEILING JOISTS TO PLATE, TOENAIL (3-8d)
18. CONTINUOUS HEADER TO STUD, TOENAIL (4-8d)
19. CEILING JOISTS, LAP OVER PARTITIONS, FACE NAIL (3-16d)
20. CEILING JOISTS TO PARALLEL RAFTERS, FACE NAIL (3-16d)
21. RAFTER TO PLATE, TOENAIL (3-8d)
22. 1" (25MM) BRACE TO EACH STUD AND PLATE, FACE NAIL (2-8d)
23. 1"x8" SHEATHING OR LESS TO EACH BEARING, FACE NAIL (2-8d)
24. WIDER THAN 1"x8" SHEATHING TO EACH BEARING, FACE NAIL (3-8d)
25. BUILT-UP CORNER STUDS (16d @ 24" O.C.)
26. 2" PLANKS (2-16d AT EACH SPLICE)
27. 2x6 BOX BEAM / HEADER (12d @ 12" O.C.)
28. BUILT-UP GIRDER AND BEAMS (20d @ 32" O.C. AT TOP & BOTTOM AND STAGGERED 2-20d AT ENDS AND AT EACH SPLICE)

NAILING:





NOTES:
 1. MIN. PLYWD. SHT. SIZE SHALL BE 2'-0" X 4'-0".
 2. MIN. 3/8" NAILING EDGE DISTANCE.
 3. EDGE NAIL (E.N.) O/ BEAMS AND AROUND ALL OPENINGS.

ROOF NAILING PLAN N.T.S. **8**


EQUIPMENT	DESIGN WEIGHT
HVAC UNIT - RTU-1	* 1300 lbs.
HVAC UNIT - RTU-2	* 2500 lbs.
EXHAUST FAN - EF-1	* 200 lbs.
EXHAUST FAN - EF-2	* 70 lbs.
HOOD #1 - TACO BELL	300 lbs.
ICE CONDENSERS	200 lbs.
FREEZER CONDENSER	300 lbs.
COOLER CONDENSER	300 lbs.

* A. ALL DESIGN WEIGHTS INCLUDE CURB.
 B. COORDINATE WEIGHTS WITH HVAC UNIT SCHEDULE 1/M1.0.

ROOF TOP EQUIPMENT WEIGHTS N.T.S. **5**




ROOF OPENING DETAIL N.T.S. **6**




WALL FRAMING DETAIL 3/8" = 1'-0" **1**

NAILING SCHEDULE N.T.S. **11**



BUILT-UP 2X COLUMNS N.T.S. **12**

PLYWOOD EDGE BLOCKING N.T.S. **9**




TYPICAL ROOF OPENING 1" = 1'-0" **10**


TRUSS SCHEDULE N.T.S. **7**

TRUSS TYPES	SINGLE TRUSS DESIGNATION	DOUBLE TRUSS DESIGNATION	BEARING POINT	COMMENTS
T1 - T28	X	XX	△	SEE NOTE 1.





NOTES:
 1. HOLDOWN CONNECTORS SHALL BE SPECIFIED BY SITE SPECIFIC ARCHITECT/ENGINEER BASED UPON LOADING DATA PROVIDED BY TRUSS DESIGNER.
 2. PROVIDE SHOP DRAWINGS PRIOR TO FABRICATION.
 3. TRUSS MEMBER SIZES ARE FOR REFERENCE ONLY. ACTUAL SIZE SHALL BE DETERMINED BY TRUSS MANUFACTURER BASED ON ACTUAL LOAD CONDITIONS AND CODES.



TRUSS ELEVATION N.T.S. **2**



HOLDOWN DETAILS 1 1/2" = 1'-0" **4**



TRUSS LOAD DIAGRAMS N.T.S. **3**

PROJECT NUMBER	20-0816
PROJECT MANAGER	RAD
PROJECT ENGINEER	SA
PROJECT DRAFTER	MJN

CARUSO TURLEY SCOTT INC.
 consulting structural engineers
 1215 W. Rio Salado Parkway
 Suite 200
 Tempe, Arizona 85281
 (480) 774-1700
 (480) 774-1701 FAX

SANDRA J. HERD
 REGISTERED
 No. 12000373
 STATE OF INDIANA
 PROFESSIONAL ENGINEER
 08-07-20

△	OWN/STATE COMMENTS 08.10.20
△	
△	
△	
△	


CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544


TACO BELL
EXPLORER LITE
 MEDIUM40

STRUCTURAL DETAILS


S4.2




TYPICAL PARAPET CAP 12" = 1'-0" **1**




SIGNAGE ATTACH. BLOCKING DTL. 1 1/2" = 1'-0" **2**




CANOPY TIE BACK BLOCKING DETAIL 12" = 1'-0" **3**



DRIVE THRU TOWER 1" = 1'-0" **5**




HEADER CONNECTION 1" = 1'-0" **6**



KICKER TO ROOF CONNECTION AT STOREFRONT 3/4" = 1'-0" **4**

PROJECT NUMBER	20-0816
PROJECT MANAGER	RAD
PROJECT ENGINEER	SA
PROJECT DRAFTER	MJN



OWN/STATE COMMENTS	08.10.20


CONTRACT DATE:	8/26/19
BUILDING TYPE:	EXP. LITE MED40
PLAN VERSION:	MARCH 2018
BRAND DESIGNER:	DAN DICKSON
SITE NUMBER:	314007
STORE NUMBER:	TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544




STRUCTURAL DETAILS


S4.3




SECTION @ TOWER 3/4" = 1'-0" **4**



CANOPY TIE BACK BLOCKING DETAIL 3/4" = 1'-0" **3**





SECTION @ WALK IN COOLER 3/4" = 1'-0" **2**



SECTION @ DINING WINDOW 3/4" = 1'-0" **1**

PROJECT NUMBER	20-0816
PROJECT MANAGER	RAD
PROJECT ENGINEER	SA
PROJECT DRAFTER	MJN



OWN/STATE COMMENTS 08.10.20


CONTRACT DATE:	8/26/19
BUILDING TYPE:	EXP. LITE MED40
PLAN VERSION:	MARCH 2018
BRAND DESIGNER:	DAN DICKSON
SITE NUMBER:	314007
STORE NUMBER:	TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544



STRUCTURAL DETAILS

S4.4



FLOOR PLAN 1/4" = 1'-0" **A**

NOTE: BOLLARDS AT
DOWNSPOUTS ARE OPTIONAL
NOTE: VESTIBULE OPTION IS SITE SPECIFIC
INDEPENDENT OF PATIO OPTION

CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD


TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
MEDIUM40

FLOOR PLAN
A1.0

6/29/20



ARCVISION
INCORPORATED
ARCHITECTURE ENGINEERING STORE PLANNING
SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com



WALL LEGEND		E	
	TYPICAL EXTERIOR WALL: 2x6 WD STUDS AT 16" O.C. W/ SHEATHING AS SCHEDULED (SEE STRUCT. DWGS.) AND R-19 KRAFT-FACED FIBERGLASS BATT INSULATION U.O.N. GC SHALL PROVIDE 2 LAYERS OF GRADE 'D' 60 lb BUILDING PAPER.		INTERIOR SOUND-RATED WALL: TYPICAL INTERIOR WALL W/ 3-1/2" UNFACED FIBERGLASS BATT INSULATION.
	TYPICAL INTERIOR WALL: WD STUDS AT 16" O.C. AS INDICATED		HOOD WALL: EXTERIOR WALL WITH 20 GA. S.S. PANEL BEHIND HOOD. EXTEND MIN. 18" BEYOND END OF HOOD. REFER TO DETAIL 2/M3.0 FOR EXTENT OF S.S. PANEL.
	2x4 WOOD STUDS		2x6 WOOD STUDS
	2x6 WOOD STUDS		DASHED LINE INDICATES INTERIOR SUBSTRATE LOCATION.
<p>WALL HEIGHTS: ALL INTERIOR NON-BEARING WALLS GO TO BOTTOM OF TRUSS, U.O.N. REFER TO STRUCTURE. WALL SUBSTRATES: - DINING ROOM: 1/2" GYPSUM WALLBOARD FROM FLOOR SLAB TO 6" ABOVE CEILING HEIGHT U.O.N. (NOTE: THE CEMENT BOARD SPECIFICATION IS DESIGNED TO ALLOW THE G.C. FLEXIBILITY.) - KITCHEN WALLS AND DINING ROOM CLOSET: 1/2" CEMENT WALLBOARD FROM T.O. SLAB TO 12" AFF. AT 12" AFF. USE 1/2" CDX PLYWOOD W/FRP SURFACE FINISH TO 6" ABOVE CEILING HEIGHT U.O.N. IF DOUBLE SIDED SHEAR WALL PLYWD IS SPECIFIED THE PLYWOOD SHALL BE CONTINUOUS FROM SILL PLATE TO TOP PLATE. SEE 4 & 11 / A6.3. - RESTROOM WALLS: 5/8" CEMENT WALLBOARD FROM T.O. SLAB OR T.O. CONCRETE CURB TO 48" A.F.F. WITH 5/8" HI-IMPACT BRAND XP WALLBOARD, TYPE X CORE FROM T.O. CEMENT BOARD TO 6" ABOVE CEILING HEIGHT U.O.N. NO SUBSTITUTIONS ALLOWED. FINISH AS SCHEDULED. SEE 11 (SIM), 12/A6.3. - ALL OTHER FRAME WALL CONDITIONS: 1/2" CEMENT WALLBOARD FROM T.O. SLAB OR T.O. CONCRETE CURB TO 48" A.F.F. WITH 1/2" GYPSUM WALLBOARD FROM T.O. CEMENT BOARD TO 6" ABOVE CEILING HEIGHT U.O.N. FINISH AS SCHEDULED.</p>			


FLOOR PLAN NOTES		D	
<p>DIMENSIONS: A. ALL DIMENSIONS ARE TO FACE OF STUD U.O.N. REFER TO FOUNDATION PLAN FOR FACE OF CONC. DIMENSIONS. B. DIMENSIONS NOTED AS "CLEAR" OR "HOLD" ARE MIN. REQD. NET CLEARANCE FROM FACE OF WALL / WAINSCOT FINISH. VERIFY FINAL EQUIPMENT SIZES W/ VENDOR PRIOR TO INT. WALL FRAMING.</p> <p>WINDOWS / DOORS: A. SEE SHT. A7.1 FOR WINDOW TYPES AND DOOR SCHEDULE. B. ALL DOOR AND WINDOW OPENING DIMENSIONS ARE TO ROUGH OPENING.</p> <p>FINISH SUBSTRATES: A. PROVIDE 1/2" THICK CEMENTITIOUS BD. FROM FLOOR SLAB TO 12" A.F.F. MIN. IN LIEU OF GYP. BD. AT ALL WALLS EXCEPT SHEARWALL SURFACES, U.O.N. B. ALL JOINTS, GAPS OR SPACES LEADING TO ALL HOLLOW OR INACCESSIBLE SPACES SHALL BE SEALED WITH "NSF INTERNATIONAL" APPROVED SEALANTS. C. ALL BACK OF HOUSE AND OFFICE WALLS SHALL HAVE 1/2" CDX PLYWOOD SUBSTRATE, U.O.N.</p> <p>DECOR: A. SEE A2.0 FOR SEATING PLAN AND DETAILS. B. SEE A7.0 FOR FLOOR FINISHES. C. SEE A8.0 - A8.3 FOR WALL FINISHES. D. SEE A7.1 FOR CEILING FINISHES.</p> <p>GENERAL: A. PROVIDE THREE FIRE EXTINGUISHERS - (2) 10 lb. BC and (1) 10 lb. ABC - TO COMPLY WITH LOCAL FIRE CODE. LOCATE PER DIRECTION OF FIRE MARSHALL OR LOCAL AUTHORIZING AGENT. B. DRAWINGS ARE BASED UPON WOOD FRAMING. UTILIZATION OF METAL STUDS ON NON-BEARING INTERIOR PARTITIONS, BULKHEADS AND SOFTS IS ACCEPTABLE. C. ALL ATTACHMENTS MADE THROUGH E.I.F.S. SHALL BE BUSHED TO PREVENT DAMAGE TO THE FINISH. PER 9/A6.2. D. ALL PENETRATIONS THROUGH E.I.F.S. SHALL BE SEALED USING MFRS. APPROVED METHOD.</p>			

KEY NOTES		B	
	STARTING POINT. ALL SUB-TRADES SHALL USE THIS POINT AS A BEGINNING LAY-OUT (INSIDE FACE OF EXT. WALL STUDS).		ROOF LADDER SEE 4/A6.0
	NO FRP BEHIND W-05 WALK-IN COOLER/FREEZER.		ADD SECOND 2X4 WALL ON KITCHEN SIDE.
	PIPE BOLLARD. SEE DETAIL 8/C1.0.		REMOVABLE ASTRAGAL FROM INSIDE ONLY.
	HOOD WALL, SEE WALL LEGEND.		METAL STUDS REQUIRED PER LOCAL CODES.
	ELECTRICAL MAIN SWITCH BOARD. REFER TO ELECT. DWGS.		INDICATES WATER HEATER LOCATION.
	CO2 FILL BOX LOCATION.		SPLASH GUARD. SEE DETAIL 9/A6.3.
	TILE TO METAL THRESHOLD.		LINE OF CANOPY ABOVE
	KEEP CLEAR FOR UTILITIES & SYRUP LINES. SEE DETAIL 14 & 19/A6.4 FOR STUD LAYOUT REQUIREMENTS.		LIGHTED WALL. REFER TO DETAIL 5/A8.0
	MOP SINK. REFER TO SHEET A2.0 & A2.1.		LANDSCAPE AREA AT PATIO
	S.S. CORNER GUARD / WALL CAP (TM-2). TYP. ALL CORNERS IN BACK-OF-HOUSE FROM REAR WALL TO THE KITCHEN SIDE OF THE SERVICE COUNTER. SEE DETAIL 19/A6.3.		CASED OPENING. REFER TO DETAIL 7/A6.4.
	ELECT. PANELS RECESSED IN 2x6 WALL.		FUR OUT WALL AS INDICATED WITH 2X4 WOOD STUDS AT 16" O.C.
	LIGHTING CONTROL PANEL SURFACE MOUNTED. REFER TO ELECT. DWGS.		KIOSK POWER STUB LOCATION TO RUN WITHIN LEG OF KIOSK
	SYRUP LINE CHASE (ABOVE). SEE DETAIL 19/A6.4.		KIOSK DATA STUB LOCATION TO RUN WITHIN LEG OF KIOSK
	14"x14" HORIZONTAL OPENING FOR SYRUP TUBES. COORDINATE WALL PENETRATION WITH COUNTER INSTALLER. SEAL CHASE TO COUNTER. SEE 11/A6.4.		



NTD:
 OPTIONAL: WINDOW SHADE BY ROLL-A-SHADE
 MATERIAL - E SCREEN KOOL BLACK CHARCOAL/
 CHARCOAL - 5% OPEN
 FASCIA - APPROVED IF FRANCHISEE
 REQUESTS - CLEAR ANODIZED
 CONTACT - ANDREW STRICKLIN
 951-245-5077
 ANDREW.STRICKLIN@ROLLASHADE.COM

NOTE: VESTIBULE OPTION IS SITE SPECIFIC
 INDEPENDENT OF PATIO OPTION



EQUIPMENT/SEATING PLAN 1/4"=1'-0" **A**

OWN/STATE COMMENTS 08.10.20
 CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

SYM.	QTY.	ITEM	SYM.	QTY.	ITEM
D-581	2	PINE PLANK SETTEE BOOTHS - 48"	D-721	2	24" X 42" ADA TABLE TOP - PLYWOOD
D-582	1	PINE PLANK SETTEE BOOTHS - 60"	D-723	4	24" X 42" TABLE TOP - PLYWOOD
D-620	29	RETRO CHAIR - 18"	D-750	TBD *	WINDOW SILL
D-623	6	BARREL BARSTOOL - 29"	D-753	TBD *	WAINSCOTING
D-640	1	SERVICE COUNTER & POS STATION	D-755	TBD *	CHAIRRAIL * CONSULTANT TO PROVIDE LINEAR FOOTAGE FOR SILLS, CHAIR RAILS AND SHROUDS.
D-646	1	CONDIMENT COUNTER - RECTANGLE	D-920	2	WAUSAU MF 5005 BOLT DOWN END POST
D-647	1	WASTE ENCLOSURE - SINGLE	D-921	2	WAUSAU MF 5006 BOLT DOWN CENTER POST
D-648	1	WASTE ENCLOSURE - DOUBLE	D-931	3	WAUSAU MF 5047 FULL PANEL 5'-6" O.C.
D-655	1	WB HUB TABLE - 72"			
D-658	1	WB HUB TABLE ADA - 48"			
D-700	3	22" X 22" X 28.5"H FREE STANDING TABLE BASE			
D-703	12	22" X 5.5" X 28.5"H FREE STANDING TABLE BASE			
D-720	3	24" X 19" TABLE TOP - PLYWOOD			

SEATING PACKAGE - BY SEATING VENDOR U.O.N. (TOTAL SEATS = 42 INT, 12 EXT.) **E**

(X)	QTY.	ITEM	REMARKS
625	1	EMOJIS, 28"X40"	SEE A8.0 FOR LOCATION
626	1	LINEAR SAUCES, 28"X40"	SEE A8.0 FOR LOCATION
624	1	CONCRETE, 28"X40"	SEE A8.0 FOR LOCATION
620	1	LINEAR SAUCES WALLPAPER	SEE A8.0 FOR LOCATION

ARTWORK SCHEDULE **D**

DECOR
 1. REFER TO SC SHEETS FOR SCOPE OF WORK RESPONSIBILITIES.
 2. (H) - SYMBOL DENOTES A HIGH TABLE OR DINING COUNTER WITH STOOLS.
 3. (HC) - SYMBOL DENOTES A HANDICAP ACCESSIBLE TABLE.

STORAGE TYPE	LINEAR FT.
DRY STORAGE	53
COLD STORAGE	25
FROZEN STORAGE	10

SHELVING QUANTITIES REQUIRED **C2**

- HOOD FIRE SUPPRESSION SYSTEM (ANSUL R-102 OR EQUAL).
- SEE SHEET A1.1 FOR SECURITY DOOR PACKAGE.
- MAINTAIN 36" MIN CLEAR ACCESSIBLE AISLE EGRESS PATHS TO EXIT DOORS. 32" AT DOORWAYS AND CASSED OPENINGS. (42" AISLE REQUIRED WHEN AISLE SERVES MORE THAN 50 SEATS)
- 30" x 48" CLEAR FLOOR SPACE FOR HANDICAP ACCESS.
- ALERT LIGHT BOX FOR 3-COMP POWER SOAK.
- PULL STATION @ 3'-8" A.F.F.
- GAS LINE DOWN TO EQUIPMENT.
- COORDINATE LOCATION OF HORIZ PVC SYRUP CHASE THRU WALL TO COUNTER.
- 6" HIGH WATER HEATER PLATFORM.
- SWITCHGEAR / ELECTRIC PANELS.
- ROOF LADDER, SEE DETAIL 4 & 7/A6.0.
- 8' LADDER.
- SAFE.
- SPLASH GUARD. SEE DETAIL 9/A6.3.
- AUTOMATIC HAND SOAP AND SANITIZER DISPENSERS PROVIDED BY ECOLAB
- FIRE EXTINGUISHER (MEETING 2015 IBC STANDARDS) TO BE LOCATED AND MOUNTED PER 2015 IBC.



KEYNOTES **B**

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544




EQUIPMENT AND SEATING PLAN
A2.0

CATEGORY	SUBCATEGORY	DESCRIPTION	A&D #	QUANTITY			SUPPLIER	ORDERED BY <small>(DISTRIBUTOR, GC, COMPANY OR FZ)</small>	INSTALLED BY <small>(MANUFACTURER OR GC)</small>	NOTES
				CLOSED KITCHEN	OPEN KITCHEN	IN-LINE AND CANTINA				
BASE EQUIPMENT	PLUMBING	Bulk CO2	S-580	1	1	1	MVE	DISTRIBUTOR	MANUFACTURER	
BASE EQUIPMENT	PLUMBING	CO2 (BULK) TANK	S-580	1	1	1	MVE	DISTRIBUTOR	MANUFACTURER	WITHOUT IMPURITY RING
BASE EQUIPMENT	PLUMBING	BUNDLED SYRUP LINES	S-600	2	2	1	PEPSI	COMPANY OR FZ	MANUFACTURER	SEE SCOPE OF WORK (PEPSI)
CONTRACTOR'S PACKAGE	WATER HEATER	Water Heater Rack	B-219	1	1	1	NEW AGE INDUSTRIAL CORP.	DISTRIBUTOR	GC	#98147
CONTRACTOR'S PACKAGE	WATER HEATER	GAS WATER HEATER	B-223	1	1	1	AO SMITH	DISTRIBUTOR	GC	Gas Fired,#BTH120,NG,60 Gal,High Efficiency,AO Smith,Sealed Combustion,120M BTU
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	72"W X 41"H DRIVE-THRU WINDOW	B-925	0	1	0	QUICKSERV	DISTRIBUTOR	GC	D/T Window, Quickserv #Bp-7241E-B, Fully Automatic
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	Roof Ladder	B-049	1	1	0	PRECISION	DISTRIBUTOR	GC	#FL-184,16'0"Oad 15'4"Ladder,Interior Use For Roof Hatch Access W/Floor Brackets
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	Roof Hatch	B-050	1	1	0	PRECISION	DISTRIBUTOR	GC	#PLHG,2'6"X3' Clear Opening,Galv Steel,Hold Open Arms,Pressure Intensifier,Heavy Duty Hinge,All Mounting Hardware Furnished By Others
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	Door and Frame	B-101	1	1	1	LOCKNET	DISTRIBUTOR	GC	New,Non-Delivery,4 Week Leadtime W/Frame,W/Sargent Panic Bar,W/Window Consists Of 1 Steel Frame: 14 Ga,Galv,Welded,Pre Finished Tan 1 Steel Door:16 Ga,Galv,Foam Insulated,Fully Reinforced F/Hdwe,Full Length Steel Security Astragal & Pre-Finis
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	DT Window	B-120	1	0	0	QUICKSERV	DISTRIBUTOR	GC	G.C. TO PROVIDE TRANSOM - CLEAR ANODIZED B-130 LEFT-RIGHT Single Slider,Quickserv#SC4030CR Self Closing,Right To Left,Slide,Manual Operation 20"X30"Opening,48"Wx4 1/2"Dx36"H,W/Auto Locking Handle,Opening Direction Is From Inside Restaurant,Closing Mechanical Upgrade W/Hold Open Device,Clear Finish
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	FLY FAN	B-160	1	1	1		DISTRIBUTOR	GC	
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	Carbon Monoxide Meter	B-381	1	1	1	AMPROBE	DISTRIBUTOR	GC	# CO2-200380,2000PPM Wall Mount,Amprobe,Lcd Display,Audible Alarm Output Relay,Includes 100 To 240Vac Power Adapter And Instructions
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	Backsplash	E-108	1	1	1	STRATOVENT	DISTRIBUTOR	GC	TB,#BACKSPASH106X111FLAT,106"H X 111"H,430S/S,Flat Wall Panels W/Divider Strips & Trim,Covering Rear Wall & 18" Beyond Left & Right Sides
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	CO2 CARBON DIOXIDE SENSOR/WARNING	S-381	1	1	1	AMPROBE	DISTRIBUTOR	GC	CO2-200
CONTRACTOR'S PACKAGE	BUILDING MISCELLANEOUS	FLY FAN	S-XX2	1	1	1	TBD	DISTRIBUTOR	GC	
CONTRACTOR'S PACKAGE	ELECTRICAL	Combined Controls,Tb; Combined Control Box	CCBOX	1	1	1	AEC	GC	GC	
CONTRACTOR'S PACKAGE	HVAC	Hood Exhaust	E-107	1	1	1	STRATOVENT	DISTRIBUTOR	GC	PRE-PIPED FOR ANSUL SUPPRESSION - #TBG3650SVBD6FT3IN,6'-3"L X 36"W,430 S/S,UL Listed Lights With (3) Cfl Bulbs Included,S/S Grease Baffle Filters,End Panels Shipped Loose,Insulated Rear Stand-Off Integral To Hood,25"H Wrappers To Enclose Top Of Hood Sized
CONTRACTOR'S PACKAGE	HVAC	Roof Curb	EF-1	1	1	1		DISTRIBUTOR	GC	#CURB195X26TBG,Stratavent 19,5"Lx19,5"Wx26"D,Vented,Factory Attached Hinges F/Grease Hood Applications
CONTRACTOR'S PACKAGE	HVAC	Exhaust fan	EF-1	1	1	1		DISTRIBUTOR	GC	Upblast,TB,#SV50HP1050TBG Stratavent,1/2Hp,120V,1PH,Electric,30"Lx30"Wx30"H 1050 Cfm,Prewired Disconnect Switch & Prewired Speed Controller,Grease Cup W/Drain Tube,F/Grease Hood Applications
CONTRACTOR'S PACKAGE	HVAC	Roof Curb	EF-2	1	1	1		DISTRIBUTOR	GC	#CURB195X14TBRR,Stratavent TB,20"Lx20"Wx20"D,Used With Svdr30TBrr570 Or Svdr30TBrr780 Fans
CONTRACTOR'S PACKAGE	HVAC	Fan,Downblast Exhaust	EF-2	1	1	1		DISTRIBUTOR	GC	#SVDR30TBRR570,570 Cfm,0.25 Hp,120V/1PH,0.375"Sp,W/Prewired Disconnect&Speed Controller,Backdraft Damper Birdscreen,Restroom Or Steam/Heat Removal Only
CONTRACTOR'S PACKAGE	HVAC	HVAC - RTU 1	RTU-1	1	1	1	LENNOX / TRANE	DISTRIBUTOR	GC	DINING RTU / YORK OPTIONAL FOR EXPLORER AND EXPLORER LITE TEMPLATES
CONTRACTOR'S PACKAGE	HVAC	HVAC - RTU 2	RTU-2	1	1	1	LENNOX / TRANE	DISTRIBUTOR	GC	KITCHEN RTU / YORK OPTIONAL FOR EXPLORER AND EXPLORER LITE TEMPLATES
CONTRACTOR'S PACKAGE	HVAC	Condenser Remote	S-740	1	1	1		DISTRIBUTOR	GC	#12-3003-0006,230V/60Hz,W/ Metal Flex,F/Use W/Fbd Remote 773 Unit E56190037 & Fbd Remote 774 Unit E56190035, INCLUDES LINE SETS - 2-50 Copper Lines, 2-Flex Line Sets, Bag of Miscellaneous Parts, and Strut Channel
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	SOAP DISPENSER (WALL MOUNT)	B-241	4	4	4	KAY	DISTRIBUTOR	GC	PROVIDED BY ECOLAB 3741
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	SANITIZER DISPENSER (WALL MOUNT)	B-251	4	4	4	KAY	DISTRIBUTOR	GC	PROVIDED BY ECOLAB 3741
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Receptacle,Paper Towel Dispenser/Waste	B-253	2	2	2	BOBRICK	DISTRIBUTOR	GC	RECESSED - Bobrick#B3944,Convertible,Recessed,W/4-1/8" Extension F/Wall,12Gal
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Wall Mirror	B-265	2	2	2	BOBRICK	DISTRIBUTOR	GC	SURFACE MTD 18"X36",S/S Finish,Bobrick,#B1651836
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Dispenser,Toilet Paper,Single Jumbo Roll	B-275	2	2	2	BOBRICK	DISTRIBUTOR	GC	SURFACE MTD - S/S, Bobrick#B2890
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Paper Towel Dispenser	B-290	2	2	2	BOBRICK	DISTRIBUTOR	GC	SURFACE MTD. #B- 262
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Grab Bar	B-300	2	2	2	BOBRICK	DISTRIBUTOR	GC	SURFACE MTD. 1 1/2"X36",S/S Finish,Bobrick,#B6806X36
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	RESTROOM PARTITION PACKAGE	B-301	0	0	0	BOBRICK	GC	GC	OVERHEAD BRACED, COLOR: SC04 "FOREST GREEN" #1090
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Grab Bar	B-305	2	2	2	BOBRICK	DISTRIBUTOR	GC	SURFACE MTD. 1 1/2"X42",S/S Finish,Bobrick,#B6806X42
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Grab Bar	B-310	2	2	2	BOBRICK	DISTRIBUTOR	GC	SURFACE MTD. - 1.5"X18",S/S Finish,Bobrick#B6806X18
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	Receptacle,F/Sanitary Napkin	B-410	1	1	1	RUBBERMAID	DISTRIBUTOR	GC	INCLUDES ACCESSORY KIT & MOUNTING HARDWARE W/Rigid Liner,12 1/2Lx5 1/4Wx10 3/4"H,White,Rubbermaid 6140,WSM 656000 - #FG614000
CONTRACTOR'S PACKAGE	RESTROOM ACCESSORY	BABY CHANGING TABLE	F-452	1	1	1	FACILITIES CONNECTION	DISTRIBUTOR	GC	OPTIONAL - SFSTP4399
CONTRACTOR'S PACKAGE	Walk-In	Walk-In	W-058	0	0	0	KOLPAK	DISTRIBUTOR	GC	FRANCHISE OPTION: KOLPAK
CONTRACTOR'S PACKAGE	Walk-In	Walk-In	W-059	1	1	0	ICS	DISTRIBUTOR	GC	Combo,TB,#105181,Budgetary 19'4"X7'X9'2" OAD,F/Medium Building Prototype, Includes LEDs
CONTRACTOR'S PACKAGE	Walk-In	Walk-In	W-059A	0	0	1	ICS	DISTRIBUTOR	GC	SMALL WALK-IN
IT / POS	POS	CREDIT CARD SATELLITE ROUTER JUNCTION	F-050	1	1	1	POS PROVIDED	TB/IT	SSP	
IT / POS	POS	Front Load Safe	F-165	3	3	3	PERMA VAULT	DISTRIBUTOR	GC	#PRO-10TM
IT / POS	POS	SAFE WITH TOUCH SCREEN CONTROLS	F-174	1	1	1	BRINKS	COMPANY	MANUFACTURER	
IT / POS	POS	RECEIPT PRINTER	U-070	2	2	2		TB/IT	SSP	
IT / POS	POS	RECIPT PRINTER	U-070	3	3	3	EPSON	TB/IT	SSP	2 FOR F/C AND 1 D/T
IT / POS	POS	POS/ORDER ENTRY TERMINAL	U-100	4	4	2		TB/IT	SSP	2 FOR F/C AND 2 D/T
IT / POS	POS	Hanging Kit Cash Drawer	U-120	4	4	2		TB/IT	SSP	#K1056,Used When Mounting M2352 & M2321 Cash Drawer Under Counter
IT / POS	POS	CASH DRAWER BRACKETS	U-121	4	4	4	SPG	TB/IT	SSP	#SU186075Y
IT / POS	POS	CASH DRAWER	U-135	4	4	4	PAR			PROVIDE DEDICATED CIRCUIT AND (2) TWO CAT5 CABLES PER TABLET
IT / POS	POS	CASH DRAWER	U-152	3	3	3	PAR	TB/IT	SSP	
IT / POS	IT	OFFICE COMPUTER	F-040	1	1	1		TB/IT	SSP	IN OFFICE AREA. SEE SHEET A8.2
IT / POS	IT	MONITOR - OFFICE	F-060	1	1	1		TB/IT	SSP	IN OFFICE AREA. SEE SHEET A8.2
IT / POS	IT	OFFICE PRINTER/COPIER/FAX/SCANNER	F-080	1	1	1		IB/II	SSP	
IT / POS	IT	UPS (UN-INTERUPTABLE POWER SUPPLY)	F-090	5	5	5		TB/IT	SSP	






CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD



EQUIPMENT SCHEDULE
A2.3

CATEGORY	SUBCATEGORY	DESCRIPTION	A&D #	QUANTITY			SUPPLIER	ORDERED BY (DISTRIBUTOR, GC, COMPANY OR #)	INSTALLED BY (MANUFACTURER OR GC)	NOTES
				CLOSED KITCHEN	OPEN KITCHEN	IN-LINE AND CANTINA				
IT / POS	IT	INTERIOR DIGITAL MENU BOARD	L-043	4	4	4	STRATACACHE	TB/IT	SSP	DIGITAL MENU BOARDS - LG 43" DISPLAY
IT / POS	IT	BASE STATION - D/T COMM. SYSTEM	U-011	1	1	1	HME	TB/IT	SSP	5 COMMUNICATORS, +7'-0" A.F.F. System, Five, #C40000-5-HS3-TB, Drive-Thru, EOS HD High Definition Includes: (1) 6200 Base Station W/O Switcherboard (5) EOS HD All-In-One Headsets, (8) Batteries Battery Charger, Speaker, Vehicle Detector Board Microphone, Cables, P
IT / POS	IT	Headset	U-011	1	1	1	HME	TB/IT	SSP	5 COMMUNICATORS, +7'-0" A.F.F. System, Five, #C40000-5-HS3-TB, Drive-Thru, EOS HD High Definition Includes: (1) 6200 Base Station W/O Switcherboard (5) EOS HD All-In-One Headsets, (8) Batteries Battery Charger, Speaker, Vehicle Detector Board Microphone, Cables, Power Adapters, Headset
IT / POS	IT	CCTV DVR & MONITOR	U-035	1	1	1	SPG	TB/IT	SSP	WITH 8 CAMERA. SEE DETAIL 12/E7.0 FOR MNTG. MONITOR - #SU186075Y OR 4 TIER SU186074Y
IT / POS	IT	CCTV DVR & MONITOR	U-035	1	1	1		TB/IT	SSP	
IT / POS	IT	Digital Cameral	U-039	1	1	1		TB/IT	SSP	12 Digital Camera For Envysion/ confirm Kit, 12 Digital Camera For Envysion, TB, Kit Includes: 2Mp Camera, 17" Office Monitor And Mount All Cabling, 12 Ch Poe Switch, Keyboard, Mouse, UPS, Shipping--Note That Fee Based Permit May Be Required Based On Location, Check With Martco And Order If Needed (E5805
IT / POS	IT	SECURITY SYSTEM	U-052	0	0	0		TB/IT	SSP	Alarm, Cross Zoned, TB, 3 Buttons, Safewatch Control OPTIONAL FOR U-063
IT / POS	IT	Alarm System Kit	U-063	1	1	1	KAY	TB/IT	SSP	TB, Base Burglar Alarm System Kit W/Cellular Communicator Vista Control Panel, Includes: Vista Alpha Keypad (1), Battery (1), Phone Jack (1), Telco Cord (1), Interior Siren, Cellular Communicator (1), Front Counter Motion Sensor (1), Drivethru - KAY 3741
IT / POS	IT	MOUNTING PLATE	U-131	4	4	4		TB/IT	SSP	ONE PER KIOSK TABLET
IT / POS	IT	STORM AUDIO-NAV KEYPAD	U-131	4	4	4				1 PER KIOSK TABLET
IT / POS	IT	KIOSK TABLET	U-135	4	4	4		TB/IT	SSP	DEDICATED CIRCUIT AND (2) CAT6 CABLES PER TABLET
IT / POS	IT	MONITOR SUPPORT ARM	U-136	4	4	4	FACILITY SOLUTIONS			1 PER KIOSK TABLET - KIT, TB, 39"L, MONITOR SUPPORT ARM, CRADLE NOT INCLUDED - #SW550340-39
IT / POS	IT	VERIFONE (CREDIT CARD MACHINE)	U-136	4	4	4		TB/IT	SSP	1 PER KIOSK TABLET
IT / POS	IT	MONITOR SUPPORT ARM	U-137	1	1	1	FACILITY SOLUTIONS			1 PER STORE; CALIFORNIA STORES 50% OF TOTAL TABLETS - KIT, TB, 24.25"L, MONITOR SUPPORT ARM, CRADLE NOT INCLUDED - #SW550340-24
IT / POS	IT	STORM AUDIO-NAV KEYPAD	U-137	1	1	1		TB/IT	SSP	1 PER STORE; CALIFORNIA STORES 50% OF TOTAL TABLETS
IT / POS	IT	KITCHEN MONITOR	U-152	3	3	3	VIEWSONIC			SEE SCOPE OF WORK - VA2055m
IT / POS	IT	V-LINE MONITOR SUPPORT ARM	U-182	0	2	2				
IT / POS	IT	MONITOR SUPPORT ARM	U-208	2	2	2	FACILITY SOLUTIONS	TB/IT	SSP	KIT, TB, 39"L - Cradle not included
IT / POS	IT	MONITOR SUPPORT ARM	U-209	2	2	2	FACILITY SOLUTIONS	TB/IT	SSP	KIT, TB, 24.25"L, MONITOR SUPPORT ARM, CRADLE NOT INCLUDED
IT / POS	IT	KITCHEN MONITOR	U-237	1	1	1				
IT / POS	IT	KITCHEN MONITOR	U-238	5	5	5				BASE EQUIPMENT MOUNTED WITH V-LINE AND EVO ARM
IT / POS	IT	KITCHEN MONITOR	U-238	4	4	4	VIEWSONIC		SSP	VA2055m
IT / POS	IT	MONITOR CEILING MOUNTED BRACKET	U-239	1	1	1				FOR ONE MONITOR EACH. SEE DETAIL 2/A6.3
IT / POS	IT	BUMP BAR	U-250	6	6	6	SPG			WITH MOUNTING PLATE - #WST1434Y
IT / POS	IT	BUMP BAR	U-250	6	6	6	QSR AUTOMATION		SSP	WITH MOUNTING PLATE - KP-7500
SMALLWARES	BUILDING MISCELLANEOUS	Trash Container	B-400	3	3	3	RUBBERMAID	DISTRIBUTOR	GC	32 Gal, Gray Rubbermaid #2632, WSM #652801
SMALLWARES	BUILDING MISCELLANEOUS	Dolly	B-400	3	3	3	RUBBERMAID	DISTRIBUTOR	GC	20, 32, 44, & 55 Gal Container, Blk, Rubbermaid 2640, WSM #65310
SMALLWARES	BUILDING MISCELLANEOUS	Waste Basket Container	B-405	5	5	5	RUBBERMAID	DISTRIBUTOR	GC	Slim Jim, W/Handles, 15 Gal. Gray, RUC#3541, WSM #6046109
SMALLWARES	BUILDING MISCELLANEOUS	WASTE BASKET	B-406	1	1	1	RUBBERMAID	DISTRIBUTOR	GC	28 QT - #FG295600BLA (BLACK)
SMALLWARES	BUILDING MISCELLANEOUS	Restroom sign - Men's	D-043	1	1	1	Technology Media Group	DISTRIBUTOR	GC	Refer to tacobellplans.com for additional sign options
SMALLWARES	BUILDING MISCELLANEOUS	Restroom sign - Women's	D-044	1	1	1	Technology Media Group	DISTRIBUTOR	GC	Refer to tacobellplans.com for additional sign options
SMALLWARES	BUILDING MISCELLANEOUS	Exit Sign	D-056	2	2	2	Technology Media Group	DISTRIBUTOR	GC	
SMALLWARES	BUILDING MISCELLANEOUS	First Aid Kit	F-270	1	1	1	PROSTAT FIRST AID YUM	DISTRIBUTOR	GC	36U
SMALLWARES	BUILDING MISCELLANEOUS	Floor Matt	F-915	1	1	1	CREWSAFE	DISTRIBUTOR	GC	RUBBERIZED - 3'X5', Ribbed, Entrance I #41150012, Charcoal, WSM #800503
SMALLWARES	BUILDING MISCELLANEOUS	Rubber Matt	F-920	1	1	1	CREWSAFE	DISTRIBUTOR	GC	RUBBERIZED - Black, 2'X8', 1/4", 2/Non Slip Corrugated Top & Rubber No-Slip Back Entrance #4-4450, WSM #800507
SMALLWARES	KITCHEN MISCELLANEOUS	Knife rack	P-550	1	1	1	EDLUND	DISTRIBUTOR	GC	S/S, 12" X12" X2 5/8", W/12" Skirt & Open Back, NSF, Hold 8 Chef'S Knives Plus 2 Smaller Knives, 1 Steel, Scissors Edlund #KR-699, WSM #303500
SMALLWARES	KITCHEN MISCELLANEOUS	Condiment Cart	S-254	1	1	1	PRONTO	DISTRIBUTOR	GC	TB, 17"Lx10.25"Wx6"H, Plain Steel W/Black Powder Coat Finish, Plastisol Feet, Custom Pronto #CHPW0446, WSM #6020323
SMALLWARES	KITCHEN MISCELLANEOUS	Straw Holder	S-283	1	1	1	SPG	DISTRIBUTOR	GC	Wst788E, F/Ka/Kl, Includes: (1) Dchese (4) Dsdvbl, (1) Dsfese, (1) Dste
SMALLWARES	KITCHEN MISCELLANEOUS	Lid dispenser	S-443	1	1	1	CAL-MIL ADA	DISTRIBUTOR	GC	18"Hx23"Dx10"W STRAW - LID DISPENSER - TB103
SMALLWARES	KITCHEN MISCELLANEOUS	Napkin dispenser	S-444	1	1	1	Tork Xpressnap	DISTRIBUTOR	GC	#5555100
SMALLWARES	KITCHEN MISCELLANEOUS	Paper bag holder	S-448	2	2	2	WSM	DISTRIBUTOR	GC	TB, Nemco #69400, S/S, Custom WSM #6034878
SMALLWARES	KITCHEN MISCELLANEOUS	Cup Dispenser	S-482	1	1	1	A.J. ANTUNES	DISTRIBUTOR	GC	DRIVE THRU - #DAC560
SMALLWARES	KITCHEN MISCELLANEOUS	Scale	S-489	2	2	2	EDLUND	DISTRIBUTOR	GC	10#X. 1OZ, Electronic, Edlund #DS-10 CSTM; WSM #113464
SMALLWARES	KITCHEN MISCELLANEOUS	VERTICAL CUP DISPENSER	S-710	4	4	4	A.J. ANTUNES	DISTRIBUTOR	GC	TO BE INSTALLED IN CUP MODULE AT POS - # DAC 5 - Refer to Furniture Catalog on tacobellplans.com for POS configuration options





CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD




EQUIPMENT SCHEDULE

A2.4





NOTE: VESTIBULE OPTION IS SITE SPECIFIC INDEPENDENT OF PATIO OPTION



ROOF PLAN 1/4" = 1'-0" **A**

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD



SCUPPER FLASHING **F**

WATERPROOFING:
 A. PAINT UNDERSIDE OF PARAPET CAP FLASHING WITH FACTORY BONDED PAINT GRIP OR PRIMER.
 B. TOP NAILING AT PARAPET CAP FLASHING WILL NOT BE ACCEPTED.
 C. PENETRATIONS IN ROOFING MEMBRANE AND FLASHING SHALL ONLY BE MADE AS INDICATED ON THE DRAWINGS OR SPECS.
 D. SEE SPECIFICATIONS FOR SEALANT SPECS.
 E. ALL SHEET MTL FLASHING SHALL BE 22 GA MIN.

MISCELLANEOUS:
 A. ROOF PENETRATIONS CLOSER THAN 12" FROM ANOTHER WILL NOT BE ALLOWED.
 B. EXHAUST FANS MIN. 10'-0" AWAY FROM ALL AIR INTAKE / SUPPLY.
 C. LOCATE WALK-IN CONDENSERS ON ROOF ONLY IF REQUIRED BY CODE.

ROOF PLAN NOTES **E**


- 1 ROOFTOP UNIT. INSTALL PLUMB AND LEVEL.
- 2 KITCHEN HOOD EXHAUST FAN. SEE SHEETS M3.0 & DETAIL 19/A6.0.
- 3 RESTROOM EXHAUST FAN. SEE 18/A6.0.
- 4 CANOPY. SEE SCOPE OF WORK.
- 5 ROOF HATCH: SEE 7/A6.0.
- 6 ICE MACHINE CONDENSERS.
- 7 WALK-IN COOLER / FREEZER CONDENSERS. SEE SCOPE OF WORK SHEET.
- 8 EQUIPMENT PLATFORM. SEE DETAIL 15/A6.0.
- 9 PIPE HOOD FOR UTILITIES. SEE DETAIL 9/A6.0.
- 10 24x36 WALK MATS. SEE ROOF SPECS.
- 11 SCUPPER AND DOWNSPOUT. SEE DETAIL F/A3.0.
- 12 WATER HEATER INTAKE. SEE DETAIL 13/A6.0 FOR BRACING.
- 13 WATER HEATER EXHAUST FLUE SHALL BE MIN. 6" HIGHER THAN INTAKE-MAINTAIN MIN. 10'-0" FROM NEAREST POINT OF RTU INTAKE. SEE DETAIL 13/A6.0 FOR BRACING.
- 14 CHANGE IN PARAPET ELEVATION SEE DETAIL 14/A6.2.
- 15 ROOF CRICKET. SEE DETAIL 16/A6.0.
- 16 METAL PARAPET CAP. SEE DETAIL 2 & 5/A6.0.
- 17 MAINTAIN MFR'S ROOFTOP UNIT MAINTENANCE CLEARANCE.
- 18 OUTSIDE AIR INTAKE FOR ROOFTOP UNIT. MAINTAIN MIN 10'-0" SEPARATION FROM PLUMBING VENTS, FLUES AND BUILDING EXHAUST.
- 19 WASTE VENT THROUGH ROOF. THE TOP OF WASTE VENTS SHALL BE 12" HIGHER THAN THE CLOSEST PARAPET CAP U.N.O. OR NOT ALLOWED BY LOCAL JURISDICTION. SEE 12/A6.0 FOR FLASHING ASSEMBLY.
- 20 POWER / GAS / CONDENSATE ENTRY UNDER HVAC UNIT (PER HVAC MFR. SPECS.) REFER TO MECH. AND PLUMB DWGS. UTILITY ACCESS FROM WITHIN CURB - NO ROOF PENETRATIONS. DO NOT RUN ON ROOF SURFACE. SEE 13/P6.0.
- 21 "DURO-LAST" SINGLE PLY ROOF MEMBRANE OVER MINIMUM R-20 RIGID INSULATION BOARD OVER 5/8" APA RATED EXTERIOR GRADE PLYWOOD OVER TRUSSES. INSTALL PER MANUFACTURERS SPECIFICATIONS.
- 22 OVERFLOW SCUPPER. SEE DETAIL F/A-3.0.
- 23 DUAL REMOTE CONDENSER. REFER ELECTRICAL AND PLUMBING.
- 24 GUTTER AND DOWNSPOUT.

KEY NOTES **B**


TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544




ROOF PLAN
A3.0



LEFT SIDE ELEVATION 1/4" = 1'-0" A




FRONT ELEVATION 1/4" = 1'-0" C



REAR ELEVATION 1/4" = 1'-0" B

NOTE: VESTIBULE OPTION IS SITE SPECIFIC INDEPENDENT OF PATIO OPTION

ARCVISION
 INCORPORATED
 ARCHITECTURE ENGINEERING STORE PLANNING
 SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
 1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
 PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com



OWN/STATE COMMENTS 08.10.20






CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544















EXTERIOR ELEVATIONS


A4.1



- NOTES**
- 1 PROVIDE A WOOD NAILER TO MATCH THE THICKNESS OF THE WALL FINISH. APPROX. 1" THICK IS TYPICAL BUT MAY VARY. TOP OF WOOD NAILER SHALL BE FLUSH WITH TOP OF WALL FINISH. THE WOOD NAILER SHALL EXTEND AT LEAST 1/2" INCH BEYOND THE LOWER HORIZONTAL EDGE OF THE PARAPET COPING TO ALLOW FOR PROPER FASTENING.
 - 2 FASTENERS USED TO ATTACH THE COPING TO WOOD NAILERS, MUST BE SPACED NO GREATER THAN 18 - INCHES ON-CENTER.
 - 3 ALLOW FOR 1/8 - INCH EXPANSION GAP BETWEEN 10-FOOT LENGTHS OF COPING. PROVIDE A COPING JOINT COVERS BETWEEN ENDS OF COPING PIECES AND AT CORNERS. JOINT COVERS SHOULD BE MADE FROM THE SAME MATERIAL AS THE COPING AND SHOULD LAP THE JOINTS A MINIMUM OF 6" ON EITHER SIDE. JOINT COVERS SHALL BE FASTENED THE SAME WAY AS THE COPING.
 - 4 FIBER CANT STRIP SLOPED 1/4:12 TOWARDS ROOF.
 - 5 ROOF MEMBRANE
 - 6 FACTORY PAINTED 24 GAUGE METAL COPING WITH 4" DROP FRONT, BACK AND ENDS (WHERE SHOWN).
 - 7 WALL FINISH: TYPICALLY 1" THK EIFS OR 7/8" THK STUCCO
 - 8 DOUBLE 2X TOP PLATE
 - 9 PLYWOOD SUBSTRATE. SEE SHEET A1.0 & S2.0 FOR ADDITIONAL DETAILS



ARCVISION
INCORPORATED
 ARCHITECTURE ENGINEERING STORE PLANNING
 SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
 1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
 PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com




















OWN/STATE COMMENTS 08.10.20

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
 MEDIUM40

CONSTRUCTION
DETAILS
ROOF
A6.0



ARCVISION
INCORPORATED
ARCHITECTURE ENGINEERING STORE PLANNING
SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com



OWN/STATE COMMENTS 08.10.20


CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
MEDIUM40

**CONSTRUCTION
DETAILS
DOOR/WINDOW**

A6.1



1 - PRE-WATERPROOFING


2 - FINISH-WATERPROOFING

NOTES


- 1 2X WOOD STUDS
- 2 PLYWOOD SUBSTRATE FOR EXTERIOR WALLS
- 3 FLASHING TAPE AT ALL VERTICAL PARAPET TRANSITIONS. EXTEND TAPE 12" OUTWARD AND UPWARD FROM CORNER AS SHOWN. LAP CORNERS WITH ANGLED TAPE AS SHOWN TO INSURE FULL COVERAGE AT CORNERS
- 4 DOUBLE 2X TOP PLATE
- 5 PAINTED 24 GAUGE PARAPET COPING. SLOPE 1/4:1 TOWARDS ROOF WITH FIBER CANT STRIPS UNDER COPING. LAP FRONT AND BACK EDGE 2" DOWN VERTICAL FACE. LAP EXPOSED COPING EDGE EXPOSED ENDS AT VERTICAL PARAPET TRANSITION.
- 6 WRAP 1" THICK EIFS ONTO VERTICAL FACE OF PARAPET TRANSITION
- 7 EIFS FINISH ON OUTER SURFACE OF EXTERIOR WALL. THICKNESS PER THE EXTERIOR ELEVATIONS ON SHEET A4.0
- 8 TERMINATION BAR AT VERTICAL TRANSITION OF EIFS AND MEMBRANE ROOFING. SEAL VERTICAL GAP BETWEEN TERMINATION BAR AND EIFS PER ROOFING MANUFACTURER SPECIFICATIONS.
- 9 PVC ROOFING MEMBRANE ON BACKSIDE OF PARAPET.

IMPORTANT: ONLY FASTEN PARAPET COPING ALONG THE FRONT AND BACK VERTICAL EDGE. NEVER ON TOP OF COPING.


PARAPET CAP & TRANSITION N.T.S. 14




CONNECTION THRU EIFS 3" = 1'-0" 9




CO2 FILL / J-BOX IN EIFS 3" = 1'-0" 5




PATIO CANOPY DETAIL 1




METAL PANEL BASE AT TOWER 1" = 1'-0" 10





TYP. E.I.F.S. @ INSIDE CORNER N.T.S. 6




TYP. E.I.F.S. TRIM HIGH-IMPACT N.T.S. 2




E.I.F.S. TRANSITION @ SLAT WALL 3" = 1'-0" 19




E.I.F.S FLASHING AT TOP OF BREAK METAL 12




E.I.F.S. TO BASE FLASHING N.T.S. 7



HOSE BIB BOX N.T.S. 8



FRONT ROOF CONNECTION DETAIL 3" = 1'-0" 20



TYP. E.I.F.S. BASE TERMINATION N.T.S. 4

NOT AN OPTION: Do not caulk below EIFS starter track edge & galv. mtl. flashing to allow for drainage behind EIFS.

NOTE: E.I.F.S. DETAILS ARE INTENDED TO BE GENERIC. MANUFACTURER'S DETAILS AND RECOMMENDATIONS SHOULD BE FOLLOWED. REFER TO SECTION 07240 OF THE SPECIFICATIONS MANUAL.

ARCVISION
 INCORPORATED
 ARCHITECTURE ENGINEERING STORE PLANNING
 SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
 1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
 PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com

Jason J. Griffin
 ARCHITECT
 No. 00920072
 STATE OF INDIANA
 8/10/20





















CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD


TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544

TACO BELL
 EXPLORER LITE
 MEDIUM40


CONSTRUCTION DETAILS WALL

A6.2







WALL PASS THRU NTS 11




CASED OPENING DETAIL 3' = 1'-0" 7



SYRUP LINE IN CEILING N.T.S. 17



JAMB @ H.M. DOOR 3' = 1'-0" 10




VALANCE WALL REQUIREMENTS
26.2' H x 156.8' L (MINIMUM)
IF YOUR VALANCE WALL DOES NOT MEET THESE REQUIREMENTS PLEASE NOTIFY STRATACACHE IMMEDIATELY

- NOTES:
- EC/GC TO INSTALL A TOTAL OS (4) IG5262 DUPLEX OUTLETS IN (2) QUAD BOXES ON FRONT OF VALANCE WALL AS SHOWN. OUTLETS TO BE ORANGE AND STRAIGHT BLADE.
 - EC/GC TO EVALUATE VALANCE WALL STRUCTURE TO ENSURE ADEQUATE SUPPORT OF DIGITAL MENU BOARDS EQUIPMENT EC/GC TO INSTALL ADDITIONAL BACKING MATERIALS (AS REFERENCED ON DRAWINGS) AS NEEDED TO ENSURE ADEQUATE SUPPORT OF DIGITAL MENU BOARDS
 - EC/GC TO INSTALL (1) DATA JUNCTION (JB) IN VALANCE WALL AS SHOWN. CONDUIT TERMINATED ABOVE CEILING TO HAVE BUSHING.
 - EC/GC TO RUN (3) CAT6 LINES FROM NETWORK SWITCH TO DATA JUNCTION BOX. CAT6 LINES SHOULD HAVE BOTH PROPERLY TERMINATED WITH RJ-45 CONNECTORS. EXCESS CAT6 CABLE TO BE COILED INTO SERVICE LOOPS AT EACH END AND LEFT ACCESSIBLE FOR DMB INSTALL TEA. CAT6 TO BE RUN IN ACCORDANCE WITH ALL LOCAL MUNICIPALITY CODE REQUIREMENTS.
 - EC/GC SHALL ACQUIRE AND SECURE ANY/ALL REQUIRED PERMITTING FOR THE WORK MENTIONED ABOVE PER MUNICIPALITY CODE REQUIREMENTS.
 - DRAWING PROVIDED IS FOR INSTALLATION OF DMB EQUIPMENT ONLY. NOT TO BE USED FOR ARCHITECTURAL PURPOSES. IF PLACEMENT OF REQUIRED ELEMENTS CANNOT BE MET AND WILL EXCEED A 3IN DEVIATION, STRATACACHE MUST BE NOTIFIED IMMEDIATELY.


JB = JUNCTION BOX
GC = GENERAL CONTRACTOR
EC = ELECTRICAL CONTRACTOR

ELECTRICAL SCHEDULE								
QTY	DESCRIPTION	VOLT/PH	BRK SIZE	COND/WIRE	PNL/CCT	RECP TYPE	HGT AFF	REQUIREMENT & REMARKS
4	MENUE BOARD - DIGITAL & MEDIA PLAYER	120/1 ISOLATED	20A			(4) IG5262	SEE PLAN	SEE LAYOUT AND NOTES


WALL MOUNTED DMB DETAIL N.T.S. 1




SYRUP BUNDLE CLG. PENETRATION N.T.S. 18




INTERIOR CHASE WALL N.T.S. 14




FINISH TRISITION AT TOWER 1 1/2" = 1'-0" 3



SYRUP CHASE ON WALL N.T.S. 19



METAL PANEL @ CORNER TOWER 1 1/2" = 1'-0" 4



MENU BOARD/SOFFIT SECTION 3/4" = 1'-0" 2

ARCVISION
INCORPORATED
ARCHITECTURE ENGINEERING STORE PLANNING
SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com

Richard J. Goff
STATE OF INDIANA ARCHITECT
8/10/20

OWN/STATE COMMENTS 08.10.20


CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
MEDIUM40

CONSTRUCTION DETAILS INTERIOR A6.4

6/29/20



△	OWN/STATE COMMENTS 08.10.20
△	
△	
△	
△	
△	
△	
△	
△	
△	


CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544


TACO BELL
EXPLORER LITE
 MEDIUM40

INTERIOR ELEVATIONS KITCHEN


A8.3




1



2




3




4

SERVING 3/8" = 1'-0"

GTO DUAL LINE 3/8" = 1'-0"




A - ROOF LADDER VIEW



5

EMPLOYEE / STORAGE 3/8" = 1'-0"




INSTALL IN ACCORDANCE WITH STATE AND LOCAL PLUMBING CODES.
 In states or municipalities requiring dedicated or hard-plumbed water lines, the dispensing unit at the 3-compartment sink must be connected to a "TEMPERED" water source. This may require the installation of a mixing/tempering valve.

ECOLAB Key Chemical Company
 8360 Capital Drive Greensboro, NC 27409-9790, USA 800.529.5458

OSR 44-680/B000/1092 ©2012 Key Chemical Company. All Rights Reserved.

MOP SINK INSTALLATION



5

ROOF ACCESS PASSAGEWAY N.T.S. **B**

- 1 SAFE - INSTALLATION BY BRINKS
- 2 FAN MOTOR STARTERS, SURFACE MOUNTED. TYP. OF 2.
- 3 HOLD-UP BUTTON
- 4 UTILITY CHASE.
- 5 TEMPERATURE SENSOR. SEE MECHANICAL DRAWINGS.


KEY NOTES

A



TOTAL SEATS ACCESSIBLE SEATS

1 - 20	1
21 - 40	2
41 - 60	3
61 - 80	4
81 - 100	5
101 - 120	6
121 - 140	7


NUMBER OF ACCESSIBLE SEATS



SEATING AND TABLES N.T.S. 18




EXAMPLE: DRINK MACHINE, ETC.




CONDIMENTS

REACH RANGES N.T.S. 14


NOTES:
1. TOP OF GRIPPING SURFACE 33" TO 36" MAX TO THE TOP OF THE BAR. SEE NOTES BELOW
2. 12" MINIMUM CLEAR ABOVE GRAB BAR




MOUNTING HTS. & CLEARANCES FOR ACCESSIBILITY BY THE DISABLED N.T.S. 1




INT. ACCESS. ROUTE CLEARANCES 1/2" = 1'-0" 10




ACCESSIBLE URINAL 3/4" = 1'-0" 6




STANDARD TOILET STALL N.T.S. 2




ACCESSIBLE RESTROOM DOORS N.T.S. 15




PROTRUDING HAZARDS 1/2" = 1'-0" 11



GRAB BAR 3/4" = 1'-0" 7




ACCESSIBLE LAVATORY 3/4" = 1'-0" 3



BOBRICK OR CHRISTY COMMERCIAL HARDWARE & SUPPLY WAREHOUSE #039-6529 OR SIMILAR ADA COMPLIANT HOOK. CHRISTY-HARDWARE.COM 877-544-5400


NOTE: SEE DOOR SCHEDULE. AND DOOR SCHEDULE NOTES

COAT HOOK N.T.S. 20




NOTE: SEE DOOR SCHEDULE. AND DOOR SCHEDULE NOTES

PARTITION DOOR LATCH @ PULL 16



CHANGES IN LEVEL N.T.S. 12



NOTE:
1. MAINTAIN 36" MIN. CLEAR AISLE EGRESS PATHS TO EXIT DOORS.
2. INTERNATIONAL SYMBOL OF ACCESSIBILITY REQUIRED ON TOP EDGE OR FRONT OF ALL ACCESSIBLE TABLES.

DINING ROOM SEATING CLEARANCES N.T.S. 8

1. INDICATED DIMENSIONS, HEIGHTS, DEPTHS, AREAS AND OTHER GRAPHIC INFORMATION ARE PROVIDED AS MINIMUMS THAT MUST BE MAINTAINED. THESE MINIMUMS ARE BASED UPON YUM STANDARDS AND MAY EXCEED ADA REQUIREMENTS.
2. 60" TURNING SPACE
- PERMITTED OVERLAP LIMITED TO 1 ARM OF T-SHAPED SPACE
- CAN OVERLAP FIXTURE & DOOR CLEARANCE
- DOOR CAN SWING INTO TURNING SPACE A MAXIMUM OF 12"
3. RESTROOM, IN GENERAL, DOOR SWING MUST BE OUTSIDE OF THE FIXTURE CLEAR FLOOR SPACE HOWEVER A DOOR CAN SWING INTO FIXTURE CLEAR FLOOR SPACE IF WHEELCHAIR SPACE 30"x48" IS PROVIDED BEYOND THE DOOR SWING.
4. TOILET ROOM MUST ALLOW FOR SIDE TRANSFER - 42" BETWEEN FIXTURES

GENERAL NOTES 4

ARCVISION
INCORPORATED
ARCHITECTURE ENGINEERING STORE PLANNING
SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com

Dickson
ARCHITECT
STATE OF INDIANA
8/10/20

OWN/STATE COMMENTS 08.10.20

CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
MEDIUM40

ACCESSIBILITY
REQUIREMENTS
ADA1.0

GENERAL:

- LOCATE, CUT AND FRAME ROOF OPENINGS AS SHOWN FOR ALL HVAC EQUIPMENT AND EXHAUST FANS.
- IT IS VERY IMPORTANT THAT ACCURATE MEASUREMENTS ARE USED WHEN LOCATING EXHAUST FAN ROOF OPENINGS TO ENSURE THAT NO ADDITIONAL OFF-SETS ARE REQUIRED IN THE EXHAUST DUCTWORK. COORDINATE ROOF OPENINGS WITH THE KITCHEN EQUIPMENT.
- PROVIDE ANY FRAMING REQUIRED FOR DIFFUSER INSTALLATION IN HARD CEILING.

HVAC:

- INSTALLATION SHALL CONFORM TO THE ENERGY CONSERVATION DESIGN MANUAL STANDARDS FOR NEW NONRESIDENTIAL BUILDINGS.
- ALL WORK AND MATERIALS SHALL COMPLY WITH GOVERNING CODES, SAFETY ORDERS AND REGULATIONS.
- OBTAIN AND PAY FOR ALL NECESSARY PERMITS, FEES AND INSPECTIONS REQUIRED BY GOVERNING AUTHORITIES.
- E.C. SHALL PROVIDE CONDUIT FOR LINE AND LOW VOLTAGE WIRING, LINE VOLTAGE WIRING SWITCHES, AND FINAL CONNECTIONS.
- M.C. SHALL PROVIDE 24V CONTROL WIRING AND FINAL CONNECTIONS. ANY EQUIPMENT THAT IS SUBSTITUTED SHALL FIT IN THE SPACE PROVIDED WITH ADEQUATE ROOM FOR SERVICING, INCLUDING SUBSTITUTE EQUIPMENT NAMED IN THE SPECIFICATIONS. SUBMIT A 1/4" SCALE DRAWING OF ALL EQUIPMENT SUBSTITUTED FOR APPROVAL PRIOR TO INSTALLATION, INCLUDING, BUT NOT LIMITED TO, STRUCTURAL AND ARCHITECTURAL IMPACT, CLEARANCE REQUIREMENTS AND UTILITY REQUIREMENTS.
- FOR INSTALLATION OF RECHARGEABLE REFRIGERANT LINES FROM ICE MACHINE TO CONDENSER ON ROOF, SEE SCOPE OF WORK.
- HVAC UNITS SHALL BE MOUNTED LEVEL ON ROOF CURBS.
- ALL SUPPLY / RETURN DUCTWORK SHALL BE EXTERNALLY INSULATED.
- ALL SUPPLY / RETURN DUCTS SHALL BE RIGID, WITH THE EXCEPTION OF THE LAST 5'-0", WHICH MAY BE FLEX.
- SMOKE DETECTOR SHALL BE INSTALLED IN THE RETURN AIR DUCT, PRIOR TO ANY OUTSIDE AIR CONNECTIONS, AND SHALL DEACTIVATE ROOFTOP UNIT UPON SENSING SMOKE. INCLUDE SMOKE DETECTOR IN THE SUPPLY AIR DUCT ONLY IF REQUIRED BY LOCAL CODE.
- ALL HOOD EXHAUST DUCTS SHALL BE RIGID 16 GA MINIMUM, WELDED DUCT. GRIND ALL WELDS SMOOTH. PROVIDE 3M FIRE BARRIER DUCT WRAP FOR ALL HOOD EXHAUST DUCTS. SEE 15/M4.0.
- ALL BRANCH DUCTS FEEDING INDIVIDUAL DIFFUSERS SHALL HAVE DAMPERS AT TAKEOFFS FOR AIR BALANCING. PROVIDE ACCESS PANELS TO DAMPERS. SEE 8/M4.0.
- ALL UTILITY PIPING FOR RTUS SHALL RUN UP THROUGH ROOF INSIDE EACH UNIT'S ROOF CURB.
- ALL OUTSIDE AIR INTAKES SHALL BE A MINIMUM OF 10'-0" FROM EXHAUST FANS AND / OR VENTS.
- SEE 8/M1.0 AND SCOPE OF WORK FOR DESCRIPTION OF HVAC PACKAGE TO BE PURCHASED THROUGH YUM! BRANDS NATIONAL CONTRACT.
- FINAL HVAC SYSTEM TESTING AND BALANCING SHALL BE PERFORMED BY INDEPENDENT AGENT CONTRACTED DIRECTLY BY THE OWNER. A RE-TEST IS MANDATORY FOR A FALSE START (I.E. NO POWER UPON AGENT'S ARRIVAL, EQUIPMENT NOT WIRED, ETC.) AND SHALL BE A COST INCURRED BY THE G.C. IN THE EVENT A SYSTEM / STORE RECEIVES A GRADE OF 5 OR BELOW AS A RESULT OF THE HVAC SYSTEM PERFORMANCE OR OPERATIONAL DEFICIENCIES, OWNER WILL REQUEST A RE-TEST AND THE COST FOR SAME SHALL BE ALSO INCURRED BY THE GENERAL CONTRACTOR.
- TRANE THERMOSTAT & REMOTE SENSOR BAYSENS119, PROVIDED WITH TRANE PACKAGE.

REFER TO SCOPE OF WORK 15700-1 HVAC FOR TEST & BALANCE & COMMISSIONING REQUIREMENTS WHICH WILL BE SUPPLIED BY THE OWNER AND COORDINATED BY THE GC.



GENERAL NOTES 10

SYMBOL & ABBREV.	DESCRIPTION
	SA/SUP SUPPLY AIR (RISE/DROP)
	RA/RET RETURN AIR DUCT (RISE/DROP)
	EA/EXH EXHAUST AIR DUCT (RISE/DROP)
	CD/SR CEILING DIFFUSER/SUPPLY REGISTER (ARROWHEAD REPRESENTS NUMBER OF THROW)
	RR/RG RETURN REGISTER/GRILLE
	ER/EG EXHAUST REGISTER/GRILLE
	RECTANGULAR DUCT ELBOW WITH TURNING VANES
	MVD MANUAL VOLUME DAMPER
	FD FIRE DAMPER
	(L) DUCT LINING (1" THICK UNLESS OTHERWISE NOTED)
	FLEX FLEXIBLE DUCT (14'-0" MAXIMUM)
	T-STAT PROGRAMMABLE THERMOSTAT, PROVIDED WITH TRANE PACKAGE.
	TS THERMOSTAT SENSOR (REMOTE), PROVIDED WITH TRANE PACKAGE.
	H HUMIDITY SENSOR (REMOTE), PROVIDED WITH TRANE PACKAGE.
	D CONDENSATE DRAIN
	DIA. DIAMETER
	DL DOOR LOUVER
	UC DOOR UNDERCUT (3/4" MINIMUM)
	(X-X) 0000 MECHANICAL EQUIPMENT DESIGNATION
	R RESET SMOKE DETECTOR RESET
	DL DOUBLE LINE DUCT SHOE TAP BRANCH TAKEOFF WITH VOLUME DAMPER

SYMBOL & ABBREV.	DESCRIPTION
A/C, AC	AIR CONDITIONING
BDD	BACK DRAFT DAMPER
CB	CIRCUIT BREAKER
CLG.	CEILING
CONN.	CONNECT/CONNECTION
CONT.	CONTINUATION
CONTR	CONTRACTOR
CFM	CUBIC FEET PER MINUTE
DET.	DETAIL
DISC.	DISCONNECT
DTR	DOWN THRU ROOF
EF	EXHAUST FAN
(E)	EXISTING
GA.	GAGE/GAUGE
GC	GENERAL CONTRACTOR
HVAC	HEATING, VENTILATING, AND AIR CONDITIONING
MFR.	MANUFACTURER
MECH.	MECHANICAL
(N)	NEW
OA/OA	OUTSIDE AIR
OBD	OPPOSED BLADE DAMPER
S/S	STAINLESS STEEL
TYP.	TYPICAL
UON	UNLESS OTHERWISE NOTED
UTR	UP THRU ROOF

MECHANICAL SYMBOLS 12

XX-XXX MARK	AREA SERVED	FAN DATA						COOLING CAPACITY			HEATING CAPACITY			UNIT ELECT DATA			MAX UNIT WEIGHT (LBS)	MANUFACTURER AND MODEL NUMBER	REMARKS
		SUPPLY CFM	MIN O.A. CFM	ESP	HP	RPM	NOM TONS	MIN CAP (MBH) TOT/SEN	EER	INPUT (MBH)	OUTPUT (MBH)	STAGES	AFUE	VOLTS/PH	MCA	MOPD			
RTU-1	DINING	3000	750	0.8*	2.75	1217	7.5	98.09/63.63	12.6	200	160	2	80	208/3	42.0	50.0	1255	TRANE YHC092F3RHA-FQC1C2A000C3	SEE NOTES 1-4
RTU-2	KITCHEN	6000	1050	1*	3	747	15.0	190.46/140.67	12.1	350	280	2	80	208/3	68.0	90.0	2701	TRANE YHD180G3RHB-FQC1C2A000C3	SEE NOTES 1-4

SCHEDULE NOTES:

- LISTED CAPACITY IS THE UNITS NET COOLING CAPACITY AT THE FOLLOWING CONDITIONS: RTU-1 - 81.2°F DB / 61.5°F WB EAT AND 95°F AMBIENT / RTU-2 - 82.0°F DB / 57.6°F WB EAT AND 95°F AMBIENT. OUTDOOR DESIGN CONDITION: SUMMER 90°F & 73°F WB, WINTER -2°F. THERMOSTAT SHALL BE PROGRAMMED FOR 73°F IN SUMMER AND 68°F IN WINTER WITH 2°F ADJ. FUNCTION UP OR DOWN. THE UNOCCUPIED TEMP SHALL BE SET TO THE STORE SCHEDULE AND 60°F MINIMUM.
- SPECIFIED RTUS ARE DOWN DISCHARGE PACKAGED GAS / ELECTRIC ROOFTOP UNITS WITH MINIMUM 2-STAGE COOLING. INCLUDES THROUGH THE ROOF CURB POWER, GAS & CONDENSATE DRAIN. GAS PIPING SHALL BE FACTORY RIGID WITH SHUT-OFF OUTSIDE OF UNIT.
- SPECIFIED UNIT INCLUDES HINGED ACCESS DOORS, 2 PLEATED FILTERS, LOW AMBIENT CONTROL TO 0 DEG. F., REFERENCE ENTHALPY ECONOMIZER (0-100%) WITH BAROMETRIC RELIEF, CIRCUIT BREAKER WITH SINGLE POINT WIRING, HAIL GUARD, FACTORY FABRICATED, KNOCK DOWN ROOF CURB, FACTORY INSTALLED DISCHARGE AIR SENSING TUBE.
- THERMOSTAT AND REMOTE SENSOR PROVIDED WITH HVAC PACKAGE. THERMOSTAT TO BE TRANE BAYSENS119 PROGRAMMABLE ZONE THERMOSTAT W/ REMOTE SENSOR OR EQUIVALENT.

HVAC UNIT SCHEDULE 1

XX-XXX MARK	CFM	SP	RPM	HP	ELECT	STARTER	ACCESSORIES					MANUFACTURER AND MODEL NUMBER	REMARKS
							DISC	BDD	BDD SCREEN	V-BELT	D-DR		
EF-1	1050	0.9	1344	0.50	120/1	-	X	-	-	-	X	STRATOVENT #SVDU50HFA	SEE NOTES 1,3,5,6,7,8,10
EF-2	570	.375	1025	1/4	120/1	-	X	X	X	X	X	STRATOVENT #SVD30HFA	SEE NOTES 2,4,7,8,9,10,11

SUPPLY AND EXHAUST FAN SCHEDULE 2

XX-XXX MARK	QUANTITY	NECK SIZE	DIFFUSER FACE OR CEILING GRID SIZE	TYPE			(NO.) & AIR PATTERN	MOUNTING		DUTY		MATERIAL		MANUFACTURER	MODEL NUMBER	REMARKS
				DIFFUSER	REGISTER	GRILL		LAY-IN	SURFACE	SUPPLY	RETURN	EXHAUST	ALUMINUM			
S-1	14	15x15	24x24	X			(6)4W (6)3W		X			X	METAL-AIRE / TITUS	5000-6 / TDC-AA-NT	FRN SQR TO RND ADAPTER	
S-3	2	9x9	14x14	X			(2)4W 0-250	X				X	METAL-AIRE / TITUS	5000-1 / TDC-AA	FRN SQR TO RND ADAPTER, PROVIDE SURFACE MOUNT BORDER.	
S-4	3	12"Ø	24x24	X			VERT 300-700	X	X			X	HART & COOLEY	RZMCDST	PLASTIC MODULAR CORE	
S-5	1	8x6	10x6			X	NO DIREC 0-150	X	X			X	METAL-AIRE / TITUS	4000-AF / 300FL	PROVIDE SURFACE MOUNT BORDER.	
R-1	6	20x20	24x24			X	NO DIREC 0-2000	X		X		X	METAL-AIRE / TITUS	RHE-6 / 50FF	HINGED / FULLY REMOVABLE FACE	
E-1	2	8x8	12x12		X		NO DIREC 0-200	X			X	X	METAL-AIRE / TITUS	CC5S-1 / 50F	FRN SQR TO RND ADAPTER PROVIDE SURFACE MOUNT BORDER.	
E-2	1	10x10	24x24		X		NO DIREC 0-400	X			X		METAL-AIRE / TITUS	CC5-FB-TB / 50F-NT	PROVIDE 2x2 LAY-IN PANEL; FRN SQR TO RND ADAPTER	

NOTES:
1. DIFFUSERS IN SURFACE MOUNTED CEILINGS SHALL BE PROVIDED WITH OPPOSED BLADE DAMPERS. SEE ARCHITECTURAL DRAWINGS FOR CEILING TYPES.

AIR DEVICE SCHEDULE 3

ITEM	OA	RA	SA	EA	PRESSURE
EF-1	--	--	--	1050	-1050
EF-2	--	--	--	570	-570
RTU-1	750	2250	3000	--	-750
RTU-2	1050	4950	6000	--	+1050
TOTAL	1800	7200	9000	1620	+180

NOTE: THE OUTSIDE PERCENTAGE OF TOTAL SUPPLY AIR IS 25% FOR RTU-1 AND 17.1% FOR RTU-2.

AIR BALANCE SCHEDULE CFM 4

TRANE PACKAGE N.T.S. 8


FOR COMPLETE INFORMATION AND PRICING ON THE TRANE HVAC PACKAGE CONTACT MARTY CUSICK, THE YUM! BRANDS ACCOUNT EXECUTIVE AT TRANE NATIONAL ACCOUNTS.
TOLL-FREE PHONE: (866) YUM-HVAC or (866) 986-4822
FAX: (502) 499-7870
EMAIL: mcusick@trane.com

FOR HVAC TEST AND BALANCE, GC TO SCHEDULE WITH TACO BELL'S PREFERRED VENDOR PER SCOPE OF WORK WORKSHEETS.

BE PREPARED AT TIME OF ORDER OR QUOTE REQUEST TO PROVIDE ALL PROJECT DETAILS REGARDING SPECIFICATIONS AND QUANTITIES AS SITE SPECIFIC DESIGN MAY NOT MATCH NATIONAL DESIGN.

SEE THE SCOPE OF WORK SHEETS FOR ADDITIONAL INFORMATION.

ARCVISION
INCORPORATED
ARCHITECTURE • ENGINEERING • STORE PLANNING
SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
PH. (314) 415-2400 FAX (314) 415-2300
www.arcvision.com



OWN/STATE COMMENTS 08.10.20



CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
MEDIUM40


MECHANICAL SCHEDULES AND NOTES

M1.0



MEP ROOF PLAN 1/4"=1'-0" **A**

- ① MAINTAIN AT LEAST 10' BETWEEN ALL EXHAUST OUTLETS AND OUTSIDE AIR INTAKES.
- ② ENSURE VTR IS MINIMUM 10' FROM ALL OUTSIDE AIR INTAKES.
- ③ PROVIDE 3" PVC WATER HEATER INTAKE TERMINATION ON ROOF. COORDINATE WORK WITH ALL OTHER TRADES. SEE 13/A6.0.
- ④ PROVIDE 3" PVC WATER HEATER FLUE VENT TERMINATION ON ROOF. COORDINATE WORK WITH ALL OTHER TRADES. ENSURE OPENING IS A MINIMUM OF 10'-0" FROM ALL OUTSIDE AIR INTAKES. SEE 13/A6.0.



△ OWN/STATE COMMENTS 08.10.20

- △
- △
- △
- △

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
 MEDIUM40
MP ROOF PLAN

MP1.0

NOT USED **F**

NOT USED **E**

KEY NOTES **B**

- SOIL AND WASTE PIPE SHALL SLOPE 2% MINIMUM, UNLESS OTHERWISE NOTED OR REQUIRED BY CODE.
- ALL DRAWN WATER & GAS LINES SHALL BE KEPT TIGHT TO THE UNDERSIDE OF EQUIPMENT & SECURED IN PLACE.
- VERIFY THE LOCATION OF THE SANITARY SEWER ON THE SITE PLAN AND SHALL REVISE THE SEWER SYSTEM AS REQUIRED.
- PROVIDE TRAP PRIMERS FOR FLOOR DRAINS IN RESTROOMS, WHERE REQUIRED BY CODES. PROVIDE DEEP SEAL TRAPS FOR FLOOR DRAINS WITHOUT TRAP PRIMERS.
- ALL CLEANOUTS SHALL BE INSTALLED WHERE READILY ACCESSIBLE. THE CONTRACTOR SHALL COORDINATE ALL CLEANOUT LOCATIONS WITH EQUIPMENT, CABINETS, ETC. AND THE OWNERS REPRESENTATIVE PRIOR TO ANY INSTALLATION.
- ALL VALVES, TRAP PRIMERS, WATER HAMMER ARRESTORS OR OTHER EQUIPMENT SHOWN IN WALLS OR ABOVE NON-ACCESSIBLE CEILING SHALL BE INSTALLED BEHIND AN ACCESS PANEL.
- ALL PLUMBING FIXTURE VENTS SHALL TERMINATE A MINIMUM OF 12 INCHES FROM ANY VERTICAL SURFACE AND 10 FEET FROM ANY OUTSIDE AIR INTAKE.
- PROVIDE GAS PIPING TO UNITS AND ALL FINAL CONNECTIONS REQUIRED FOR OPERATION.
- INSTALL SHUT-OFF VALVES ON ALL HOT & COLD WATER LINES TO FIXTURE OR APPLIANCE. ALL EXPOSED WATER AND WASTE LINES TO BE CHROME PLATED.
- PROVIDE A LEVER HANDLE GAS SHUT-OFF VALVE IN THE BRANCH PIPING OF EACH APPLIANCE OR PIECE OF EQUIPMENT. FOR EACH APPLIANCE INSTALL QUICK DISCONNECT FLEXIBLE PIPE WHEN ALLOWED BY CODE AND RESTRAINING DEVICE FURNISHED BY OWNER. PROVIDE PRESSURE REDUCING VALVES AT EACH PIECE OF EQUIPMENT OR APPLIANCE. IF GAS PRESSURE GREATER THAN 10"wc IS USED DOWNSTREAM FROM THE GAS METER.
- ALL VALVES, UNIONS, ETC. SHALL BE SAME SIZE AS PIPE UNLESS OTHERWISE INDICATED ON DRAWINGS.
- REFER TO KITCHEN EQUIPMENT DRAWINGS FOR PLUMBING ROUGH-IN SCHEDULE & FOR ADDITIONAL WORK TO BE FURNISHED & INSTALLED BY CONTRACTOR. ALL ROUGH-IN PLUMBING AND FINAL CONNECTIONS TO KITCHEN EQUIPMENT SHALL BE MADE BY THE CONTRACTOR U.O.N.
- REFER TO MECHANICAL SHEETS FOR HVAC AND HOOD PLUMBING REQUIREMENTS.
- ALL GAS LINES SHALL BE SUPPORTED SEE SPECS.
- ALL FLOOR SINKS AND FLOOR DRAINS IN TRAFFIC AREAS SHALL BE INSTALLED FLUSH TO FLOOR SURFACE.
- PROVIDE WATER HAMMER ARRESTOR FOR ALL HAND SINKS AND URINAL WATER LINES.
- PROVIDE AIR GAPS FOR INDIRECT DRAINS AS REQUIRED BY CODE. AIR GAP SHALL BE MINIMUM 2 TIMES THE DIAMETER OF THE INDIRECT DRAIN.
- PRIOR TO COMMENCING WORK ON THIS PROJECT, VERIFY DEPTH, SIZE, LOCATION AND CONDITION OF ALL EXISTING UTILITIES IN FIELD. SHOULD CONDITIONS EXIST OTHER THAN THOSE INDICATED WHICH WOULD CAUSE THE DESIGN TO BE ALTERED, CONTRACTOR SHALL NOTIFY OWNER IMMEDIATELY.
- COORDINATE INSTALLATION OF PLUMBING WORK WITH ALL OTHER TRADES SO AS TO AVOID UNNECESSARY DELAY OR INTERFERENCES. CONTRACTOR SHALL REVIEW ARCHITECTURAL AND EQUIPMENT SHEETS.
- FURNISH & INSTALL ALL BACKFLOW PROTECTION DEVICES REQUIRED BY AGENCIES HAVING JURISDICTION. BACKFLOW DEVICES REQUIRING TESTING SHALL BE INSTALLED NO HIGHER THAN 5'-0" A.F.F.
- PROVIDE CONDENSATE DRAIN FROM A/C UNITS TO APPROVED DRAIN. GAS PIPING TO UNITS AND ALL FINAL CONNECTIONS REQUIRED FOR OPERATION.
- THE OWNER OR KITCHEN EQUIPMENT SUPPLIER MAY SUBSTITUTE EQUIPMENT OR THE EQUIPMENT MAY VARY FROM WHAT IS SHOWN. THEREFORE, VERIFY ALL CRITICAL DIMENSIONS WITH THE OWNER PRIOR TO CONSTRUCTION. FAILURE OF THE CONTRACTOR TO VERIFY THESE DIMENSIONS SHALL PLACE THE RESPONSIBILITY FOR ANY SUBSEQUENT RELOCATION DIRECTLY UPON THE CONTRACTOR.
- ALL WATER LINES SHALL BE RUN OVERHEAD U.O.N.
- ALL WATER LINES SHALL BE FLUSHED PRIOR TO CONNECTING ANY FIXTURES OR EQUIPMENT.
- PROVIDE ESCUTCHEON PLATES AND SILICONE SEALANT AT ALL UTILITY PENETRATIONS INTO WALLS, CEILINGS AND FLOORS. DO NOT USE CAULKS OR EXPANDING FOAMS FOR SEALANT.
- CPVC SCHEDULE 40 WASTE PIPE CAN BE SUBSTITUTED FOR BLACK IRON WASTE PIPE WHERE ALLOWED BY LOCAL MUNICIPALITIES.
- PEX PLASTIC TUBING AND FITTING CAN BE USED AS AN OPTION. ALL INSTALLATION SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS AND SHALL COMPLY WITH SECTION 605.10.1 AND SECTION 605.10.2.

GENERAL NOTES

E

ITEM	QTY.	GPH	TOTAL GPH
HAND SINK / LAVATORY	4	5	20
PRE RINSE SINK	1	20	20
3 COMP POT SINK	1	90	90
MOP SINK	1	50	50
TOTAL			180

DEMAND FACTOR = 0.7
TOTAL HW DEMAND = 126 GPH

BTU/HR OUTPUT = TOTAL HW DEMAND x 8.34 x TEMP RISE
= 126 x 8.34 x 80
= 84,067 BTU
BTU/HR INPUT = 84,067 / 0.75
= 112,089 BTU

HOT WATER DEMAND

C

SYMBOLS	ABBREV.	DESCRIPTION
	Y.B.	YARD BOX
	R.D.	ROOF DRAIN
	A.P.	ACCESS PANEL
	V.T.R.	VENT THRU ROOF
	V.B.F.	VENT BELOW FLOOR
	U.T.R.	UP THRU ROOF
	V.C.P.	VITRIFIED CLAY PIPE
	C.I.	CAST IRON
	A.C.P.	ASBESTOS CEMENT PIPE
	(N)	NEW
	(E)	EXISTING
⊕	F.D.	FLOOR DRAIN
⊙	H.D.	HUB DRAIN
⊖	OFD	OVERFLOW DRAIN
⊗	F.S.	FLOOR SINK
	G.L.	GAS LINE
	A.F.F.	ABOVE FINISHED FLOOR
(X-X) [0000]		PLUMBING EQUIPMENT DESIGNATION
(XXX)		KITCHEN EQUIPMENT NUMBER: REFER TO KITCHEN EQUIP. DRAWINGS FOR DESCRIPTION.
— SS —	⊠	SOIL OR WASTE (SANITARY)/ WASTE STUB
— GW —	⊠	SOIL OR WASTE (GREASE WASTE)/WASTE STUB
— G —	G	GAS / GAS STUB
— CW —	CW	COLD WATER / CW STUB
— HW —	HW	HOT WATER / HW STUB
— HWR —	H.W.R.	HOT WATER RETURN
— V —	V.	SANITARY VENT
— SD —	S.D.	STORM DRAIN
— CD —	C.D.	CONDENSATE DRAIN
⊕	F.C.O.	FLOOR CLEANOUT OR CLEANOUT TO GRADE
⊕	W.C.O.	WALL CLEANOUT
— FW —	FW	FILTERED WATER
— TW —	TW	PREMIXED TEMPERATURE WATER
+	H.B.	HOSE BIBB
— S.O.V. —	S.O.V.	SHUT-OFF GATE VALVE
— S.O.C. —	S.O.C.	SHUT-OFF GAS COCK
— C.V. —	C.V.	CHECK VALVE
— P.T.R.V. —	P.T.R.V.	PRESS-TEMPERATURE RELIEF VALVE
— B.V. —	B.V.	BALL VALVE
— C.W. —	C.W.	COLD WATER BELOW GRADE
⊕	E.C.O.	EXTERIOR CLEAN OUT
	BFP	BACK FLOW PREVENTER
	FU	FIXTURE UNIT
— S.O.V. —	S.O.V.	ANSUL SHUT-OFF GATE VALVE
— U —	U	UNION (LINE SIZE)
⊕	P.O.C.	POINT OF CONNECTION

PLUMBING LEGEND

D

FIXTURE	NO.	DRAIN		COLD WATER		HOT WATER	
		D.F.U.	TOTAL D.F.U.	F.U. C.W.	TOTAL C.W.	F.U. H.W.	TOTAL H.W.
WATER CLOSET (FLUSHOMETER TANK)	2	4	8	2	4	--	--
WATER FILTRATION UNIT	1	--	--	1	1	--	--
LAVATORY	2	1	2	1.5	3	1.5	3
HAND SINK	2	2	4	1.5	3	1.5	3
PREP SINK *	1	--	--	2	2	2	2
3 - COMPARTMENT SINK *	1	--	--	3	3	3	3
HOSE BIBB	2	--	--	2.5:1	3.5	--	--
FLOOR DRAIN	7	2	14	--	--	--	--
HUB DRAIN	1	2	2	--	--	--	--
FLOOR SINK	4	6	24	--	--	--	--
MOP SINK	1	3	3	2.25	2.25	2.25	2.25
RETHERMALIZER*	1	-	-	--	--	1.0	1.0
TOTAL	-	-	67	--	20.75	--	14.25

PROBABLE DEMANDS/ AND PIPE SIZING REQUIREMENTS: COLD WATER: 20.75 FU = 20 GPM; DRAIN: GW 43 DFU; SAN 24 DFU; HOT WATER: 14.25 FU = 17 GPM. USE 1-1/2" OW SERVICE; USE 4" SANITARY (MIN); USE 4" SANITARY (MIN); USE 1-1/4" HW SERVICE.

BASED ON 2012 INDIANA PC (COMBINATION DRAIN & VENT). *FIXTURE HAS INDIRECT WASTE TO FLOOR SINK

WATER CALCULATION'S



B

ITEM	FIXTURE	SOIL OR WASTE	VENT	COLD WATER	HOT WATER	TEMPD WATER	WASTE FU	WATER FU	DESCRIPTION	MANUFACTURER / MODEL NUMBER
(ECO) 1	EXTERIOR CLEANOUT	--	--	--	--	--	--	--	CAST IRON CLEANOUT WITH THREADED ADJUSTABLE HOUSING, ROUND SCORIATED HEAVY CAST IRON COVER.	JOSAM / MODEL: 56000 WADE / MODEL: 6000Z ZURN / MODEL: Z-1400
(FS) 1	FLOOR SINK	4"	2"	--	--	--	6	--	LIGHT DUTY, ACID RESISTANCE, WHITE PVC FLOOR SINK W/ 12" SQUIRE WHIT PVC HALF GRATE AND STAINLESS STEEL DEBRIS BUCKET WITH LIFTING HANDLE.	SIOUX CHIEF / MODEL: 861-4PNDW
(FS) 2	FLOOR SINK	4"	2"	--	--	--	6	--	PVC 12" SQUARE FLOOR SINK, 6" DEEP, WITH ALUMINUM DOME STRAINER AND NICKEL BRONZE HINGED TOP.	SIOUX / MODEL: 861-4-PND
(FD) 1	FLOOR DRAIN (3")	3"	2"	--	--	--	2	--	LIGHT DUTY ADJUSTABLE PVC WITH THREADED ADAPTOR AND 5" DIAMETER NICKEL BRONZE RING AND FASTENED GRATE	ZURN / MODEL: FD-2210 SIOUX CHIEF 842 OATEY 72000
(ECO) 1	FLOOR CLEANOUT	--	--	--	--	--	--	--	CAST IRON CLEANOUT WITH THREADED ADJUSTABLE HOUSING, ROUND SCORIATED HEAVY CAST IRON COVER.	JOSAM / MODEL: 56000 WADE / MODEL: 6000Z ZURN / MODEL: Z-1400
(WCO) 1	WALL CLEANOUT	--	--	--	--	--	--	--	CAST IRON CLEANOUT TEE WITH INLET/OUTLET SPIGOT AND THREADED BRASS PLUG, WITH STAINLESS STEEL ACCESS COVER.	JOSAM / MODEL: 58510 WADE / MODEL: 8560E ZURN / MODEL: Z-1446-BP
(HB) 1	HOSE BIBB	--	--	3/4"	--	--	--	2.5/1	NON-FREEZE WALL HYDRANT WITH INTEGRAL VACUUM BREAKER, BRONZE CASING AND NICKEL BRONZE BOX.	JOSAM / MODEL: 71000 WADE / MODEL: 8660L ZURN / MODEL: Z-1300
(WC) 1	WATER CLOSET	4"	2"	1/2"	--	--	4	2	WHITE VITREOUS CHINA FLOOR MOUNTED FLUSHOMETER TANK (PRESSURE ASSISTED) TYPE, ELONGATED BOWL, ADA COMPLIANT, 1.1 GPF, WITH OPEN FRONT SEAT LESS COVER, OLSENITE #95 OR EQUIVALENT. FLUSHOMETER TANK; SLOAN FLUSHMATE OR EQUAL. PROVIDE TANK COVER LOCKS. FLUSH LEVERS SHALL BE RIGHT HAND OR LEFT HAND AS REQUIRED TO CORRESPOND WITH ACCESS FROM WIDE SIDE OF STALL. VERIFY FLUSH SIDE REQUIREMENTS	AM. STD. "CADET" / MODEL: 2467.100 KOHLER "HIGHLINE" / MODEL: K-3519 CRANE "ECONOMISER" / MODEL: 31888
(L) 1	LAVATORY	1-1/4"	1-1/2"	--	--	1/2"	2	1.5	WHITE VITREOUS CHINA, WALL HUNG, WITH CONCEALED ARMS SUPPORT SEE 8/P6.0, 4" CENTERS, WITH INTEGRAL BACKSPASH, ADA ACCESSIBLE, FLAT GRID STRAINER, BRAIDED WATER LINES. FAUCET: FURNISHED BY OWNER-INSTALLED BY GC. ELECTRONIC HANDWASHING FAUCET, SLOAN BATTERY FAUCET, ADA COMPLIANT, 0.5 GPM AERATOR.	A.S. COMRADE / MODEL: 0124.131 CRANE "HARWICH" / MODEL: 1412V SLOAN FAUCETS SF-2350
(S) 1	HAND SINK	1-1/2"	1-1/2"	--	--	1/2"	2	1.5	S-1: STAINLESS STEEL HAND SINK, WALL HUNG, INCLUDES A 6" GOOSENECK STAINLESS FAUCET, W/SINGLE KNEE PEDAL, BRAIDED WATER LINES, AND 0.5 GPM AERATOR	--
(S) 2	MOP SINK	3"	2"	1/2"	1/2"	--	3	3	MOP SINK, AERO - 3MP-2121-6 W/ 48" HIGH S.S LEFT SIDE AND BACK-SPLASH, FURNISHED BY OWNER, INSTALLED BY GC. FAUCET: T&S #B2465, WITH VACUUM BREAKER, FURNISHED BY OWNER, INSTALLED BY GC.	--
(S) 3	3-COMP. SINK	INDIRECT	--	1/2"	1/2"	--	--	3	SINK FAUCET, 0.65 GPM NOZZLE, DRAIN, & GEN IV POWER SOAK STANDARD. GEN III IS AN OPTION FOR FRANCHISES	--
(S) 4	PREP SINK	INDIRECT	--	1/2"	1/2"	--	--	2	SINK, FAUCET, 0.65 GPM NOZZLE, & DRAIN	--
(GI) 1	GREASE INTERCEPTOR	4"	--	--	--	--	--	--	3,000 GALLON INTERCEPTOR, SEE CIVIL DRAWINGS FOR ADDITIONAL INFORMATION	--
(MV) 1	MIXING VALVE	--	--	1/2"	1/2"	--	--	--	THERMOSTATIC, 125 P516, 200V/F BRONZE BODY, STAINLESS STEEL PISTON LINER, CHECK VALVES SIZE PER PIPE CONNECTIONS.	POWERS SERIES LF495 LAWLER SERIES 310 LEONARD SERIES 170
(WH) 1	WATER HEATER	--	--	1-1/4"	1-1/4"	--	--	--	GAS FIRED WATER HEATER, 98.5% THERMAL EFF., 120,000 BTUH INPUT, 60 GAL. STORAGE TANK, 138 GPH @ 100 DEG. RISE REC. RATE, 3" PVC FLUE & AIR INTAKE, ASME RTD TEMP. & PRESS. REL. VALVE, ELECTRONIC IGNITION SYSTEM AND ELECTRONIC CONTROLS. Call 800-477-1953 Option #1 for National Account Price & Service.	AO SMITH / BTH 120 STATE / SUF 100 120 NE
(ET) 1	EXPANSION TANK	--	--	3/4"	--	--	--	--	EXPANSION TANK, STEEL, EXPANSION MEMBRANE 150 PSI, 160" F, 12 GALLON CAPACITY.	WATTS SERIES DET AMTROL SERIES ST WILKINS SERIES WXTP
(BFP) 1	BACKFLOW PREVENTOR	--	--	1-1/2"	--	--	--	--	REDUCED PRESSURE ZONE BACKFLOW PREVENTER, CAST BRONZE CONSTRUCTION WITH QUARTER TURN FULL-PORT BALL VALVES AND BRONZE STRAINER.	WATTS / MODEL: 009M2QTS WILKINS / MODEL: 975XLS FEBCO / MODEL: 860
(SA) 1	SHOCK ARRESTOR	--	--	1/2"	--	--	--	--	STAINLESS STEEL CASING WITH STAINLESS STEEL BELOW, PRECHARGED WITH NITROGEN, SIZED PER PDI-WH201	WADE / SHOKSTOP JOSAM / MODEL: 75000 ZURN / SHOKTROL
(RO) 1	REVERSE OSMOSIS	INDIRECT	--	1/2"	--	--	--	--	REVERSE OSMOSIS FILTER SYSTEM BY OWNER SEE TO DETAIL 9/P6.0	WADE / SHOKSTOP JOSAM / MODEL: 75000 ZURN / SHOKTROL
(HD) 1	HUB DRAIN	3"	2"	--	--	--	2	--	CAST IRON DEEP SEAL P-TRAP WITH FUNNEL, NO-HUB OUTLET AND BRASS GASKETED CLEANOUT PLUG.	JOSAM / MODEL: 88213 WADE / MODEL: 2453EF ZURN / MODEL: Z-1019
(BFP) 2	DOUBLE CHECK VALVE	--	--	VERIFY	--	--	--	--	WATTS REGULATOR MODEL LF7R DOUBLE CHECK VALVE ASSE 1024 PROVIDE WITH SHUT-OFF VALVE	--

*. IF GEN POWER SOAK SINK USED THEN ADD A MIXING VALVE TO SINK ABOVE SUSPENDED CEILING.

PLUMBING SCHEDULE

A



CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD



PLUMBING SCHEDULES AND NOTES

P1.0




REVISION	DATE
△	FEB18
△	
△	
△	
△	

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544



WATER AND GAS PLAN
P3.0



WATER & GAS PLAN 1/4"=1'-0" **A**



- A. WATER DISTRIBUTION PIPING IS SHOWN ABOVE FINISH CEILING. UNDER SLAB DISTRIBUTION ALLOWED AT CONTRACTOR OPTION. COORDINATE ALL DETAILS.
- B. NO ROOF PENETRATIONS PERMITTED WITHIN THE ROOF WATER VALLEYS. REFER TO ROOF PLAN FOR LOCATIONS.
- C. REFER TO SHT P4.0 FOR ROUGH-IN LOCATIONS.
- D. REFER TO SHEET P5.0 FOR WATER AND GAS ISOMETRIC DRAWINGS.
- E. FLUSH ALL WATER SUPPLY LINES OF ALL DEBRIS AND IMPURITIES PRIOR TO CONNECTING TO WATER FILTERS.
- F. PROVIDE REDUCED PRESSURE BACKFLOW TO SERVE CARBONATOR. DRAIN RELIEF TO FLOOR SINK WITH AIR GAP.
- G. PROVIDE A VENTED DOUBLE CHECK VALVE W/ATMOSPHERIC PORT FOR THE WATER LINES SUPPLY LINES TO FOOD SERVICE EQUIPMENT (ASSE -1022.)
- H. EQUIPMENT VENDOR TO FOLLOW MANUFACTURER'S REQUIREMENTS TO INSTALL DOUBLE CHECK VALVE ON EQUIPMENTS WHERE APPLICABLE.

- ① 1-1/4" GAS UP TO RTU-2 WITH DIRT LEG, GAS COCK, UNION.
- ② 1" GAS DOWN TO WATER HEATER WITH GAS COCK, DIRT LEG AND UNION.
- ③ 1/2" TEMPERED AND COLD WATER DOWN IN WALL TO HAND SINK.
- ④ 1.25" HOT AND 1.25" COLD WATER LINES DOWN TO WATER HEATER.
- ⑤ 1/2" HOT AND COLD WATER LINES DOWN IN WALL TO PREP SINK.
- ⑥ 1/2" HOT AND COLD WATER LINES DOWN IN WALL TO THREE COMPARTMENT SINK.
- ⑦ 1/2" COLD WATER 2'-0" A.F.F. CONNECT TO WATER FILTER FOR HOT WATER SYSTEM P-452. PROVIDE SHUT-OFF VALVE PRIOR TO CONNECTION TO THE WATER FILTER.
- ⑧ 1/2" COLD AND HOT WATER DOWN IN THE WALL TO THE MOP SINK.
- ⑨ 1/2" CW DOWN IN WALL TO WATER CLOSET FLUSHOMETER TANK.
- ⑩ REDUCED PRESSURE BACKFLOW PREVENTER PER LOCAL UTILITY REQS. PROVIDE SHUT-OFF VALVES AT BOTH SIDES OF METER, PIPE BFP RELIEF TO FLOOR SINK. VERIFY LOCATIONS WITH CIVIL DWGS.
- ⑪ 1-1/4" GAS UP TO RTU-1 WITH DIRT LEG, GAS COCK, UNION.
- ⑫ 1/2" TEMPERED WATER LINE DOWN IN WALL TO LAVATORY.
- ⑬ 3/4 CW DOWN IN WALL TO WATER FILTER S-286. SEE DETAIL 4/P6.0.
- ⑭ 3/4" CW DOWN IN WALL TO URINAL FLUSH VALVE.
- ⑮ EMERGENCY GAS SHUT-OFF VALVE LOCATED BELOW CEILING.
- ⑯ 3/4" CW DOWN IN WALL TO EXTERIOR HOSE BIBB.
- ⑰ BUNDLED SYRUP LINES TO BEVERAGE DISPENSERS S-284 & S-285 AND FILTERED WATER LINES TO ICE MAKERS S-513 AND FROZEN BEVERAGE DISPENSER S-739. SEE DRAWINGS A2.0 AND P5.0.
- ⑱ 1-1/4" GAS DOWN ALONG WALL TO TACO BELL COOKING EQUIPMENT.
- ⑲ GAS DIRT LEG W/ GAS COCK TO COOKING EQUIPMENT. PROVIDE FLEXIBLE GAS HOSE KIT FOR CONNECTION TO COOKING EQUIPMENT. SEE 5/P5.0 FOR SIZES.
- ⑳ 3" PVC COMBUSTION AIR AND VENT FOR WATER HEATER. SEE M2.0.
- ㉑ 1/2" HOT WATER DOWN IN WALL TO TB RETHERMALIZER. PROVIDE SHUT-OFF VALVE OUTSIDE OF WALL FOR CONNECTION TO RETHERMALIZER.
- ㉒ RUN GAS PIPE 18" A.F.F. WITH DIRT LEGS FOR GAS HOSE KITS TO COOKING EQUIPMENT. HARD GAS LINE BEHIND COOKING EQUIPMENT SHALL NOT BE MORE THAN 6" MAX. FROM THE WALL SURFACE.
- ㉓ 3/4" FILTER WATER LINE DOWN IN UTILITY CHASE OF DRY PRODUCTION LINE. PROVIDE SHUT-OFF VALVE ON FW PIPING IN CEILING NEAR CHASE.
- ㉔ 3/4" COLD WATER TO REVERSE OSMOSIS FILTER P-315 AND 3/4" FILTER WATER FROM REVERSE OSMOSIS FILTER. PROVIDE SHUT-OFF VALVE ON CW PIPE PRIOR TO CONNECTION TO FILTER. SEE DETAIL 9/P6.0.
- ㉕ GAS METER REGULATOR VALVES, BRACKETS, ETC. AS REQUIRED BY LOCAL GAS CO. SEE CIVIL DRAWINGS FOR CONTINUATION.
- ㉖ 1/2" COLD WATER. CONNECT TO WATER FILTER FOR BUNN POD BREWER S-547. PROVIDE SHUT-OFF VALVE PRIOR TO CONNECTION TO THE WATER FILTER.
- ㉗ AVOID ROUTING PIPING THRU ROOF HATCH OPENING. COORDINATE IN FIELD.
- ㉘ INSTALL NEW WATER PIPING ON WARM SIDE OF INSULATION.
- ㉙ PLUMBING CONTRACTOR TO INSTALL WATER METER AND MAIN SHUT-OFF VALVE IN ACCESSIBLE LOCATION.

NOT USED **D**

WATER & GAS PLAN NOTES **C**

KEY NOTES **B**



PLUMBING ROUGH-IN PLAN 1/4"=1'-0" **A**

EQUIP #	EQUIPMENT ITEM	TYPE	ELEVATION	REMARKS	EQUIP #	EQUIPMENT ITEM	TYPE	ELEVATION	REMARKS
(FS 1)	FLOOR SINK		--		(S 3)	3-COMPARTMENT SINK FAUCET	CW/HW	+38" A.F.F.	--
(FD 1)	FLOOR DRAIN		--		(S 4)	PREP SINK	W	+19" A.F.F.	--
(HD 1)	HUB DRAIN		--		(S 4)	PREP SINK FAUCET	CW/HW	+38" A.F.F.	--
(WH 1)	WATER HEATER	CW			(S-513)	ICE MAKER	FW	-	VIA SYRUP BUNDLE
(WH 1)	WATER HEATER	G	+15" A.F.F.		(C-107)	REITHERMALIZER	HW	+8" A.F.F.	
(WC 1)	WATER CLOSET FLUSH VALVE	CW	+29" A.F.F.	BOTH HANDICAP AND REGULAR	(C-107)	REITHERMALIZER	G	+12" A.F.F.	
(UR 1)	URINAL FLUSH VALVE	CW	+47" A.F.F.	WALL MOUNTED	(C-226)	DOUBLE OPEN FRYER	G	+12" A.F.F.	
(UR 1)	URINAL WASTE STUB	W	+16-1/2" A.F.F.	WALL MOUNTED	(S-286)	WATER FILTER SYSTEM	CW	+94" A.F.F.	INLET TO & OUTLET FROM FILTER
(L 1)	LAVATORY	TW	+20" A.F.F.	--	(P-362)	UTILITY CHASE FOR V-LINE	FW	CLG.	STUB AT CLG.
(L 1)	LAVATORY WASTE LINE	W	+16-1/2" A.F.F.	--	(P-452)	FILTER FOR HOT WATER SYSTEM	CW	+24" A.F.F.	
(S 1)	HAND SINK	TW	+18" A.F.F.	RIM OF LAV @ +2'-8" A.F.F.					
(S 2)	MOP SINK	W	-6" A.F.F.	RECESSED IN FLOOR					
(S 2)	MOP SINK FAUCET	CW/HW	+36" A.F.F.	--					
(S 2)	MOP SINK FAUCET	CW/HW	+42" A.F.F.	CLOSET MOP SINK ONLY					
(S 3)	3-COMPARTMENT SINK	W	+19" A.F.F.	--					

PLUMBING ROUGH-IN SCHEDULE **D**

SYMBOL	DESCRIPTION
●	HOT WATER
●	COLD WATER
●	TEMPERED WATER
■	GAS
⊖	FLOOR DRAIN
⊗	FLOOR SINK
○	HUB DRAIN
◆	WASTE OUTLET
○	FLOOR CLEANOUT
○	WALL CLEANOUT
○	FILTERED WATER
◇	VENT UP FROM UNDER SLAB
○	WATER LINE THRU FLOOR.

SYMBOL LEGEND **C**

- ALL DIMENSIONS TO FLOOR SINKS, FLOOR DRAINS AND HUB DRAINS ARE TO CENTER OF FIXTURE.
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE THIS DATA ON THE LOCATION OF ALL PLUMBING ROUGH-INS WITH INFORMATION PROVIDED ON THE ARCHITECTURAL AND STRUCTURAL DRAWINGS AND THE EQUIPMENT ACTUALLY SUPPLIED AND TO CONFIRM THE CORRECTNESS OF ANY DIMENSIONS INDICATED HEREIN.


PLUMBING ROUGH-IN NOTES **B**

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD


TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544

TACO BELL
EXPLORER LITE
 MEDIUM40


PLUMBING ROUGH-IN PLAN
P4.0




TEMPERING VALVE N.T.S. 17




RTU CONDENSATE N.T.S. 13




REVERSE OSMOSIS SYSTEM N.T.S. 9




WATER FILTRATION SCHEMATIC N.T.S. 6



WATER HEATER N.T.S. 2



DRINK SYSTEM SCHEMATIC N.T.S. 11



DRINK SYSTEM SCHEMATIC DETAIL N.T.S. 16

- GENERAL NOTES:**
- OVERALL FILTER DIMENSIONS: 21" WIDE x 12" DEEP x 48 1/2" HIGH
 - SEE DETAIL SCOPE OF WORK FOR SCOPE DEFINITIONS.
 - ROUGH-INS SHALL BE PROVIDED BY THE CONTRACTOR.
 - INSTALLATION MUST COMPLY WITH ANY STATE OR LOCAL PLUMBING CODES.
 - THE FILTER MUST BE PROTECTED AGAINST FREEZING.
 - USE ONLY TEFLON (HIGH-LOW TEMPERATURE) TAPE TO SEAL THREADED PARTS; NO PIPE DOPE.
 - DO NOT INSTALL WHERE LINE PRESSURE EXCEEDS 125 PSI OR WHERE TEMPERATURE EXCEEDS 100 F.
 - SEE THE EQUIPMENT PLAN FOR LOCATION.
 - SEE DETAIL 12 THIS SHEET FOR BUNDLE DETAILS.
 - ** FOR ICE MACHINES SUPPLY LINES SHALL BE INSTALLED @ FILTER OUTLET.
 - BACKFLOW PREVENTERS FOR FILTER ASSEMBLY ARE PROVIDED.

THERE ARE TWO SELF-SERVE DRINK/ICE SYSTEMS WHICH SHARE A COMMON FLOOR SINK WITH THE D/T DRINK/ICE SYSTEM.

NOTE INSTALL ELECTRICAL, WATER, AND DRAIN IN ACCORDANCE WITH ALL LOCAL, STATE & FEDERAL CODES.

EQUIPMENT RATING:
 ED250 DISPENSER - 115V, 3.5 AMPS
 ED300 DISPENSER - 115V, 4.0 AMPS
 CARBONATOR - 115V, 60 Hz, 7.0 AMPS
 BOOSTER ASSEMBLY - 115V, 60 Hz, 6.5 AMPS


LEGEND

KITCHEN EQUIPMENT # (SHEET A2.0)	FLOW ARROW
SYSTEM	POINT OF CONNECTION (PEPSI)
	POINT OF CONNECTION (GC)


QTY	MODEL #	DESCRIPTION
1	SEE SHEET P1.0	HIGH EFFICIENCY COMMERCIAL WATER HEATER
1	MFK7	MANIFOLD KIT *
1	DET12	EXPANSION TANK
1	HAL	ALARM LIGHT W/ INSTALLATION INSTRUCTIONS
1	PK100	STAND

* THE FOLLOWING ARE INCLUDED IN THE MANIFOLD KIT:

QTY	DESCRIPTION	QTY	DESCRIPTION
1	3/4" BLK GAS COCK	1	3" PVC 90°
1	3/4" BLK UNION	1	1/2" PVC STREET 90°
1	3/4" BLK TEE	1	1/2" PVC 90° ELBOW
3	3/4" x 2 1/2" BLK NIPPLE		
1	3/4" x 4 BLK NIPPLE		
2	3/4" THD BALL VALVE		
1	1 1/2" FX UNION		
1	1 1/2" CXC 90		
1	1 1/2" CXC TEE		
1	1 1/2" BALL VALVES CXC		
1	1 1/2" CHECK VALVES CXC		
1	1 1/2" GALV ST 90		
1	1 1/2" CX ST 90		
1	HPT-507 1/2" P-TRAP		
1	1/2" P4 S/M		
1	1 1/2" x 1 1/2" x 1/2" TEE COPPER		
1	DIAL THERMOMETER		
1	1/2" COPPER FEMALE FITTING ADAPTER		




LAVATORY SUPPORT N.T.S. 8



DRINK MACH. BUNDLE CONFIG. N.T.S. 12

- LEGEND**
- FLUE THRU ROOF - SEE DETAIL 12/A6.0
 - WATER HEATER PLATFORM PROVIDED BY W.H. MANUFACTURER.
 - FINISHED FLOOR
 - THERMAL EXPANSION TANK BY WATTS - SEE PLUMBING SCHEDULE - STRAP AND SUPPORT TO WALL
 - SCHEDULE 40 PVC, MINIMIZE TURNS AND TRANSITIONS.
 - GAS COCK VALVE WITH FULL SIZE DIRT LEG
 - 3/4" DRAIN WITH VALVE & CAP
 - COMBINATION TEMPERATURE AND PRESSURE RELIEF PER LOCAL CODE
 - RUN T&P DISCHARGE FULL SIZE TO HUB DRAIN
 - 22" DEEP HEAT TRAP
 - AIR INTAKE W/ INTERNAL INSECT SCREEN PROVIDED BY MFR.
 - SUPPORT VENT PIPE RUNS EVERY 5'-0" VERTICALLY AND EVERY 3'-0" HORIZONTALLY.
 - OUTLET THERMOMETER PROVIDED BY MFR. LOCATE WITHIN 12" OF W.H. OUTLET.
 - SEE DETAIL 7/P6.0 FOR SCHEDULE OF ITEMS PROVIDED BY W.H. MFR.
 - DRAIN PAN TO HUB DRAIN.
 - P-TRAP AND LINE TO DRAIN PROVIDED BY MANUFACTURER. LEAVE AIR GAP BETWEEN BOTTOM OF TRAP AND DRAIN. SEE DETAIL E/P2.0.



- KEY NOTES:**
- 3/4" COLD WATER INLET TO 1/2" COPPER LINE AND FITTINGS AT FILTER.
 - 3/4" OUTLET W/ INTEGRAL BACKFLOW PREVENTER, EQUAL TO WATTS REGULATOR CO. SERIES 007 AND SERVICE BALL VALVE.
- GENERAL NOTES:**
- OVERALL DIMENSIONS 21" WIDE x 12" DEEP x 48 1/2" HIGH
 - SEE SCOPE OF WORK FOR ADDITIONAL INFORMATION.
 - INSTALLATION MUST COMPLY WITH STATE OR LOCAL PLUMBING CODES.
 - THE UNIT MUST BE PROTECTED AGAINST FREEZING.
 - USE ONLY TEFLON (HIGH-LOW TEMPERATURE) TAPE TO SEAL THREADED PARTS; NO PIPE DOPE.
 - DO NOT INSTALL WHERE LINE PRESSURE EXCEEDS 125 PSI OR WHERE TEMPERATURE EXCEEDS 100 F.
 - SEE SHT. A2.0 FOR LOCATION.

WATER FILTER SYSTEM N.T.S. 4

ARCVISION
 INCORPORATED
 ARCHITECTURE ENGINEERING STORE PLANNING
 SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
 1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63116
 PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com



REVISION	DATE
△	FEB18
△	
△	
△	
△	

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544

EXPLORER LITE
 MEDIUM40

PLUMBING DETAILS
P6.0
 6/29/20

NATIONAL ACCOUNTS: SWITCHGEAR
SUPPLY and INSTALL STANDARD PACKAGE

CORPORATE AND FRANCHISE DEVELOPMENT

YUM NATIONAL ACCOUNT AGREEMENT IS WITH SQUARE-D FOR ELECTRICAL SWITCHGEAR EQUIPMENT FOR COMPANY AND FRANCHISE DEVELOPMENT. CUTLER-HAMMER ELECTRICAL SWITCHGEAR EQUIPMENT IS AN APPROVED ALTERNATE MANUFACTURER FOR FRANCHISE DEVELOPMENT ONLY.


UNDER THIS AGREEMENT, THE CONTRACTOR IS RESPONSIBLE FOR PURCHASE AND INSTALLATION OF THE SYSTEMS DESCRIBED IN THE PLANS. ALL COMPANY AND FRANCHISE PROJECTS SHALL CONTACT ACCUSERV FOR A PRICE QUOTE AND A BILL OF MATERIAL CONFIRMATION FOR THEIR SPECIFIC PROJECT. SEE THE SWITCHGEAR SECTION IN THE SCOPE OF WORK FOR ADDITIONAL INFORMATION.

PRIMARY CONTACT: BUDDY BOCKWEG
PHONE: (877) 707-7378
FAX: (502) 961-0357
EMAIL: buddy@accuserv.com

THE SWITCHGEAR PACKAGE CONSISTS OF SERVICE ENTRANCE, SWITCHGEAR, MAIN PANELS, SUB PANELS, LIGHTING CONTACTORS AND ALL ASSOCIATED PRODUCTS TO COMPLIMENT THE SWITCHGEAR PACKAGE.

BE PREPARED AT TIME OF ORDER OR QUOTE REQUEST TO PROVIDE ALL PROJECT DETAILS REGARDING SPECIFICATIONS AND QUANTITIES AS SITE SPECIFIC DESIGN MAY NOT MATCH PROTOTYPICAL DESIGN.

NOTE: THE SITE-ADAPT CONSULTANT IS RESPONSIBLE FOR DETERMINING IF THE SITE-SPECIFIC SWITCHGEAR PACKAGE FALLS WITHIN A JURISDICTION THAT REQUIRES EUSERC-COMPLIANT METERING EQUIPMENT.




NOTE: CONFIRM DIMENSIONS WITH SUPPLIER

SERVICE ENTRANCE EQUIPMENT ELEVATION - NON-EUSERC PACKAGE E

	2X4 LIGHT FIXTURE		NIGHT LIGHT		CONNECTION TO EQUIPMENT
	2X4 LIGHT FIXTURE WITH BATTERY PACK		CEILING MOUNTED SPEAKER		BRANCH CIRCUIT HOMERUN TO PANEL
	1X4 LIGHT FIXTURE		WALL MOUNTED SPEAKER		DISCONNECT SWITCH SEE NOTE FOR TYPE
	1X4 LIGHT FIXTURE WITH BATTERY PACK		JUNCTION BOX		PHOTOCELL
	DOWNLIGHT FIXTURE		WALL MOUNTED JUNCTION BOX		RAIN SENSOR
	SUSPENDED DOWNLIGHT FIXTURE		TELEPHONE OUTLET		WALL MOUNT LIGHT FIXTURE
	PENDANT MOUNTED LIGHT FIXTURE		DEDICATED GROUNDED OUTLET		EMERGENCY LIGHT
	TRACK MOUNTED PENDANT LIGHT FIXTURE		DOUBLE DUPLEX GROUNDED OUTLET		SINGLE POLE, SINGLE THROW TOGGLE SWITCH
	DIRECTIONAL FIXTURE, TRACK MOUNTED		GROUND FAULT DUPLEX OUTLET		SINGLE POLE, SINGLE THROW TOGGLE SWITCH W/ PILOT LIGHT
	DIRECTIONAL FIXTURE, TRACK MOUNTED TO UNDERSIDE OF INTERIOR CANOPY		FLUSH MOUNTED CEILING GROUND FAULT DUPLEX OUTLET		DIMMER SWITCH WITH SEPARATE MANUAL ON/OFF
	COOLER FIXTURE		GROUND FAULT DUPLEX W/ BOTTOM, HALF SWITCHED		RELAY
	EXIT SIGN (WALL MOUNTED)		CEILING DUPLEX OUTLET		CONDUIT RUN, UNDERGROUND
	EXIT SIGN (CEILING MOUNTED)		FLUSH MOUNTED CEILING GROUND FAULT DUPLEX OUTLET		SMOKE DETECTOR
	SECURITY STROBE		DOUBLE DUPLEX GROUNDED OUTLET		EXTERIOR WALL FIXTURE
			SINGLE ISOLATED GROUND		EXTERIOR DECORATIVE WALL FIXTURE
			SPECIAL PURPOSE OUTLET		WEATHERPROOF GROUND FAULT
			CEILING SPECIAL PURPOSE OUTLET		
			ELECTRICAL PANEL SEE SHEET E2.1 FOR PANEL SCHEDULE.		
			HOLD UP EMERGENCY BUTTON		
			ELECTRICAL MOTOR		
			DUCT MOUNTED SMOKE DETECTOR		

ELECTRICAL LEGEND D



FIRE ALARM NOTE

AS REQUIRED, IT SHALL BE THE GENERAL CONTRACTORS RESPONSIBILITY TO ENGAGE THE SERVICES OF AN APPROVED FIRE ALARM CONTRACTOR. THE FIRE ALARM CONTRACTOR SHALL BE REQUIRED TO PROVIDE DRAWINGS, SPECIFICATIONS & INSTALLATION ACCORDING TO MUNICIPALITIES GUIDELINES. FIRE ALARM SERVICE MAY ALSO INCLUDE PROVIDING FIRE ALARM MONITORING TO BUILDINGS INSTALLED FIRE ALARM CONTROL SYSTEM. FIRE ALARM CONTRACTOR TO PROVIDE COMPATIBLE DEVICES & ALL BRACING, WIRING, ETC. COORDINATE WITH SPRINKLER CONTRACTOR FOR DETAILS.

SINGLE LINE DIAGRAM A


- INSTALLED TENANT SWITCHBOARD A.I.C. RATINGS SHALL EXCEED THAT OF THE CALCULATED FAULT-CURRENT PROVIDED BY THE SERVING UTILITY COMPANY. ALL BRANCH DEVICES CONNECTED DOWNSTREAM OF MSB SHALL BE U.L. LISTED AND APPROVED TO SERIES RATE WITH ALL COMPONENTS OF THIS ELECTRICAL SYSTEM
- SEE SCOPE OF WORK FOR DETAILS REGARDING OWNER SUPPLIED AND/OR INSTALLED PRODUCTS. CONTRACTOR IS RESPONSIBLE FOR ALL OTHER ASPECTS OF THE PROJECT.
- IF UTILITY COMPANY PROPOSES A SERVICE DIFFERENT FROM THAT ILLUSTRATED, CONTACT THE CONSTRUCTION ENGINEER FOR A DECISION BEFORE PROCEEDING. COORDINATE AVAILABLE SHORT CIRCUIT CURRENT W/ LOCAL UTILITY AND PROVIDE CIRCUIT BREAKERS W/ SUFFICIENT INTERRUPTING CAPACITY.
- ALL WIRING SHOWN AS COPPER TYPE "THH/THWN" FEEDERS FROM UTILITY TRANSFORMER TO MSB AND TO INTERIOR PANELS MAY BE ALUMINUM IF ALLOWED BY AH-J. ADJUST FEEDER SIZES AS NECESSARY.
- ARMOR CABLE ACCEPTABLE FOR ALL APPLICATIONS WHERE ALLOWED BY LOCAL CODES AS DELINEATED BY N.E.C. 330.10. ALL CONDUIT MUST BE CONCEALED U.N.O.
- PROVIDE SERVICE EQUIPMENT LABELS PER N.E.C. 110.24(A), (B), 110.16.
- ALL CONTRACTORS PRIOR TO BID SUBMISSION PROCESS SHALL VISIT PROPOSED WORK SITE AND FIELD VERIFY ALL EXISTING CONDITIONS. ANY CONDITION THAT DIFFERES FROM THAT SHOWN ON THESE PLANS SHALL BE REPORTED TO THE TENANTS ARCHITECT/ENGINEER SO THAT NEW AND REVISED BID DRAWINGS OR INFORMATION MAY BE ISSUED. MODIFICATIONS TO THE SCOPE OF WORK WHICH RESULTS FROM THE CONTRACTORS NEGLIGENCE TO VISIT THE SITE PRIOR TO SUBMITTING BID, SHALL BE THE CONTRACTORS SOLE RESPONSIBILITY.
- REFER TO SHEET E2.1 FOR PANEL SCHEDULES.

GENERAL NOTES C

- WIRE ISOLATED GROUND TO ISOLATION GROUND BUS IN PANEL AND LAND ISOLATED GROUND TO SINGLE POINT GROUND. DO NOT COMBINE COMMON GROUND TO ISOLATED GROUND.
- 6 BUILDING MAIN DISCONNECT FOR THIS SERVICE: MAXIMUM 6 MAINS PER N.E.C. ARTICLE: SERVICES 230.71 (SEE PANEL SCHEDULE, E2.1 FOR RATINGS) LABEL EACH MAIN BREAKER AS INDICATED: (ENGRAVED LETTERS X 3/4" HIGH) 'PANEL A' 'PANEL B' 'PANEL D' 'PANEL EVO-LINE' 'SPACE' 'SPACE'
- EQUIPMENT CABINET IS FURNISHED WITH EVO LINE.
- PROVIDE 2" CONDUIT STUBBED INTO BUILDING FROM LATERAL POLE OR PEDESTAL FOR TELEPHONE.
- VERIFY AVAILABLE FAULT CURRENT AT SERVICE ENTRANCE WITH THE UTILITY CO. AND CONFIRM 65 KAIC RATED EQUIPMENT IS SUFFICIENT.
- (3) 5/8" DIAMETER, X 10'-0" COPPER CLAD GROUND RODS. INSTALL 10'-0" APART AND CONNECT GROUND SYSTEM PER N.E.C. ARTICLE 250.
- ESTABLISH NEW ACCOUNT ON BEHALF OF CLIENT. INSTALL UNDERGROUND SERVICE LATERAL TO UTILITY TRANSFORMER PER SERVING UTILITY COMPANY SPECIFICATIONS. 4#350KCMIL (CU) IN EACH OF (2) 3". TO PAD MOUNT TRANSFORMER. GENERAL/ELECTRICAL CONTRACTOR SHALL COORDINATE SERVICE EQUIPMENT PER LOCAL UTILITY CODE.

KEY NOTES B

ARCVISION
INCORPORATED
ARCHITECTURE ENGINEERING STORE PLANNING
SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com



△	OWN/STATE COMMENTS 08.10.20
△	
△	
△	
△	

CONTRACT DATE:	8/26/19
BUILDING TYPE:	EXP. LITE MED40
PLAN VERSION:	MARCH 2018
BRAND DESIGNER:	DAN DICKSON
SITE NUMBER:	314007
STORE NUMBER:	TBD



RISER DIAGRAM AND LEGEND E2.0

COMMERCIAL KITCHEN EQUIPMENT SCHEDULE																											
EQUIPMENT IDENTIFICATION			EQUIPMENT ELECTRICAL CHARACTERISTICS								EQUIPMENT CIRCUIT							EQUIPMENT DISCONNECT									
TAG	TYPE	EQUIPMENT NAME	PHASE	WIRES W/GND	VOLTS	MAX HP	FLA / RLA	KW	MCA	TIME-DELAY FUSE	INVERSE-TIME BREAKER	SETS	BRANCH CIRCUIT	WIRE TYPE	CONDUIT TYPE	TYPE	SIZE	NEMA	EQUIPMT	REMOTE	PANEL BOARD	SUPPLIED BY	INSTALLED BY	NOTES			
B-223	O	WATER HEATER IGNITION	1	3	120		4	0.48	4	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	MCCB	20						EC	EC	8		
B-381	O	CO2 CARBON DIOXIDE SENSOR/WARNING	1	3	120		0.3	0.04	0.3	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
C-079	KR	DUAL FRYER W/ UNDER FRYER FILTER SYSTEM	1	3	120		8	0.96	8	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
C-107	O	REETHERMALIZER	1	3	115		2	0.23	2.5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
C-197	KR	SPLIT LID CLAM SHELL TOASTER	1	3	120		15.8	1.896	20	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
C-254	KR	CHEESE MELTER (SINGLE)	1	3	208		16	3.3	20	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	6-20					ES	ES	2		
C-400	O	COOK TIMER	1	3	120		3.5	0.42	4.4	15	15	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	15	5-15					ES	ES	2		
E-107	O	STRAVTOVENT 6'-3" EXHAUST HOOD	1	3	120		9.8	1.18	12.3	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	-	20	5-20					ES	ES	8		
E-272	O	HOOD FIRE SUPPRESSION SYSTEM	1	3	120		6.3	0.76	7.9	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	-	20	5-20					ES	ES	8		
F-040	O	OFFICE COMPUTER	1	3	120		2.5	0.3	3.1	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
F-050	O	ALTERNATE PAYMENT ROUTER BOX	1	3	120																						
F-060	O	MONITOR-OFFICE	1	3	120																						
F-080	O	OFFICE PRINTER/COPIER/FAX/SCANNER	1	3	120		2	0.24	2.5	15	15	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	15	5-15					ES	ES	2		
F-090	O	UPS (UN-INTERRUPTABLE POWER SUPPLY)	1	3	120		4	0.48	5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
F-102	O	MONEY COUNTER	1	3	120																						
F-131	O	MUSIC SYSTEM (MUZAK)	1	3	120		4.2	0.5	5.3	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	8		
F-174	O	SAFE WITH TOUCH SCREEN CONTROLS	1	3	120		3	0.36	3.8	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
L-043	O	INTERIOR MENU BOARD PACKAGE	1	3	120		9	1.08	11.3	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
N-043	O	3-COMP POWER SOAK 102" L x 31"D (R TO L)	1	3	208		11.4	2.372	14.25	15	15	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	15	6-15					ES	ES	2		
P-362B	KR	DUAL LINE, 157" READY TO ACCEPT EVO CABINETS	3	4	208			45		200	200	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	MCCB	200	-									
P-417	O	8-CHANNEL TIMER	1	3	120		0.5	0.06	0.625	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	-	20	5-20									
P-452	KR	HOT WATER DISPENSER	1	3	208		19.5	4.08	24.4	30	30	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	30	6-30					ES	ES	2		
R-209	KM	FULL HT FREEZER	1	3	115		7.2	0.828	9	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-15					ES	ES	2		
S-023	KM	WARMER, EVO TACO TOWER, TB, 208V, L TO R UNIT	1	3	208		24	2.496																			
S-024	KM	WARMER, EVO TACO TOWER, TB, 208V, R TO L UNIT	1	3	208		24	2.496																			
S-026	KR	HEATED CABINET-FULL HEIGHT (RH)	1	3	120		16	1.92	20	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
S-027	KR	HEATED CABINET-FULL HEIGHT (LH)	1	3	120		16	1.92	20	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-15					ES	ES	2		
S-065	KR	DESSERT TOWER	1	3	120		6.8	0.82		20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-15					ES	ES	2		
S-204	O	DT/TIMING SYSTEM	1	3	120		7.2	0.86	9	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
S-284	KM	BEVERAGE DISPENSER - SELF SERVE	1	3	120		9.3	1.116	11.6	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
S-285	KM	BEVERAGE DISPENSER - DRIVE THRU	1	3	120		10.8	1.296	12.8	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
S-286	O	WATER FILTER SYSTEM	1	3	120		2	0.24	2.5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	-	20	5-20					ES	ES	2		
S-489	KR	DIGITAL SCALE																									
S-513-1	KM	ICE MAKER S/S & DT (2)	1	3	120		2.3	0.26	2.9	15	15	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	15	5-15					ES	ES	2		
S-513-2	KM	ICE MAKER CONDENSER	1	3	208		13.2	2.61	16.5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	F	20	5-20					ES	ES	5,8		
S-204	O	ORDER CONFIRMATION BOARD/SWITCHBOX	1	3	120		1.1	0.13	1.4	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
S-540	KM	PEPSI BOOSTER TANK/CO2 MONITOR	1	3	120		4.7	0.54	5.9	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
S-546	O	ICED TEA BREWER	1	3	120		14.8	1.78	18.5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
S-547	O	BUNN POD BREWER	1	3	120		11.9	1.43	14.9	15	15	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	15	5-15					ES	ES	2		
S-739	KM	FROZEN BEVERAGE DISPENSER, REMOTE	1	3	208		24	5	30	30	30	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	30	6-30					ES	ES	2		
S-740	KM	FROZEN BEVERAGE CONDENSER, REMOTE	1	3	208		12	2.5	15	15	15	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	F	15	-					ES	ES	5,8		
U-011	O	BASE STATION - D/T COMMUNICATION SYSTEM	1	3	120		2	0.24	2	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
F-504	O	CCTV DVR & MONITOR	1	3	120		5	0.6	5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	15	5-15					ES	ES	2		
U-061	O	CREDIT CARD READER (VSTAT)	1	3	120		2	0.24	2.5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
U-063	O	SECURITY SYSTEM	1	3	120		2.5	0.3	2.5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
U-070	O	RECEIPT PRINTER	1	3	120		2	0.24	2	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
U-100	O	POS/ORDER ENTRY	1	3	120		3	0.36	3	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20										
U-238	O	KITCHEN MONITOR	1	3	120		5	0.6	5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	C&P	20	5-20					ES	ES	2		
W-059-1	KM	WALK-IN COOLER	3	4	208		14.2	4.86	17.8	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	-	20	15-20					ES	ES	8		
W-059-2	KM	WALK-IN FREEZER	3	4	208		11.6	3.96	14.5	20	20	1	SEE PANEL SCHEDULES, SHEET E2.1	CU	ST	-	30	15-20					ES	ES	8		

TYPE: H-HEATING, C-COOLING, R-KITCHEN RESISTIVE, KM-KITCHEN MOTOR, WH-WATER HEATER, OM-OTHER MOTORS, O-OTHER DISCONNECT TYPE: HP-HP RATED SWITCH, C&P-CORD & PLUG, LC & P-LOCKING CORD & PLUG, F-FUSED, NF-NON-FUSED, MCCB-MOLDED CASE CIRCUIT BREAKER. SUPPLIED/INSTALLED BY: EC-ELECTRICAL CONTRACTOR, HC-HVAC CONTRACTOR, PC-PLUMBING CONTRACTOR, ES-EQUIPMENT SUPPLIER

- NOTES:
- REQUIRES SHUNT TRIP PROTECTION
 - CORD & PLUG SUPPLIED AND INSTALLED BY ES. EC SHALL PROVIDE RECEPTACLE.
 - CORD & PLUG SUPPLIED AND INSTALLED BY ES. RECEPTACLE SUPPLIED BY ES AND INSTALLED BY EC.
 - CORD, PLUG, & RECEPTACLE SUPPLIED AND INSTALLED BY EC.
 - SINGLE PHASE, THREE WIRE EQUIPMENT. PROVIDE PHASE CONDUCTORS AND GROUND.
 - THREE PHASE, FOUR WIRE EQUIPMENT. PROVIDE NEUTRAL CONDUCTOR AND GROUND.
 - OUTLETS SUPPLIED AND INSTALLED BY ES. CONDUIT & WIRING PROVIDED BY EC.
 - HARD WIRED CONNECTION BY E.C.

KITCHEN EQUIPMENT SCHEDULE

B

BRANCH CIRCUIT WIRING SCHEDULE									
TO BE USED FOR BRANCH CIRCUIT WIRING UNLESS NOTED OTHERWISE									
OC RATING	POLES	CONDUCTOR AND CONDUIT SIZE						GROUND	CONDUIT
		HOT		NEUTRAL		GROUND			
		NO.	AWG	NO.	AWG	AWG			
15A	1	1	12	1	12	12		3/4"	
	2	2	12	-	-	12		3/4"	
	3	3	12	-	-	12		3/4"	
20A	1	1	12	1	12	12		3/4"	
	2	2	12	-	-	12		3/4"	
	3	3	12	-	-	12		3/4"	
25A	1	1	10	1	10	10		3/4"	
	2	2	10	-	-	10		3/4"	
	3	3	10	-	-	10		3/4"	
30A	1	1	10	1	8	10		3/4"	
	2	2	10	-	-	10		3/4"	
	3	3	10	-	-	10		3/4"	
35A	1	1	8	1	8	10		3/4"	
	2	2	8	-	-	10		3/4"	
	3	3	8	-	-	10		3/4"	
40A	1	1	8	1	8	10		3/4"	
	2	2	8	-	-	10		3/4"	
	3	3	8	-	-	10		3/4"	
45A	1	1	8	1	8	10		3/4"	
	2	2	8	-	-	10		3/4"	
	3	3	8	-	-	10		3/4"	
50A	1	1	6	1	6	10		1"	
	2	2	6	-	-	10		1"	
	3	3	6	-	-	10		1"	

NOTES:
1. THE ABOVE SCHEDULE IS BASED ON COPPER, 75 DEGREE CONDUCTORS

BRANCH CIRCUIT WIRING SCHEDULE

A

VOLTAGE DROP SCHEDULE							
120V BRANCH CIRCUITS: MAXIMUM CIRCUIT LENGTH; 3% MAX VOLTAGE DROP							
BRANCH CIRCUIT WATTAGE	WIRE GAUGE						
	#12	#10	#8	#6	#4	#3	
3840	N/A	N/A	69	110	174	220	
3500	N/A	N/A	76	120	191	242	
3250	N/A	N/A	82	130	206	--	
3000	N/A	N/A	88	140	223	--	
2880	N/A	58	92	146	233	--	
2500	N/A	66	106	169	268	--	
2250	N/A	74	118	187	298	--	
1920	54						

THE DEDICATED POS POWER CIRCUIT REQUIRES AN ISOLATED GROUND IN ADDITION TO THE NORMAL COMMON BUILDING GROUND. THE ISOLATED GROUND WIRE SERVES TWO PURPOSES:

- * AS A SAFETY PATH TO GROUND.
- * AS A ZERO REFERENCE POINT FOR ALL POS DIGITAL LOGIC.


THE GROUND MUST EXHIBIT THE LOWEST POSSIBLE IMPEDANCE TO MINIMIZE VOLTAGE TRANSIENTS AND NOISE.

BE SURE TO:

- * USE AN INSULATED CONDUCTOR FOR THE ISOLATED GROUND WIRE.
- * RUN THE ISOLATED GROUND WIRE THROUGH THE SAME CONDUIT AS THE HOT AND NEUTRAL WIRES.
- * INSTALL ONLY ISOLATED GROUND (IG) TYPE RECEPTACLES.
- * CONNECT THE ISOLATED GROUND WIRE TO BUILDING GROUND ONLY AT THE MAIN SERVICE PANEL.
- * VERIFY THAT IG RECEPTACLES PRE-WIRED IN OWNER SUPPLIED EQUIPMENT HAVE A TRUE ISOLATED GROUND THAT CAN BE TRACED BACK TO THE BUILDING GROUND AT THE MAIN SERVICE PANEL/SWITCH.


DO NOT CONNECT THE ISOLATED GROUND WIRE TO THE CONDUIT, JUNCTION BOXES, THE FRAME ON A SUBPANEL, OR ANY OTHER METAL SURFACE.

DEDICATED CIRCUITS: DEDICATED CIRCUITS REQUIRE A DEDICATED HOT AND A DEDICATED NEUTRAL THAT ARE NOT SHARED WITH ANY OTHER CIRCUITS. IG RECEPTACLES MUST BE "PHASE ALIGNED" WITH THE "B" PHASE OF SUBPANEL IN WHICH IT IS INSTALLED.




NOTE: USE GFCI BRANCH CIRCUIT BREAKERS FOR ISOLATED GROUND OUTLET CIRCUITS.


P.O.S. ISOLATED GROUND SYSTEM N.T.S. **F**



SECURITY BUTTON ON WALL N.T.S. **C**




SECURITY BUTTON UNDER COUNTER N.T.S. **D**



REFER TO COMMUNICATIONS SCHEDULE ON SHEET E5.0 FOR EQUIPMENT DESCRIPTION/MOUNTING HEIGHTS.

ENLARGED POWER AND COMMUNICATIONS PLAN (OFFICE) 1/2" = 1'-0" **B**




REFER TO COMMUNICATIONS SCHEDULE ON SHEET E5.0 FOR EQUIPMENT DESCRIPTIONS/MOUNTING HEIGHTS.

DRIVE-THRU ELEVATION COMPONENT RELATION DETAIL 1/2" = 1'-0" **G**

NOT USED N.T.S. **E**

KEY NOTES N.T.S. **A**

1. THERMOSTAT CONTROLS. COORDINATE WITH MECHANICAL SHEETS.
2. CONTROLLED RECEPTACLE (TBCCB OPTION). CIRCUIT THROUGH TBCCB CONTROL BOX (INSTALLED IN THE OFFICE) AND CONTROLLED VIA OCCUPANCY/VACANCY SENSOR, BUILT INTO FRONT OF THE CONTROL BOX. SEE E6X SERIES SHEETS FOR ADDITIONAL INFORMATION. RECEPTACLE SHALL BE PERMANENTLY MARKED, U.L. LISTED AND PROVIDE INDICATION OF CONTROLLED RECEPTACLE, FOR EACH REQUIRED RECEPTACLE.
3. NOT USED.
4. PHONE JACK FOR MODEM.
5. LOCATION OF TACO BELL COMBINED CONTROL BOX - TBCCB. CONTRACTOR TO VERIFY (IN THE FIELD). CONSIDER OPERATOR NEED TO ACCESS SWITCHES ON THE FRONT OF THE CONTROL BOX AND BUILT-IN OCCUPANCY SENSOR FOR MANAGER'S OFFICE.
6. DATA JACK FOR TECH-IN-A-BOX WITH 2 PORTS.



NO.	OWN/STATE COMMENTS	DATE
1	OWN/STATE COMMENTS	08.10.20

CONTRACT DATE: 8/26/19
BUILDING TYPE: EXP. LITE MED40
PLAN VERSION: MARCH 2018
BRAND DESIGNER: DAN DICKSON
SITE NUMBER: 314007
STORE NUMBER: TBD

TACO BELL
3615 BREMEN HWY
MISHAWAKA, IN 46544



TACO BELL
EXPLORER LITE
MEDIUM40

ENLARGED POWER PLAN AND DETAILS

E3.1

GENERAL NOTES

- A. CONFIRM LIGHTING FIXTURE QUANTITIES WITH SUPPLIER. ALL FIXTURES SUPPLIED WITH LAMPS.
- B. EMERGENCY AND NORMAL LIGHTING MARKED WITH "NL" SUBSCRIPT SHALL OPERATE CONTINUOUSLY. EMERGENCY LIGHTING NOT MARKED WITH "NL" SUBSCRIPT SHALL OPERATE UNDER CONTROL OF LIGHTING SWITCH AS INDICATED. PROVIDE UNSWITCHED CONSTANT HOT TO EMERGENCY BALLAST AND EMERGENCY LIGHTING NOT MARKED WITH "NL" SUBSCRIPT SHALL OPERATE UNDER CONTROL OF LIGHTING SWITCH AS INDICATED. PROVIDE UNSWITCHED CONSTANT HOT TO EMERGENCY BALLAST AND SWITCHED HOT TO NORMAL BALLAST.
- C. ALL CONDUITS ENTERING OR LEAVING COOLER/FREEZER SHALL BE PROVIDED WITH SEAL-OFF FITTING WITH COMPOUND PER NEC 300.17(B).
- D. ALL INTERIOR LIGHTING CIRCUITS TO BE WIRED THRU THE LIGHTING CONTROL RELAY. ALL EXTERIOR NON-EMERGENCY LIGHT FIXTURES AND EXTERIOR SIGNS SHALL BE CONTROLLED THROUGH PHOTOCELL AND LIGHTING CONTROL RELAYS. SEE SHEET E6.0.
- E. CONTRACTOR TO FIELD VERIFY CEILING TYPE AND PROVIDE PROPER MOUNTING HARDWARE.
- F. RECESSED FIXTURES INSTALLED IN AN INSULATED CEILING SHALL BE I.C. RATED. CONTRACTOR TO CONSULT WITH LIGHTING MANUFACTURERS TO PROVIDE U.L. LABELING TO REFLECT ACTUAL LAMP WATTAGE USED, NOT MAX FIXTURE WATTAGE.
- G.



1 120-VOLT, 20-AMP, 1-POLE WALL-SWITCH. PROVIDE COVERPLATE PER DECOR SPECIFICATIONS.

NOTES:
 CONTRACTOR TO VERIFY EXACT CONFIGURATION REQUIRED WITH SPACE AVAILABLE. PROVIDE LABELS AS DIRECTED BY OWNER. SWITCHES SHALL NOT BE MOUNTED HIGHER THAN 48".
 SWITCH 'GANGING' SHOWN FOR REFERENCE ONLY. CONTRACTOR TO DETERMINE (IN-FIELD) THE EXACT NUMBER OF GANGED SWITCHES ACCORDING TO TYPE OF SWITCHING USED AND DE-RATING FACTORS OF MULTIPLE DEVICES INSTALLED PER LOCAL N.E.C.
 SWITCHES PROVIDE A MANUAL CONTROL POINT (BETWEEN THE LIGHTING CONTACTOR AND LIGHTING FIXTURES).

SWITCH BANK DETAIL D

NO.	QTY	LOCATION	MFR / CATALOG NUMBER	DESCRIPTION	LAMP #	BALLAST TYPE	MOUNTING TYPE	HT.	VOLT	WATT	REMARKS
A	5	SITE LIGHT	LSI INDUSTRIES MRM-LED-18L-SIL-40-70CRI-H-BRZ	LED AREA LIGHTS FORWARD THROW, BRONZE FINISH	1	LED	POLE	20'-0"	120	150	PROVIDED WITH REAR HOUSING SHIELD DOUBLE HEAD
B	0	SITE LIGHT	LSI INDUSTRIES MRM-LED-18L-SIL-40-70CRI-BRZ	LED AREA LIGHTS FORWARD THROW, BRONZE FINISH	1	LED	POLE	20'-0"	120	300	
A6	5	SITE POLE	LSI INDUSTRIES 4SQB3-S07G-20-D180-BRZ	4" SQ 7 GA 20FT POLE D180	-	-	-	-	-	-	SEE CIVIL PLANS FOR POLE DETAILS
B1	6	KITCHEN	ELITE 24-FPL-BL-LED-4000L-DIM10-MVOLT-85	2x4 LED FLAT PANEL	-	LED	RECESSED GRID	-	120	39	
B1E	5	RR, OFFICE, & KITCHEN	ELITE 24-FPL-BL-LED-4000L-DIM10-MVOLT-85-0-EMG-LED-20W	2x4 LED FLAT PANEL	-	LED	EM RECESSED GRID	-	120	39	PROVIDED WITH INTEGRAL BATTERY PACK
B2	2	KITCHEN	ELITE 22-FPL-BL-LED-4000L-DIM10-MVOLT-85	2x2 LED FLAT PANEL	-	LED	NA RECESSED GRID	-	120	37.4	
B2E	6	KITCHEN	ELITE 22-FPL-BL-LED-4000L-DIM10-MVOLT-85-0-EMG-LED-20W	2x2 LED FLAT PANEL	-	LED	EM RECESSED GRID	-	120	37.4	PROVIDED WITH INTEGRAL BATTERY PACK
C1W	16	DINING	TCP: LED14DR5630K95 ELITE HOUSING: B6IC-AT-W	RECESSED LED DOWNLIGHT	1	LED	NA RECESSED DROP CLG	-	120	14	
C1WE	5	DINING	TCP: LED14DR5630K95 ELITE HOUSING: B6IC-AT-W	RECESSED LED DOWNLIGHT	1	LED	EM RECESSED DROP CLG	-	120	14	
C6W	8	DINING	TCP: LED14DR5630K95 ELITE HOUSING: E45180172	RECESSED LED DOWNLIGHT	1	LED	NA RECESSED HARD CLG	-	120	14	
D5	2	EXTERIOR SCIENCE	PROGRESS LTG - P5642-20 TOP COVER P5798-31	BRONZE 6" DOWN CYLINDER	1	SEE REMARKS	NA	ONT OF BRACKET AT 14" A.F.F.	120	18	(BULB) TCP L14PAR38 D30KFLW
E2	4	EXTERIOR	THOMAS & BETTS CAMLSDOB-CW	EXTERIOR EMERGENCY EGRESS FIXTURE	2	LED	NA UNIVERSAL	SEE KEY NOTES	120	18	UNSWITCHED HOT
E3	0	DINING	EVENLITE PW12-LC-V1-TB	BATTERY BACK-UP/ INVERTER	-	-	-	-	120	-	CONVERTS STANDARD FIXTURES TO EMER.
F6	3	HUB TABLE	BASELIGHT C01578EXT69INT/BLC25WINC MAX	HUB TABLE PENDANT	1	LED	NA PENDANT	VARIABLES	120	25	
F7	8	PERIMETER TABLE	HI-LITE: H2421-96-CB15-20WLB-60P1 TCP: LED10A19D0D27K (BULB)	12" GALVANIZED PENDANT	1	10W LED	NA PENDANT	6'-8" A.F.F.	120	10	
G1	VERIFY	EXTERIOR SLAT WALL	CONTECH #TLTO-12V-2-WW-16CR	OUTDOOR LED STRIP LIGHT	-	LED	NA	-	120	1.8/FT	BY SIGN VENDOR
G3	VERIFY	COLOR CHANGING LIGHT WALL	LED POWER #HB-40 W/ ACCESSORIES	DINING ROOM LED STRIP	1	LED	NA	-	120	96	
X1B	2	DINING	LIGHTALARMS QLXN500R-N, PW-08118-L	EXIT SIGN, LED UNIVERSAL MOUNT LED	-	-	-	CEILING	120	3	PENDANT MOUNT FIXTURE +9 A.F.F. TO BOTTOM
X1W	1	KITCHEN	LIGHTALARMS QLXN500R-N	EXIT SIGN, LED UNIVERSAL MOUNT LED	-	-	-	WALL	120	3	
WP1	1	EXTERIOR WALL	LUMARK (EATON) LDWP-FC-3B-120V	LED WALL PACK	1	LED	-	WALL 8'-6"	120	27	FULL CUTOFF DOOR


- NOTES:**
 1. CONTRACTOR TO CONSULT WITH LIGHTING MANUFACTURERS TO PROVIDE FIXTURE LAMPS & UL LABELING TO REFLECT ACTUAL LAMP WATTAGE USED, NOT MAX FIXTURE WATTAGE.
 2. RECESSED FIXTURES INSTALLED IN AN INSULATED CEILING SHALL BE I.C. RATED.

LIGHTING FIXTURE SCHEDULE C

1. UTILIZE TIMECLOCK CONTROLS FOR LIGHTING CIRCUITS. REFER TO E6.0 FOR ADDITIONAL INFORMATION.
2. FOR LIGHTING FIXTURES, CONDUIT, CONDUCTORS AND INSTALLATION RESPONSIBILITIES, REFER TO SCOPE OF WORK.
3. WALK-IN FIXTURE & SWITCH FACTORY INSTALLED WITH UNIT. CONTRACTOR TO COMPLETE CIRCUITING. PROVIDE LIQUID-TIGHT FLEXIBLE CONDUIT FOR CONDUCTORS. REFER TO GENERAL NOTE 'C'.
4. EXHAUST HOOD LIGHT FIXTURES SUPPLIED WITH HOOD AND MOUNTED IN PRE-WIRED J-BOX. COMPLETE CIRCUITING PER DETAIL E6.0.
5. COORDINATE J-BOX LOCATION WITH WOOD FRAMING SO IT REMAINS CONCEALED BEHIND FIXTURE. VERIFY MOUNTING HEIGHT WITH ARCH. DRAWINGS.
6. NOT USED.
7. C1WE FIXTURES WIRED THROUGH INVERTER E3 ON CIRCUIT B-4.
8. NOT USED.
9. REFER TO ARCHITECTURAL EXTERIOR ELEVATIONS ON A4.0 AND A4.1 FOR DIMENSIONED LOCATION OF FIXTURE.
10. LIQUID TIGHT FLEXIBLE CONDUIT TO FIXTURES. SEAL ALL ELECTRICAL CONDUITS INTO THE WALK-IN COOLER PER U.L. LISTING RECOMMENDATIONS.
11. ALERT LIGHT - ONLY APPLIES WHEN A GEN IV POWER SOAK IS USED. DISREGARD IF GEN III POWER SOAK IS USED. SEE SHEET E3.0 FOR POWER REQUIREMENTS.
12. MOUNT "E2" AT 6'-8" A.F.G. TO CENTER OF FIXTURE.
13. REFER TO DETAIL #B, SHEET E7.0. WIRE RESTROOMS AHEAD OF ANY LIGHTING CONTROL OR RELAY.
14. NOT USED.
15. NOT USED.
16. NOT USED.
17. PROPOSED SWITCH BANK LOCATION FOR LOCAL LIGHTING CONTROL (COORDINATE EXACT SWITCH BANK LOCATION WITH OWNER IN FIELD). CONTRACTOR TO PROVIDE SWITCH INDICATION AND LABEL FOR THEIR INTENDED USE. SEE SWITCHBANK DETAIL, THIS SHEET FOR MORE INFORMATION. VERIFY EACH THE LIGHTING AREA BEING CONTROLLED BY SWITCH BANK, IS WITHIN THE LINE OF SIGHT FROM THE CONTROLLING LOCATION. ANY 'CONTROLLED' LIGHTING IN AREAS, NOT WITHIN THE LINE OF SIGHT, FROM THE CONTROLLING DEVICE LOCATION, SHALL BE PROVIDED WITH WITH AN ANUNCIATOR DEVICE (E.G. WITH PILOT LIGHT), SO WHEN THE AREA BEING CONTROLLED IS LIT, THE CONTROLLING DEVICE IS ANNUNCIATED.
18. F6 FIXTURES TO BE MOUNTED FROM HUB TABLE CROSS BAR BY ELECTRICAL CONTRACTOR. COORDINATE PRE-DRILLED HOLES AND WIRING WITH FURNITURE VENDOR. FIXTURES TO BE HUNG AT STAGGERED LENGTHS DOWN FROM THE CROSS BAR. REFER TO ARCHITECTURAL DRAWINGS FOR INFORMATION. COORDINATE LENGTH WITH TACO BELL PROJECT MANAGER.
19. NIGHT LIGHT.
20. COORDINATE THE POSITION OF LIGHT FIXTURES WITH ARCHITECTURAL DRAWINGS.
21. FLUSH MOUNTED JUNCTION BOX WITH NEMA TYPE RECEPTACLE & COVER TO MATCH DECOR. MOUNT WITHIN 6" ABOVE OR 18" PROJECTION FROM WINDOW PER NEC 210.62. ROUTE CIRCUIT THROUGH RELAY PANEL FOR CONTROL.
22. NOT USED.
23. MOUNT "E2" AT 6'-10" A.F.G. TO CENTER OF FIXTURE.
24. PROVIDE NEW INVERTER. SEE LIGHTING FIXTURE SCHEDULE FOR INFORMATION. OPTIONAL MOUNTING CONFIGURATIONS THROUGH MANUFACTURER. INSTALL INVERTER AT A LOCATION TO MINIMIZE EXCESSIVE VOLTAGE-DROP ON CONDUCTORS. COORDINATE LOCATION WITH GENERAL CONTRACTOR. MAKE ALL FINAL CONNECTIONS.
25. CANOPY DOWN LIGHTS FURNISHED WITH CANOPY. MAKE FINAL CONNECTION.
26. J-BOX FOR CANOPY LIGHTS. VERIFY POINT OF CONNECTION. WIRE VIA EXTERIOR LIGHTING CONTRACTOR.
27. JUNCTION BOX MOUNTED IN INTERIOR SPACE, ABOVE ACCESSIBLE CEILING. ROUTE SECONDARY CONDUCTORS TO LOCATION DIRECTED BY SIGN VENDOR.
28. JUNCTION BOX MOUNTED ABOVE ACCESSIBLE CEILING. MOUNT TRANSFORMER TO JUNCTION BOX AND ROUTE SECONDARY CONDUCTORS TO LIGHT STRIP. G.C. TO VERIFY LED MOUNTING LOCATION.

LIGHTING PLAN 1/4"=1'-0" A

KEY NOTES B



- △ OWN/STATE COMMENTS 08.10.20
- △
- △
- △
- △


CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544



LIGHTING PLAN AND SCHEDULE

E4.0



PROVIDE 2" C.O. UNDERGROUND FOR FUTURE HIGH SPEED INTERNET. RUN TO ABOVE OFFICE CEILING.

2" C.O. FROM TELEPHONE COMPANY POINT OF CONNECTION (UNDERGROUND). INSTALL INSIDE REAR WALL AND EXTEND TO ABOVE KITCHEN CEILING LEVEL.

ENLARGED PLAN E3.1

	HOLD-UP BUTTON (SEE DETAILS C & D, SHEET E3.1)		DOOR CONTACT (LINKED TO AUDIO / VISUAL ALARM)
	MUSIC SYSTEM SPEAKERS		'SOUND ALERT' DEVICE
	SECURITY STROBE		KEYPAD (MOUNTED AT 48" A.F.F.)
	J-BOX		ALARM SIREN ABOVE CEILING
	2" x 4" J-BOX W/ DATA PORTS		BUMP PAD (MOUNT AT FRONT COUNTER)
	MOTION DETECTOR		HOOD FIRE SUPPRESSION SYSTEM PULL STATION
	OCCUPANCY SENSOR, CEILING MOUNTED. SEE DETAIL B / E7.0		TECH-IN-A-BOX
	DOOR CONTACT		

COMMUNICATIONS LEGEND **C**

- 1/2" CONDUIT WITH PULL STRING FOR HOLD-UP BUTTON SIGNAL WIRE TO SECURITY.
- ROUTE CONDUIT/CONDUCTORS THRU MILLWORK TO NEAREST FULL HEIGHT WALL TO STUB-UP. ROUTE CONDUIT TO AVOID OBSTACLES/EQUIPMENT IN MILLWORK.
- ELECTRICIAN TO INSTALL (1) OPEN DATA JUNCTION BOX IN VALANCE WALL. CONDUIT TERMINATED ABOVE CEILING TO HAVE BUSHING.
- ELECTRICIAN TO RUN (3) ORANGE CAT 6 LINES FROM NETWORK SWITCH TO DATE JUNCTION BOX. CAT6 LINES SHOULD HAVE BOTH ENDS PROPERLY TERMINATED WITH RJ-45 CONNECTORS. EXCESS CAT6 CABLE TO BE COILED INTO SERVICE LOOPS AT EACH END AND LEFT ACCESSIBLE FOR DMB INSTALL. TEAM. CAT6 TO BE RUN IN ACCORDANCE WITH ALL LOCAL MUNICIPALITY CODE REQUIREMENTS.

KEY NOTES **D**

- SUPPLY AND INSTALL OUTLETS AND CONDUIT FOR OWNER SUPPLIED AND INSTALLED CABLE AND LOW VOLTAGE WIRING (J.O.N.) TELEPHONE AND MUSIC SYSTEM WIRING SHALL BE SUPPLIED AND INSTALLED. SEE SCOPE OF WORK SHEETS.
- SEE SHEETS. E3.0 AND E3.1 FOR ELECTRICAL INFO ON POS, SECURITY SYSTEM, CCTV SYSTEM, (OFFICE) COMPUTER, DRIVE-THRU TIMER AND DRIVE-THRU COMMUNICATION SYSTEM.
- THIS PLAN INCLUDES CONDUITS AND J-BOXES FOR POS, SECURITY SYSTEM, CCTV SYSTEM, (OFFICE) COMPUTER, TELEPHONE SYSTEM, MUSIC SYSTEM, DRIVE-THRU TIMER AND DRIVE-THRU COMMUNICATION SYSTEM.
- ALL OUTLETS AND BOXES MOUNTED IN THE SERVING COUNTER CABINETRY ARE TO BE 24" AFF. INSTALL JUNCTION BOXES WITH CONDUIT UNDER CABINET TO NEAREST WALL AND TO ABOVE CEILING.

COMMUNICATIONS NOTES **E**

COM. #	EQUIPMENT ITEM	ELEVATION	REMARKS
H 01	UNDER COUNTER SECURITY BUTTON		INSTALL 3045 CTW PART. SEE DETAIL D/E3.1
H 02	WALL MOUNTED SECURITY BUTTON	+18" A.F.F.	2x4 J-BOX FLUSH MOUNTED IN WALK-IN WALL BY COOLER MANUFACTURER WITH 1/2" CONDUIT TO OUTSIDE OF COOLER NEAR KITCHEN CEILING. SECURITY SYSTEM INSTALLER TO INSTALL HOLD-UP BUTTON FACING DOWN AND RUN WIRING. SEE DETAIL G/E3.1
HM 02	D/T TIMER SIGNAL PROCESSOR J-BOX	+114" A.F.F.	4X4X4" DEEP (MIN.) J-BOX ABV. CLG. W/ (1) 1" CONDUIT TO HM-07B, (1) 1" CONDUIT TO HM-04, (1) 1-1/2" CONDUIT TO HM-08 & (1) 1" CONDUIT TO HM-12. SEE DET. G/E3.1.
HM 03	D/T BASE STATION J-BOX	+72" A.F.F.	4X4 J-BOX @ D/T BASE STATION W/ (1) 1-1/2" C TO HM-08 & (1) 1-1/2" C TO HM-07A. SEE DET. G/E3.1.
HM 04	D/T COMM SYSTEM J-BOX	+18" A.F.F.	4X8 J-BOX W/ (1) 1" CONDUIT TO HM-02, (1) 1" CONDUIT TO HM-07A, (1) 1" CONDUIT TO PICK-UP WINDOW D/T LOOP, AND (3) 1" CONDUITS TO D/T MENU BOARD. SEE DET. G/E3.1.
HM 07A	D/T TIMER DISPLAY J-BOX	+62" A.F.F.	2X4 J-BOX W/ (1) 1-1/2" CONDUIT TO HM-03 AND (1) 1" C TO HM-04. SEE DET. G/E3.1.
HM 07B	D/T TIMER DISPLAY J-BOX	+108" A.F.F.	2X4 J-BOX ABV. CEILING W/ (1) 1" CONDUIT TO HM-02. SEE DET. G/E3.1.
HM 08	D/T J-BOX	+96" A.F.F.	4X4X4" DEEP (MIN.) J-BOX W/ (1) 1-1/2" CONDUIT TO HM-03 & (1) 1-1/2" CONDUIT TO HM-02. SEE DET. G/E3.1.
HM 10	OCB SWITCH	+52" A.F.F.	2X4 J-BOX W/ (1) 1" CONDUIT TO ABOVE CEILING
HM 11	D/T CONTROL UNIT J-BOX	+108" A.F.F.	2X4 J-BOX ABV. CEILING W/ (1) 1" CONDUIT TO HM-12. SEE DET. G/E3.1.
HM 12	D/T ETHERNET SWITCH J-BOX	+114" A.F.F.	2X4 J-BOX ABV. CLG W/ (1) 1" CONDUIT TO HM-11, 1" CONDUIT TO HM-02, AND 1" CONDUIT TO OFFICE ROUTER
IR 01	IRRIGATION TIMER	+80" A.F.F.	4X4 J-BOX W/ 1" CONDUIT TO IRRIGATION VALVES.
M 01	RECESSED CEILING SPEAKERS, COLOR - BLACK	CEILING	SPEAKER WIRING FROM SPEAKERS IN DINING ROOM TO AMPLIFIER IN OFFICE.
M 03	MUSIC SYSTEM J-BOX	+60" A.F.F.	4X4 J-BOX & COVER W/ (1) 1/2" CONDUIT TO ABOVE CEILING FOR MUSIC SYSTEM. SEE SCOPE OF WORK.
O 01	(4) 1" DATA CONDUITS	U.G.	FROM MENU BOARD/SPEAKER POST TO ABOVE CEILING FOR OCB AND D/T COMM. SYST. SEE DET. C/E7.0.
P 02	KITCHEN MONITOR J-BOX	@ CLG.	2X4 J-BOX FLUSH @ CEILING. FOR M.A.P.S. LINE / DRIVE THRU MONITOR J-BOX.
P 04	BUMP PAD J-BOX	+24" A.F.F.	2X4 J-BOX W/ (1) 3/4" CONDUIT TO P-02
P 07	POS J-BOX W/ 2-1/2" DIA HOLE IN COVER PLATE	+24" A.F.F.	6X6X4" DEEP J-BOX W/ 2-1/2" CONDUIT IN WALL TO ABV. CEILING, WITH PULL STRING FOR POS.
S 01	J-BOX SECURITY SYSTEM	+48" A.F.F.	4X4 J-BOX AT SECURITY SYSTEM CONTROL PANEL W/ (1) 2" CONDUIT TO S-02.
S 02	J-BOX SECURITY SYSTEM	+106" A.F.F.	4X4 J-BOX ADJACENT TO T-02 W/ (1) 2" CONDUIT TO S-01.

COM. #	EQUIPMENT ITEM	ELEVATION	REMARKS
S 03	J-BOX SECURITY SYSTEM	+24" A.F.F.	2X4 J-BOX W/ (1) 1/2" CONDUIT TO ABV. CLG. FOR HOLD-UP BUTTON SIGNAL WIRE. SEE ELEVATION C/E3.1.
S 04	J-BOX SECURITY SYSTEM	+84" A.F.F.	2X4 J-BOX W/ COVER & (1) 1/2" CONDUIT TO ABOVE CEILING.
S 05	J-BOX SECURITY SYSTEM	+24" A.F.F.	2X4 J-BOX W/ 3/4" CONDUIT TO S-05 AND TO ABOVE CEILING.
S 06	J-BOX SECURITY SYSTEM	+48" A.F.F.	2X4 J-BOX W/ (1) 1/2" CONDUIT TO ABOVE CEILING FOR SECURITY SYSTEM KEYPAD.
S 07	J-BOX SECURITY SYSTEM	TOP OF JAMB	2X4 J-BOX W/ (1) 1/2" CONDUIT TO ABOVE CEILING FOR DOOR CONTACT.
S 08	'SOUND ALERT' DEVICE	CEILING	CONNECT TO SECURITY SYSTEM.
S 09	SECURITY STROBE LIGHT	CEILING	CONNECT TO SECURITY SYSTEM.
S 10	ALARM SIREN	ABV. CEILING	CONNECT TO SECURITY SYSTEM
S 11	MOTION / HEAT DETECTOR	+78" A.F.F.	STUB 1/2" CONDUIT. D5835 OR D5820. MOUNT 90" A.F.F. FOR OFFICE
S 12	J-BOX SECURITY DVR	+42" A.F.F.	2X4 J-BOX FOR SECURITY DVR.
T 01	TELEPHONE SERVICE BOX PER LOCAL TELEPHONE COMPANY. PROVIDE 24"X24"X3/4" PLYWOOD PANEL AT CLG. PROVIDE PULL STRING IN 2" CONDUIT.	+48" A.F.F.	PROVIDE (1) 25 PAIR TELEPHONE CABLE. ONLY (2) LINES TO BE USED. LINE ONE FOR VOICE/FAX. LINE (2) FOR COMPUTER MODEM.
T 02	SECURITY SYSTEM PHONE JACK	+106" A.F.F.	2X4 J-BOX ADJACENT TO S-02 W/ RJ-31X PHONE JACK.
T 03	VOICE LINE PHONE JACK	+42" A.F.F.	2X4 J-BOX W/ DOUBLE RJ-11 PHONE JACK & 1" CONDUIT TO ABOVE CEILING.
T 04	COMPUTER LINE PHONE JACK	+42" A.F.F.	2X4 J-BOX W/ RJ-11 PHONE JACK AND 1" CONDUIT TO ABOVE CEILING.
T 05	POS PHONE JACK	+24" A.F.F.	2X4 J-BOX W/ 1" CONDUIT TO ABOVE CEILING.
TV 01	CLOSED CIRCUIT TELEVISION (CCTV)		CCTV INSTALLATION IS BASED ON THE CRIME INDEX AS DETERMINED BY YUM! LOSS PREVENTION MANAGER. THE STANDARD CCTV PACKAGE WILL CONSIST OF (1) CCTV MONITOR W/ WALL BRACKET AND (1) MINI-DOME CAMERA MTD. TO BTM OF MENU BOARD BULKHEAD.
TV 02	SECURITY CAMERA	BULKHEAD/ CEILING	MINI-DOME CAMERA. 2X4 J-BOX W/ (1) 1/2" CONDUIT TO ABOVE CEILING (7 TOTAL).
V 01	ALTERNATE PAYMENT ROUTER BOX	+90" A.F.F.	4X4 J-BOX W/ 1/2" CONDUIT TO ABOVE CEILING FOR ETHERNET CABLES (DOUBLE JACK)
V 02	CREDIT CARD READER (VSAT)	+24" A.F.F.	2X4 J-BOX W/ 1/2" CONDUIT TO ABOVE CEILING FOR ETHERNET CABLES.

COMMUNICATIONS ROUGH-IN SCHEDULE **B**

△	OWN/STATE COMMENTS 08.10.20
△	
△	
△	
△	

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544


EXPLORER LITE
 MEDIUM40

COMMUNICATIONS PLAN

E5.0


ARCVISION
 INCORPORATED
 ARCHITECTURE • ENGINEERING • STORE PLANNING
 SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
 1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
 PH. (314) 415-2400 FAX (314) 415-2300
 www.arcv.com





FIELD WIRE OTHER
 THE PANEL ENCLOSURE IS RATED TYPE 1 TO PROTECT AGAINST TYPE 1 CONDUIT ENTRY HUBS
UL LISTED
 This panel is Listed to applicable UL Standards and requirements by UL. Field wiring of field components shall not be listed unless this mark.

- CONTACTORS**
- S1 SIGNS
 - S2 SIGNS
 - EL EXTERIOR LIGHTS
 - PL PARKING LOT LIGHTS
 - IL INTERIOR LIGHTS
 - MS MOTOR STARTER
 - MO MANAGERS OFFICE
- RELAYS**
- R1 RELAY #1
 - R2 RELAY #2
 - IR INTERLOCK RELAY
 - PCR PHOTOCELL RELAY
- MISCELLANEOUS**
- TC1 TIMELOCK #1
 - OC1 OCCUPANCY SENSOR #1
 - OC2 OCCUPANCY SENSOR #2
 - RS REMOTE SWITCH
 - PCB PHOTOCELL BYPASS SWITCH
 - OCS OPEN/CLOSED SWITCH
 - HS HOOD STAT
 - TDR TIME DELAY RELAY
 - PC PHOTOCELL



Taco Bell BMS Control Box

The intent of the BMS Control Box is to activate or deactivate the following:

- Kitchen Lighting
- Dining Room Lighting
- Exterior Lighting
- Exterior Signs
- Exhaust hood exhaust fan
- Exhaust hood lighting
- Make up air / replacement air fan
- Rest room / cook line exhaust fan
- Managers Office lighting & at least one duplex outlet

Sequence of Operation

Occupied Mode
 A Timeclock in the Control Box is programmed to place the building in Occupied mode 15 minutes before the first Team Member arrives on the premises. This allows power to proceed to the following:

- The photocell for the Parking Lot Lights and Open/Closed switch
- The restroom and cook line exhaust fan marked "EF-2"
- Light switches for the dining room lights

- The kitchen and rest room lights
- A timer relay for the exhaust hood motor starter marked "EF-1" and a relay (IR) for the make up air replacement air fan (evaporator fan) in RTU 1 and RTU 2.


The timer relay for the exhaust hood motor starter immediately activates motor starter EF-1 and relay IR. When activated, motor starter EF-1 continues to provide power to the exhaust hood exhaust fan. It also closes auxiliary contacts that turn on the exhaust hood lights. Activation of relay IR causes the contacts for RTU 1 and RTU 2 to close, returning 24 volts to the evaporator fan controller of each respective unit.

Occupied mode may also be invoked when optional Occupancy sensors and/or an Occupied switch located in the managers office is activated or placed in the Occupied position.

Unoccupied Mode

The Timeclock in the Control Box is programmed to place the building in "Unoccupied" mode at a time provided by Operations. This removes power for the following:


- Photocell for the Parking Lot Lights and the Open/Closed switch
- The Interior lights
- The R-1 relay





NOTE: PROVIDE TBCCB BY-PASS CONTROL FOR FIXTURE REQUIRING 24-HOUR OPERATION (E.G. EGRESS LIGHTING, EMERGENCY EQUIPMENT).

PROVIDE LOCAL CONTROL AS REQUIRED BY CODE.

CONTROL BOX
 Taco Bell's supplier of the Control Box is Air Care Experts.
 Combined Control Box is part of the lighting package.
 The Control Box includes the box and all components shown within the box and internal wiring between the components.
 Primary Contact: Chuck McCabe
 Phone: 949 770 2222
 Fax: 949 770 5885
 Email: CMCCABE@ACE-IAQ.COM



TACO BELL COMPONENT RELATIONSHIP



SUBPANEL LAYOUT

When in Unoccupied mode and upon a drop in temperature below 85 degrees in the exhaust hood, control voltage to the timer relay is dropped however the timer relay for the exhaust hood motor starter continues power to motor starter EF-1 and the relay (IR) for the make up air replacement air fan (evaporator fan) in RTU 1 and RTU 2 for fifteen minutes after the loss of power to the timer. Motor starter EF-1 continues to provide power to the exhaust hood exhaust fan. It also keeps closed the auxiliary contacts that turn on the exhaust hood lights. Power also continues to relay (IR) for the make up air replacement air fan (evaporator fan) in RTU 1 and RTU 2. After fifteen minutes without power to the timer, the timer opens contacts to EF-1 motor starter, the auxiliary hood lighting contacts and relay (IR) for the make up air replacement fan (evaporator fan) in RTU 1 and RTU 2. This drops power to the exhaust fan and the hood lights. Relay IR opens its contacts interrupting the 24 volts returned to RTU 1 and RTU 2 evaporator fan controllers. RTU 1 and RTU 2 evaporator fans may continue to operate if their respective zone controllers are calling for evaporator fan operation.

Any detection by the Occupancy sensor in the Managers office or the optional Remote Occupancy Sensor or the optional Remote Occupancy Switch will override the Timeclock and keep the building in OCCUPIED mode.

OPEN/CLOSED Automatic and Manual Operation
 An OPEN/CLOSED switch exists on the front panel of the Control Box. This switch has three positions. When in the Automatic position, a timeclock will activate the Signs and Exterior Lights, provided the Photocell has determined that it is dark enough outside for the lights to be on, at a time that has been programmed into the timeclock. A Team Member may place the OPEN/CLOSED switch in the Manual OPEN or Manual CLOSED position to override the timeclock operation of the Open mode or Closed mode.

Manual OPEN Mode
 When a Team Member places the OPEN/CLOSED switch in the Manual OPEN position it activates the Signs and Exterior Lights when the Photocell determines it is dark enough for the lights to be on. The store will remain in the OPEN operation until the switch is moved to either the CLOSED position or the Automatic timeclock operation.

Manual CLOSED Mode
 When a Team Member places the OPEN/CLOSED switch in the Manual CLOSED position it turns off the Signs and Exterior Lights. The store will remain in the CLOSED operation until the switch is moved to either the OPEN position or the Automatic timeclock operation.

External Operations Not Part Of The Control Box Operation But Required To Be Installed

The following operations should take place between the package units and various components:

- Control voltage for RTU 2 shall pass through contacts in the fire suppression system for the exhaust hood so that RTU 2 evaporator fan shuts down upon an activation of the fire suppressant into the hood. The system shall be wired directly between the fire suppression system and RTU 2.
- A remote smoke detector system featuring testing, annunciation and remote unit reset shall be installed in the manager's office for each RTU. The system shall be wired directly between each RTU and its respective testing, annunciation and reset device.

ARCVISION
 INCORPORATED
 ARCHITECTURE • ENGINEERING • STORE PLANNING
 SAINT LOUIS / DALLAS / LAS VEGAS / ORLANDO
 1950 CRAIG ROAD, SUITE 300 ST. LOUIS, MO 63146
 PH. (314) 415-2400 FAX (314) 415-2300 www.arcv.com



△	OWN/STATE COMMENTS 08.10.20
△	
△	
△	
△	

CONTRACT DATE: 8/26/19
 BUILDING TYPE: EXP. LITE MED40
 PLAN VERSION: MARCH 2018
 BRAND DESIGNER: DAN DICKSON
 SITE NUMBER: 314007
 STORE NUMBER: TBD

TACO BELL
 3615 BREMEN HWY
 MISHAWAKA, IN 46544

TACO BELL
 EXPLORER LITE
 MEDIUM40

ELECTRICAL DETAILS
E6.0

