



W-1 EXTERIOR SHEAR WALL

2x6 WOOD STUDS AT 16" O.C., SECURED TO SLAB.

1/2" EXTERIOR PLYWOOD SHEATHING AS SCHEDULED (SEE STRUCTURAL DRAWINGS). R-20 KRAFT-FACED FIBERGLASS BATT INSULATION.

1/2" INTERIOR PLYWOOD SHEATHING AS SCHEDULED (SEE STRUCTURAL DRAWINGS). SEE SHEETS A7.2, A8.0, A8.1, A8.2, A8.3 (INTERIOR FINISHES) / A4.0, A4.1, A4.2 (EXTERIOR FINISHES).

2x6 WOOD STUDS AT 16" O.C., SECURED SLAB. 1/2" EXTERIOR PLYWOOD SHEATHING AS SCHEDULED (SEE STRUCTURAL DRAWINGS).

R-20 KRAFT-FACED FIBERGLASS BATT INSULATION.

1/2" GYPSUM BOARD INTERIOR FINISH (TYPICAL FOR DINING ROOM WALLS). 1/2" PLYWOOD INTERIOR FINISH (TYPICAL FOR KITCHEN WALLS).

1/2" CEMENT BOARD INTERIOR FINISH (TYPICAL FOR RESTROOM WALL BEHIND WALL TILE AREA). 1/2" GYPSUM BOARD INTERIOR FINISH (TYPICAL FOR RESTROOM WALLS AT NON-TILED WALL AREA). SEE SHEETS A7.2, A8.0, A8.1, A8.2, A8.3 (INTERIOR FINISHES) / A4.0, A4.1, A4.2 (EXTERIOR FINISHES).

W-3 EXTERIOR TOWER WALL(SEE STRUCTURAL FOR ADDITIONAL DETAILS):

2X6 WOOD STUDS AT 16" O.C., SECURED TO SLAB

1/2" EXTERIOR PLYWOOD SHEATHING.

R-20 KRAFT FACED FIBERGLASS BATT INSULATION

2X6 FURRED WALL W/ 1/2" EXTERIOR PLYWOOD SHEATHING ON EXTERIOR SIDE

MINERAL WOOL INSULATION OR EQUAL TO BE FILLED IN FRAMING CAVITY

2" GYPUSM BOARD INTERIOR FINISH (TYPICAL FOR DINING ROOM WALLS) SEE WALL SECTIONS DETAIL A/A5.0 FOR MORE INFORMATION

SEE SHEETS A4.0, A4.1 FOR EXTERIOR FINISHES.

EXTERIOR WALL WITH 20 GA. S.S. PANEL BEHIND HOOD. EXTEND MIN. 18" BEYOND END OF HOOD. 550S162-43 MTL STUDS AT 16" O.C. SECURED TO SLAB W/ 5/8" DENSGLASS SHEATHING ON THE EXT. OF FRAMING W/ WALL PANEL FINISH RE: A4.0 FOR FINISH SCHEDULE

ON INSIDE OF FRAMING PROVIDE 1/2" CEMENT BOARD

FULL HEIGHT RE: A5.2 FOR WALL SECTION

2x4 (2x6 WHERE NOTED) WOOD STUDS AT 16" O.C., SECURED TO SLAB.

1/2" CEMENT BOARD TO 6" A.F.F., BOTH SIDES.

1/2" GYPSUM BOARD FROM TOP OF CEMENT BOARD TO 2" ABOVE CEILING (DINING ROOM SIDE). 1/2" PLYWOOD FROM TOP OF CEMENT BOARD TO 2" ABOVE CEILING (KITCHEN SIDE). SEE SHEETS A7.2, A8.0a, A8.0b, A8.1, A8.2, A8.3 (INTERIOR FINISHES).

2x4 (2x6 WHERE NOTED) WOOD STUDS AT 16" O.C., SECURED TO SLAB.

3-1/2" UN-FACED SOUND BATT INSULATION, FULL HEIGHT of FINISHED WALL 1/2" CEMENT BOARD FULL HEIGHT BEHIND WALL TILE AREA; 1/2" GYPSUM BOARD AT NON-TILED

WALL AREAS (RESTROOM SIDE).

1/2" CEMENT BOARD TO 6" A.F.F. (KITCHEN / DINING ROOM / OFFICE SIDE). 1/2" GYPSUM BOARD FROM TOP OF CEMENT BOARD TO 2" ABOVE CEILING (DINING ROOM SIDE). 1/2" PLYWOOD FROM TOP OF CEMENT BOARD TO 2" ABOVE CEILING (KITCHEN / OFFICE SIDE).

WALL TYPES

2x6 WOOD STUDS AT 16" O.C., SECURED TO SLAB.

½" PLYWOOD FROM TOP OF CURB TO 2" ABOVE CEILING; ONE SIDE. SEE SHEETS A7.2, A8.0a, A8.0b, A8.1, A8.2, A8.3 (INTERIOR FINISHES).

SEE SHEETS A7.2, A8.0a, A8.0b, A8.1, A8.2, A8.3 (INTERIOR FINISHES).

NOTE: REFER TO WALL BASE DETAILS, SHEET A6.2.

A. ALL DIMENSIONS ARE FROM INSIDE FACE OF CURB TO FACE OF STUD. REFER TO FOUNDATION PLAN FOR FACE OF CURB DIMENSIONS. SEE KEYNOTE 1. THIS SHEET. B. DIMENSIONS NOTED AS "CLEAR" OR "HOLD" ARE MIN. REQ'D. NET CLEARANCE FROM FACE OF WALL FINISH. C. VERIFY FINAL EQUIPMENT SIZES W/ VENDOR PRIOR TO INT. WALL FRAMING.

A. SEE SHEET A1.1 FOR WINDOW TYPES AND DOOR SCHEDULE. B. ALL DOOR AND WINDOW OPENING DIMENSIONS ARE TO ROUGH OPENING.

FINISH SUBSTRATES:

A. PROVIDE 1/2" THICK CEMENT BOARD FROM FLOOR SLAB TO 6" A.F.F., U.N.O. B. ALL JOINTS, GAPS OR SPACES LEADING TO ALL HOLLOW OR INACCESSIBLE SPACES SHALL BE SEALED WITH

"NSF INTERNATIONAL" APPROVED SEALANTS. C. ALL BACK OF HOUSE AND OFFICE WALLS SHALL HAVE 1/2" CDX PLYWOOD SUBSTRATE, U.O.N. D. PROVIDE SOLID BLOCKING FOR WALL SUPPORTED ITEMS.

A. SEE A2.0 FOR SEATING PLAN AND DETAILS. B. SEE A7.0 FOR FLOOR FINISHES.

C. SEE A8.0, A8.1, A8.2, A8.3 FOR WALL FINISHES. D. SEE A7.1 FOR CEILING FINISHES.

A. PROVIDE THREE FIRE EXTINGUISHERS - (2) 10 lb. BC and (1) 10 lb. ABC - TO COMPLY WITH LOCAL FIRE CODE. LOCATE PER DIRECTION OF FIRE MARSHALL OR LOCAL AUTHORIZING AGENT. B. DRAWINGS ARE BASED UPON WOOD FRAMING. UTILIZATION OF METAL STUDS ON NON-BEARING INTERIOR

FLOOR PLAN NOTES

PARTITIONS, BULKHEADS AND SOFFITS IS ACCEPTABLE. C. ALL ATTACHMENTS MADE THROUGH E.I.F.S. SHALL BE BUSHED TO PREVENT DAMAGE TO THE FINISH.

SEE DETAIL 9 / A6.2. D. ALL PENETRATIONS THROUGH E.I.F.S. SHALL BE SEALED USING MFR'S. APPROVED METHOD. E. COORDINATE FRAMING ABOVE CEILING WITH HVAC DUCT WORK.

F. SEE SHEET A8.1 FOR ENLARGED RESTROOM AND OFFICE PLAN.

STARTING POINT: ALL SUB-TRADES SHALL USE THIS POINT OF (11) 8" x 12" HORIZONTAL OPENING FOR SYRUP TUBES. ORIGIN FOR LAY-OUT (INSIDE CORNER OF CONCRETE CURB). INSIDE FACE OF CURB TO FACE OF CURB DIMENSIONS: > 26'-9" (SIDE to SIDE).

2 CUSTOMER COUNTER KNEE-WALL BY G.C.

> 66'-5" (FRONT to BACK).

- SEE PLAN and SECTION, SHEET A6.1.
- (3) PIPE BOLLARD. REFER TO SITE DRAWINGS. COORDINATE WITH LOCATION OF GAS METER. 4 HOOD WALL, SEE WALL LEGEND. COORDINATE WITH HOOD LOCATION; SEE SHEET M2.0. REFER TO COOK LINE ELEVATION, 15
- SHEET A8.2 and HOOD SECTIONS 4 and 12, SHEET M3.0. 5 ELECTRICAL MAIN SWITCH BOARD. REFER TO ELECTRICAL
- DRAWINGS. 6 CO2 FILL BOX LOCATION.
- 7 METAL THRESHOLD.

D

- 8 GATE WITH PANIC HARDWARE
- 9 ELECTRICAL PANELS; REFER TO ELECTRICAL DRAWINGS.
- (10) SYRUP / FILTERED WATER TUBE BUNDLES IN CHASE WALL.

COORDINATE WALL OPENING with DRINK STATION EQUIPMENT SUPPLIER. SEE DETAIL 4 / A6.3. REFER TO ELEVATION 1 / A8.0 and 5 / A8.2.

FLOOR PLAN 1/4"=1'-0" A

- (12) PROVIDE HORIZONTAL DOOR SWEEPS AT ALL EXTERIOR DOORS. SEE SHEET A1.1.
- (13) COORDINATE WALL CLEARANCE WITH MOP SINK DIMENSIONS; SEE SHEET A2.0. REFER TO EQUIPMENT CUT SHEETS PROVIDED ON PLANS.YUM.COM WEBSITE.
- 14 GAS METER
- S.S. CORNERGUARD / WALL CAP. TYPICAL AT ALL CORNERS FROM REAR WALL TO KITCHEN SIDE OF SERVICE COUNTER. SEE DETAIL 10 / A6.3
- PROVIDE CLOSURE STRIPS W/ BACKER ROD AND SEALANT BETWEEN COLD STORAGE BOX AND ADJACENT WALL SURFACES. DISCONTINUE WALL COVERING BEHIND BOXES.
- 17 EXTERIOR FENCE BY OTHERS
- 18 TANKLESS WH SYSTEM SEE MEP DRAWINGS

KEY NOTES



Digitally signed by Harold Hutter DN: c=US, o=Unaffiliated, ou=A01410C000001734EB2BCC F00000303, cn=Harold Hutter Date: 2022.03.31 15:16:29 -04'00'

HAROLD DANIEL HUTTER III

FL. REG. AR98913
PLAN SET REVISIONS:
\triangle
Ι Λ

CONTRACT DATE

Kb 30-19

2018.A

BUILDING TYPE: PLAN VERSION:

SITE NUMBER: **ENTITY NUMBER:**

STORE NUMBER: LIS PROJECT; 2019-304

KFC

3615 W SILVER SPRINGS BLVD. OCALA, FL



FLOOR PLAN

В